Viewsonic VG Series VG2755 LED display 68.6 cm (27") 1920 x 1080 pixels Full HD Black

Brand : Viewsonic

Product family: VG Series

Product code: VG2755

Product name : VG2755

- USB Type-C

- Full HD 1080p resolution
- Frameless bezel

- SuperClear® IPS technology

- VGA, HDMI and DisplayPort inputs

27" IPS LED, FHD, 60Hz, 16:9, 250 cd/m², 1000:1, 16.7M, 5 ms, 178/178, 2W x2, Display Port, HDMI, USB 3.1, 100-240 VAC, 50/60 Hz, 5.1 kg

Viewsonic VG Series VG2755. Display diagonal: 68.6 cm (27"), Display resolution: 1920 x 1080 pixels, HD type: Full HD, Display technology: LED, Response time: 5 ms, Native aspect ratio: 16:9, Viewing angle, horizontal: 178°, Viewing angle, vertical: 178°. Built-in speaker(s). Built-in USB hub, USB hub version: 3.2 Gen 1 (3.1 Gen 1). VESA mounting, Height adjustment. Product colour: Black









Display		Ports & interfaces	
Display diagonal * Display resolution * HD type * Native aspect ratio * Display technology * Panel type * Backlight type Touchscreen *	68.6 cm (27") 1920 x 1080 pixels Full HD 16:9 LED AH-IPS W-LED X	DisplayPorts quantity DisplayPort version Audio input Headphone out * HDCP AC (power) in Ergonomics VESA mounting *	1 1.2 × × ×
Display brightness (typical) Response time Anti-glare screen Screen shape * Supported graphics resolutions Contrast ratio (typical) * Contrast ratio (dynamic) Maximum refresh rate *	250 cd/m ² 5 ms ✓ Flat 720 x 400, 800 x 600 (SVGA), 854 x 480 (WVGA), 1024 x 768 (XGA), 1280 x 1024 (SXGA), 1440 x 900 (WXGA+), 1680 x 1050 (WSXGA+), 1920 x 1080 (HD 1080) 1000:1 50000000:1 60 Hz	Panel mounting interface Cable lock slot * Cable lock slot type Height adjustment * Height adjustment Pivot Pivot angle Swivelling Swivel angle range Tilt adjustment	100 x 100 mm ✓ Kensington ✓ 13 cm ✓ 0 - 180° ✓ 0 - 120° ✓
Viewing angle, horizontal Viewing angle, vertical Display number of colours * Pixel pitch Horizontal scan range Vertical scan range Viewable size, horizontal Viewable size, vertical Display diagonal (metric)	178° 178° 16.78 million colours 0.311 x 0.311 mm 15 - 82 kHz 24 - 75 Hz 59.8 cm 33.6 cm 68.58 cm	Tilt angle range On Screen Display (OSD) Number of OSD languages Plug and Play Power Energy efficiency class (SDR) * Energy consumption (SDR) per 1000 hours * Power consumption (typical) *	-5 - 40° 14 2 D 16 kWh 19.1 W
Colour depth	6 bit	Power consumption (standby) *	0.3 W

<table-container>pippingpercent set or sound prior (%)percent set or sound prior (%)of A (%)NIDA G-SYNC*XNore consumption (%)1.0 × (%)NIDA G-SYNC*XNore consumption (%)1.0 × (%)MUDA G-SYNC*XParting temporation (%)1.0 × (%)MUDA G-SYNC*XParting temporation (%)1.0 × (%)MUDA G-SYNC*XParting temporation (%)1.0 × (%)NUB G-SYNC*XParting temporation (%)1.0 × (%)Multing temporation (%)XNore (%)2.0 × (%)Multing space (%)XNore (%)2.0 × (%)Multing space (%)XNore (%)XXMulting space (%)XXXXMulting space (%)XXXXMulting space (%)XXXX<th></th><th></th><th></th><th></th></table-container>				
Performance Power consumption (PowerSave) 13 W NVIDIA G-SYNC* X AC input voltage 100 - 240 V AMD FreeSynC* X Cinput frequency 50 - 60 Hz InterestynC* X Operational conditions Vertext InterestynC* Y Operating temperature (T-T) 0 - 40 °C Mutimedia Operating temperature (T-T) 0 - 40 °C Built-in camera* Y Actain included ✓ Number of speakers 2 Cables included ✓ Market positionins * Y Stand included ✓ Market positionins * Graphics design Weight 6 dimensions ✓ Product colour* Black Pepth (with stand) 612 mm Product colour* Black Weight (with stand) 612 mm Product colour* Black Weight (with stand) 612 mm Country of origin ✓ Height (with stand) 612 mm Country of origin ✓ Height (without stand) 612 mm Certification ✓	Display		Power	
AC input voltage100 - 240 VAMD FreeSync*XAMD FreeSync*XFicker-free technology✓Uow Blu Light technology✓WultimediaOperating temperature (T-1)Built-in speaker(S)*✓Mutimedia✓Built-in speaker(S)*✓More Speaker(S)*✓Market positioning*✓Stand included✓Market positioning*Graphics designMarket positioning*Graphics designProduct colour*BlackBlackDepth (with stand)Product colour*BlackPertor of originChinaPertor of originChinaCountry of originChinaCurtificationSize (Energy)Prots & InteracesVNumber of Stype-B upstreemVPorts furtheracesSize (Energy)Built-In USB hub*✓VerificationSize (Energy)Ports GuartineSize (Energy)Built-In USB hub*✓VSB Type-A downstreem port typeUSB Type-B, USB Type-CNumber of USB Type-C downstream ports quantity1USB Type-C d	NTSC coverage (typical)	72%	Power consumption (off)	0.3 W
NNDR ASYNC*KA clinput frequency50-60 HzFlicker-free technologyIOperational conditionsFlicker-free technologyIOperating temperature (T.T)0-40 °CMulteriest technologyIOperating temperature (T.T)0-40 °CMultino Bile Light technologyIStand IncludedIBuilt-in came 3IStand IncludedISuilt-in came 3IStand IncludedINumber of speakers2Stand IncludedINumber of speakersIStand IncludedIMarket positioning *Graphics designVidth with stand)202 nmProduct colourBlackDepth (with stand)202 nmProduct colourBlackDepth (with stand)25 smProduct colourBlackDepth (with stand)53 smCertificationISCWight (with stand)SizemaCurtify of originChinaHeight (with stand)SizemaCurtificationISCWight (with stand)SizemaDisto EnergyMight (with stand)SizemaSizemaBuilt-in USB hub **ISizemaSizemaSize stand in Clude SizemaSizemaSizemaDisto EnergyMight (with stand)SizemaSize stand in clude SizemaSizemaSizemaCurtificationSizemaSizemaDisto EnergyMight (with stand)SizemaSize stand in clude SizemaSizemaSizemaSize stand in clude SizemaSizema<	Performance		Power consumption (PowerSave)	13 W
AND FreeSync*AC input frequency50 - 60 HzPicker-free technology✓ Operation conditions Ficker-free technology✓Operating temperature (TM)0 - 0%Low Blue Light technology✓Operating temperature (TM)0 - 0%Mutimedia✓Operating tentive humidity (H-H)20 - 0%Built-in speaker(s) *✓ Packaging content ✓Built-in speaker(s) *✓Stand included✓Ms rated power✓Quick start guide✓Ms rated powerGraphics designWith (with stand)612 mmProduct colour *BlackDepth (with stand)533 mmProduct colour *BlackDepth (with stand)533 mmProduct colour *BlackDepth (with stand)52 mmDetachable stand✓Vidith (without stand)612 mmFreet colourBlackDepth (without stand)52 mmCountry of originChinaHeight (without stand)62 mmCurtification✓Package guidh303 mmNumber of USS Type-E, IJCESO03, MX-Coc Built-in USB hub *✓Package guidh620 mmUSB hub versionJ. 2 Gen 1 (3.1 Gen 1)Package weight310 mmUSB hub versionJ. 2 Gen 1 (3.1 Gen 1)Package keight10.7 kgUSB hub versionJ. 2 Gen 1 (3.1 Gen 1)Package keight10.7 kgUSB Type-C downstream port yeu auntityJ. SecondSocondSocondUSB Type-C downstream port yeu auntityJ. SecondS	NVIDIA G-SYNC *	*	AC input voltage	100 - 240 V
Filcker-free technology Image: space s			AC input frequency	50 - 60 Hz
Low Blue Light technologyI operating temperature (T-T) Operating relative humidity (H-H)0 - 40 °C 20 - 90%MuttimediaI operating relative humidity (H-H)20 - 90%Built-in speaker(s)I operating relative humidity (H-H)20 - 90%Built-in speakersI operating relative humidity (H-H)I operating relative humidity (H-H)20 - 90%Market positioning operating speakersI operating relative humidity (H-H)I operating relative humidity (,	v	Operational conditions	
MultimediaOperating relative humidity (H-H)20-90%Built-in speaker(s)*Built-in camera *XStand includedBuilt-in camera *XStand includedNumber of speakers2Cables includedRMS rated power4Quick start guideDesignWattQuick start guideMarket positioning *Graphics designWidth (with stand)512 mmProduct colour *BlackDepth (with stand)533 mmFrameless designVidth (with stand)5.5 kgPeter colourBlackWeight (with stand)5.2 kgDetachable standYCourty of originChinaHeight (without stand)5.2 mmCertificationChinaHeight (without stand)5.1 kgDist bub *S.2 Gen 1(3.1 Gen 1)YYUSB hub version3.2 Gen 1(3.1 Gen 1)Package weight3.0 mmUSB hub version3.2 Gen 1(3.1 Gen 1)Package weight10.7 kgUSB hub *AAcage weight10.7 kgUSB Type-A downstream port yeAcage weight10.7 kgUSB Type-A downstream port yeAcage weight10.7 kgUSB Type-A downstream ports quantity1Statinability certificatesStoed9USB Type-A downstream ports quantity1Acage weight3.6049USB Type-A downstream ports quantity1StoedpaceStoedpaceUSB Type-A downstream ports quantity			Operating temperature (T-T)	0 - 40 °C
Built-in camera*XStand included✓Number of speakers2Cables includedAC, DisplayPort, USBRMs rated power4 WQuick start guide✓DesignVeright & dimensions612 mmProduct colour *BlackDepth (with stand)612 mmProduct colour *BlackDepth (with stand)202 mmFrameless design✓Height (with stand)533 mmFront bezel colourBlackDepth (with stand)512 mmPottect colour *BlackDepth (with stand)612 mmFrameless design✓With (with stand)52 mmCountry of originChinaHeight (without stand)622 mmCertificationCTUVus, FCC-B, ICES003, MX-Cor, Mexico EnergyPackage width692 mmBuilt-in USB hub*✓Package depth430 mmUSB hub version3.2 Gen 1 (3.1 Gen 1) Package veight218 mm218 mmUSB type-A downstream ports quantity1Sustainability certificatesSico49USB Type-A downstream ports quantity1Sustainability (EREL) code Energy Labelling (EREL) codeSico49VSB Type-C downstream ports quantity1Gogitsc dataSico49VSB Type-C downstream ports quantity1Gogitsc dataSico49VSB Type-C downstream ports quantity1Gogitsc dataSico49VSB Type-C downstream ports quantity1Gogitsc dataSico49Vi portXAASico49V	Multimedia			20 - 90%
Number of speakers2Cables includedAC, DisplayPort, USBRNS rated power4 WQuick start guide✓DesignWeight & dimensionsCables includedMarket positioning *Graphics designWidth (with stand)612 nmMarket positioning *BlackDepth (with stand)202 nmS33 nmFrameless design✓Depth (with stand)533 mmFront bezel colourBlackWidth (with stand)512 nmDetachable stand✓Width (with stand)52 nmCountry of originI BackDepth (with stand)52 nmCountry of originKinaDepth (with stand)52 nmCertificationWidto EnergyWeight (without stand)52 nmBuilt-in USB hub *✓Package depth51 kgNumber of USB Type-Bustream quantity✓Package depth430 nmUSB hub version3.2 Gen 1 (3.1 Gen 1) Package depthPackage depth430 nmUSB hub version3.2 Gen 1 (3.1 Gen 1) Package depthPackage depth400 nmUSB Type-A downstream ports quantity1Package depth50649USB Type-C downstream ports quantityAStatinability certificateaStotinability certificateaUSB Type-C downstream ports quantityAStotinability certificateaStotinability certificateaUSB Type-C downstream ports quantityAAStotinability certificateaStotinability certificateaUSB Type-C downstream ports quantityAAStotinabil	Built-in speaker(s) *	4	Packaging content	
RMS rated power4 WQuick start guide< ADesignGraphics designWight & dimensions612 mmMarket positioning*Graphics designWidth (with stand)612 mmProduct colour*BlackDepth (with stand)202 mmFrameless designHeight (with stand)533 mmFront bezel colourBlackWeight (with stand)512 mmDetachable standWidth (without stand)612 mmFeet colourBlackDepth (without stand)52 mmCountry of originChinaHeight (without stand)52 mmCertificationChinaHeight (without stand)51 kgBuilt-in USB hub*Package depth430 mmUSB type-RownPackage depth430 mmUSB hub version3.2 Gen 1 (3.1 Gen 1)Package depth430 mmUSB type-A downstream ports quantity1Satainability certificatesENERGY STAR, RoHSUSB Type-C downstream ports quantity1Sustainability certificatesENERGY STAR, RoHSUSB Type-C downstream ports quantity1Sustainabilit	Built-in camera *	×	Stand included	1
RMS rated power4 WQuick start guide< ADesignGraphics designWight & dimensions612 mmMarket positioning*Graphics designWidth (with stand)612 mmProduct colour*BlackDepth (with stand)202 mmFrameless designHeight (with stand)533 mmFront bezel colourBlackWeight (with stand)512 mmDetachable standWidth (without stand)612 mmFeet colourBlackDepth (without stand)52 mmCountry of originChinaHeight (without stand)52 mmCertificationChinaHeight (without stand)51 kgBuilt-in USB hub*Package depth430 mmUSB type-RownPackage depth430 mmUSB hub version3.2 Gen 1 (3.1 Gen 1)Package depth430 mmUSB type-A downstream ports quantity1Satainability certificatesENERGY STAR, RoHSUSB Type-C downstream ports quantity1Sustainability certificatesENERGY STAR, RoHSUSB Type-C downstream ports quantity1Sustainabilit	Number of speakers	2	Cables included	AC, DisplayPort, USB
Market positioning*Graphics designWidth (with stand)612 mmProduct colour *BlackDepth (with stand)202 mmFrameless design✓Height (with stand)533 mmFront bezel colourBlackWeight (with stand)7.5 kgDetachable stand✓Width (without stand)612 mmFreet colourBlackDepth (without stand)622 mmCountry of originChinaDepth (without stand)52 mmCertificationChinaHeight (without stand)52 mmPorts & interfacesYWeight (without stand)5.1 kgBuilt-in USB hub *✓Packaging dataUSB hup version3.2 Gen 1 (3.1 Gen 1)Package height218 mmUSB type-B upstream port typeUSB Type-B, USB Type-CPackage keight10.7 kgNumber of USB Type-B, downstream ports quantity1Sutainability certificatesENERGY STAR, RoHSUSB Type-C downstream ports quantity1Sutainability (EPREL) code350(49)USB Type-C downstream ports quantity1IIUV portXIIIHDMI *✓IIIHDMI *IIIIHDMI *IIIIHDMI *IIIIHDMI *IIIIHDMI *IIIIHDMI *IIIIHDMI *IIIHDMI *	RMS rated power	4 W	Quick start guide	1
Product colour *BackDepth (with stand)202 mmFrameless design✓Height (with stand)533 mmFront bezel colourBlackWeight (with stand)7.5 kgDetachable stand✓Width (without stand)612 mmFeet colourBlackDepth (with out stand)52 mmCountry of originChinaHeight (without stand)362 mmCountry of originChinaWeight (without stand)5.1 kgCountry of originChinaHeight (without stand)5.1 kgPorts 6 interfacesVWeight (without stand)5.1 kgBuilt-in USB hub *✓Package depth430 mmUSB hub version3.2 Gen 1 (3.1 Gen 1)Package depth430 mmUSB hub restorn1Package veright10.7 kgUSB Stype-A downstream port typeUSB Type-B, USB Type-CPackage veright10.7 kgVeright (Without stand)1ScalanabilityStatianability CertificatesSNEGY STAR, RoHSUSB Type-C downstream ports quantity1Sustainability CertificatesSNEGY STAR, RoHSSustainability CertificatesSico49Sico49Sico49VGA (D-sub) ports quantity1Immenized System (HS) codeSizo210ViportXMemonized System (HS) codeSizo210HDMI *✓Immenized System (HS) codeSizo210	Design		Weight & dimensions	
Frameless designImage: stand service of the sta	Market positioning *	Graphics design	Width (with stand)	612 mm
Front bezel colourBlackWeight (with stand)7.5 kgDetachable stand✓Widht (with stand)612 mmDetachable stand✓Depth (without stand)52 mmFeet colourBlackDepth (without stand)362 mmCountry of originChinaHeight (without stand)362 mmCertificationCTUVus, FCC-B, ICES003, MX-Coc Mexico EnergyWeight (without stand)5.1 kgPots únterfacesBuilt-in USB hub *✓Package width692 mmSublit-in USB hub *✓Package depth430 mmUSB upstream port typeUSB Type-B, USB Type-CPackage depth430 mmNumber of USB Type-B upstream quantity1Package typeBoxUSB Type-A downstream ports quantity1Sustainability certificatesENERGY STAR, RoHSUSB Type-Coloustify1European Product Registry for energy Labelling (EPREL) codeStatianabilityVGA (D-Sub) ports quantity1Listen StateStatianabilityVI portXListen StateStatianability CertificatesStatianabilityVI portXListen StateStatianability CertificatesStatianabilityVI portXListen StateStatianability CertificatesStatianabilityVI portXListen StateStatianability CertificatesStatianabilityHDMI *✓IListen StateStatianability CertificatesStatianabilityListen StateMice StateHarmonized System (HS) code </td <td>Product colour *</td> <td>Black</td> <td>Depth (with stand)</td> <td>202 mm</td>	Product colour *	Black	Depth (with stand)	202 mm
Detachable standImage: stand	Frameless design	4	Height (with stand)	533 mm
Feet colourBlackDepth (without stand)52 mmCountry of originChinaHeight (without stand)362 mmCertificationCTUVus, FCC-B, ICES003, MX-Coc Mexico EnergyWeight (without stand)5.1 kgPackaging dataPackaging dataPackage width692 mmBuilt-in USB hub*Image width92 mmUSB hub*Image width692 mmUSB hub*Image width107 kgUSB Type-B upstream ports quantityUSB Type-B, USB Type-CPackage weight10.7 kgNumber of USB Type-B upstream ports quantityImage weight10.7 kgImage weightUSB Type-A downstream ports quantityImage weightImage weightImage weightUSB Type-C downstream ports quantityImage weightImage weightImage weight <td>Front bezel colour</td> <td>Black</td> <td>Weight (with stand)</td> <td>7.5 kg</td>	Front bezel colour	Black	Weight (with stand)	7.5 kg
Country of originChinaHeight (without stand)362 mmCertificationCTUVus, FCC-B, ICES003, MX-CoC, Mexico EnergyHeight (without stand)5.1 kgPorts & interfacesPackaging dataBuilt-in USB hub *Package width692 mmBuilt-in USB hub *Package depth430 mmUSB hub version3.2 Gen 1 (3.1 Gen 1)Package depth218 mmUSB upstream port typeUSB Type-B, USB Type-CPackage weight10.7 kgNumber of USB Type-B upstream ports quantity1Package typeBoxUSB Type-A downstream ports quantity1Sustainability certificatesENERGY STAR, RoHSUSB Type-C downstream ports quantity1European Product Registry for Energy Labelling (EPREL) code356049VGA (D-Sub) ports quantity1Logistics dataSustainability certificates85285210VI portXHarmonized System (HS) code85285210HDMI *1IIIHDMI ports quantity1IIHDMI ports quantity1IHDMI ports quantity1 </td <td>Detachable stand</td> <td>1</td> <td>Width (without stand)</td> <td>612 mm</td>	Detachable stand	1	Width (without stand)	612 mm
Certification CTUVus, FCC-B, ICES003, MX-CoC, Mexico Energy Weight (without stand) 5.1 kg Ports & interfaces Packaging data Packaging data Package width 692 nm Built-in USB hub * Package depth 430 nm 92 nm USB hub version 3.2 Gen 1 (3.1 Gen 1) Package depth 430 nm 92 nm USB hub version USB Type-B, USB Type-B, USB Type-C Package weight 10.7 kg Number of USB Type-B upstream port squantity 1 Package type Box USB Type-A downstream ports quantity 1 Sustainability certificates ENERGY STAR, RoHS USB Type-C downstream ports quantity 1 Sustainability certificates ENERGY STAR, RoHS USB Type-C downstream ports quantity 1 Logistics data Statianability certificates ENERGY STAR, RoHS VISA (D-Sub) ports quantity 1 Logistics data Statianability certificates ENERGY STAR, RoHS VISA (D-Sub) ports quantity 1 Logistics data Statianability certificates ENERGY STAR, RoHS VISA (D-Sub) ports quantity 1 Logistics data Statianability certificates Statianability certificates Statianability cer	Feet colour	Black	Depth (without stand)	52 mm
CertificationMexico EnergyPackaging dataPorts & interfacesPackage width692 mmBuilt-in USB hub *Package depth430 mmUSB hub version3.2 Gen 1 (3.1 Gen 1)Package height218 mmUSB upstream port typeUSB Type-B, USB Type-CPackage weight10.7 kgNumber of USB Type-B upstream ports quantity1Package typeBoxUSB Type-A downstream ports quantity3SustainabilityENERGY STAR, RoHSUSB Type-C downstream ports quantity1European Product Registry for 	Country of origin	China	Height (without stand)	362 mm
Ports & interfacesPackaging dataBuilt-in USB hub *Built-in USB hub *USB hub version3.2 Gen 1 (3.1 Gen 1)Package depth430 mmUSB upstream port typeUSB Type-B, USB Type-CPackage height218 mmNumber of USB Type-B upstream ports quantity1Package typeBoxUSB Type-A downstream ports quantity3SustainabilityENERGY STAR, RoHSUSB Type-C downstream ports quantity1Sustainability certificatesENERGY STAR, RoHSUSB Type-C downstream ports quantity1Logistics dataSocial StateVGA (D-Sub) ports quantity1Logistics dataSocial StateUVI portXHarmonized System (HS) codeSocial StateHDMI *1InterfaceSocial StateHDMI ports quantity1InterfaceSocial	Certification		Weight (without stand)	5.1 kg
Package width692 mmBuilt-in USB hub *✓Package depth430 mmUSB hub version3.2 Gen 1 (3.1 Gen 1)Package height218 mmUSB upstream port typeUSB Type-B, USB Type-CPackage weight10.7 kgNumber of USB Type-B upstream ports quantity1Package typeBoxUSB Type-A downstream ports quantity3Sustainability certificatesENERGY STAR, RoHSUSB Type-C downstream ports quantity1European Product Registry for Energy Labelling (EPREL) code356049VGA (D-Sub) ports quantity1Logistics dataSustainability code85285210HDMI *✓1Harmonized System (HS) code85285210	Ports & interfaces		Packaging data	
USB hub version3.2 Gen 1 (3.1 Gen 1)Package depth450 mmUSB upstream port typeUSB Type-B, USB Type-CPackage height218 mmNumber of USB Type-B upstream ports quantity1Package typeBoxUSB Type-A downstream ports quantity3Sustainability certificatesENERGY STAR, RoHSUSB Type-C downstream ports quantity1Sustainability certificatesENERGY STAR, RoHSUSB Type-C downstream ports quantity1Logistics data36049VGA (D-Sub) ports quantity1Logistics dataSustainability certificatesDVI portXHarmonized System (HS) code85285210HDMI ports quantity1Sustainability certificatesSustainability code			Package width	692 mm
USB upstream port typeUSB Type-B, USB Type-CPackage neight218 mmNumber of USB Type-B upstream ports quantity1Package weight10.7 kgUSB Type-A downstream ports quantity3Package typeBoxUSB Type-C downstream ports quantity3Sustainability certificatesENERGY STAR, RoHSUSB Type-C downstream ports quantity1Sustainability certificates56049VGA (D-Sub) ports quantity1Logistics dataSoVVI portXHarmonized System (HS) code85285210HDMI *1II		-	Package depth	430 mm
Number of USB Type-B upstream ports quantity1Package weight10.7 KgUSB Type-A downstream ports quantity3Package typeBoxUSB Type-C downstream ports quantity3SustainabilityENERGY STAR, RoHSUSB Type-C downstream ports quantity1Sustainability certificatesENERGY STAR, RoHSVGA (D-Sub) ports quantity1Logistics dataSige typeVVI portXHarmonized System (HS) code85285210HDMI ports quantity1Sige typeSige typeHDMI ports quantity1Sige type <td< td=""><td></td><td></td><td>Package height</td><td>218 mm</td></td<>			Package height	218 mm
ports quantityIPackage typeboxUSB Type-A downstream ports quantity3SustainabilityENERGY STAR, RoHSUSB Type-C downstream ports quantity1Sustainability certificates Energy Labelling (EPREL) codeENERGY STAR, RoHSVGA (D-Sub) ports quantity1Logistics dataSolvantityVDV portXHarmonized System (HS) code85285210HDMI ports quantity1SolvantitySolvantity		ОЅВ Туре-В, ОЅВ Туре-С	Package weight	10.7 kg
Substripter A downstream ports3Sustainability certificatesENERGY STAR, RoHSUSB Type-C downstream ports quantity1European Product Registry for Energy Labelling (EPREL) code356049VGA (D-Sub) ports quantity1Logistics dataVGADVI portXHarmonized System (HS) code85285210HDMI ports quantity1VGAVGA	, , , , , , , , , , , , , , , , , , ,	1	Package type	Box
quantitySustainability certificatesENERGY STAR, RoHSUSB Type-C downstream ports quantity1European Product Registry for Energy Labelling (EPREL) code356049VGA (D-Sub) ports quantity1Logistics dataUSBDVI portXHarmonized System (HS) code85285210HDMI ports quantity1USBUSBHDMI ports quantity1USB<		3	Sustainability	
quantityIEuropean Fround Critegistry for Energy Labelling (EPREL) code356049VGA (D-Sub) ports quantity1Logistics dataDVI port×Harmonized System (HS) code85285210HDMI ports quantity1Image: State St		5	Sustainability certificates	ENERGY STAR, RoHS
DVI port Logistics data HDMI* ✓ HDMI ports quantity 1		1		356049
DVI port K G HDMI * Image: Constraint of the second			Logistics data	
HDMI ports quantity 1	•		•	85285210
			Harmonized System (HS) code	05205210
HDMI Version 1.4				
	HUMI version	1.4		





766907989410

0766907989410

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.