

## Tripp Lite Protect It! 7-Outlet Surge Protector, 7 -ft. Cord, 2160 Joules, Coaxial Protection

**Brand :** Tripp Lite

**Product code:** SUPER7COAX

**Product name :** Protect It! 7-Outlet Surge Protector, 7 -ft. Cord, 2160 Joules, Coaxial Protection

Protect It! 7-Outlet Surge Protector, 7 -ft. Cord, 2160 Joules, Coaxial Protection

Tripp Lite Protect It! 7-Outlet Surge Protector, 7 -ft. Cord, 2160 Joules, Coaxial Protection:

The SUPER7COAX surge suppressor from Tripp Lite has 7 outlets and a 7-ft. cord with a space-saving right-angle plug. The unit has 2160 joules of surge energy absorption to handle the strongest surges. Built-in 2.2 GHZ gold coax jacks prevent surges from damaging your cable/satellite equipment. Diagnostic LEDs alert the user to potential power problems. \$75,000 Ultimate Lifetime Insurance (U.S., Canada, and Puerto Rico only).

- 7 outlets
- 7-ft. cord with space-saving right-angle plug
- Surge suppression rating: 2160 joules
- 1 set of 2.2 GHz gold coaxial jacks
- EMI/RFI noise filtering
- Can accommodate up to 3 transformers without blocking remaining outlets
- \$75,000 Ultimate Lifetime Insurance (U.S., Canada, and Puerto Rico only) covers connected equipment
- Diagnostic LEDs indicate protection present & ground present
- Keyhole supports for wall mounting



Power		Weight & dimensions	
Surge energy rating *	2160 J	Depth	261.6 mm
AC outlets quantity *	7 AC outlet(s)	Height	39.1 mm
AC outlet types *	NEMA 5-15R	<b>Certificates</b>	
Nominal input voltage *	120 V	Certification	UL1449, UL1363, UL497A, FCC 68, cUL
AC input frequency	50 - 60 Hz	<b>Indication</b>	
Peak power	1800 W	LED indicators	✓
Peak current, common mode	144000 A	<b>Packaging data</b>	
Ports & interfaces		Package width	48.3 mm
Power plug	NEMA 5-15P	Package depth	149.9 mm
Features		Package height	320 mm
Product colour *	White	Package weight	860 g
EMI/RFI noise filtering	✓	<b>Logistics data</b>	
EMI/RFI noise filtering	20 dB	Master (outer) case width	622.3 mm
Country of origin	China	Master (outer) case length	254 mm
Technical details		Master (outer) case height	340.4 mm
Weight (imperial)	0.68 kg (1.5 lbs)	Master (outer) case gross weight	17 kg
Sustainability certificates	RoHS	Products per master (outer) case	20 pc(s)
Weight & dimensions		Master (outer) case GTIN (EAN/UPC)	10373320109096
Weight	630 g		
Cable length *	2.1 m		
Width	69.1 mm		



0037332010902



037332010902

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 16-MAY-2024. Prints or copies of Information are only valid on the printed Publication date