

StarTech.com OAM Managed Gigabit Ethernet Fiber Media Converter - Multi Mode LC 550m - 802.3ah Compliant

Brand : StarTech.comProduct code: ET91000LCOAM

Product name : OAM Managed Gigabit Ethernet Fiber Media Converter - Multi Mode LC 550m - 802.3ah Compliant

StarTech.com Multimode (MM) LC Fiber Media Converter with SFP - OAM Management - 802.3ah Compliant - Gigabit Ethernet - 550m - 850nm (ET91000LCOAM)
StarTech.com OAM Managed Gigabit Ethernet Fiber Media Converter - Multi Mode LC 550m - 802.3ah Compliant. Maximum data transfer rate: 1250 Mbit/s, Converter input interface: 1000Base-LX, 1000Base-SX, 1000Base-T, 100Base-TX, 10Base-T, Converter output interface: 1000Base-LX, 1000Base-SX. Fiber optic connector: LC, Connectivity technology: Wired. Maximum transfer distance: 550 m, Wavelength: 850 nm, Fiber mode structure: Multi-mode. LED indicators: LAN, Link, Power, Product colour: Black, Housing material: Steel. Input voltage: 100 - 240 V, Input current: 0.36 A, Output voltage: 12 V



Network		Power	
Maximum data transfer rate *	1250 Mbit/s	Input voltage	100 - 240 V
Converter input interface	1000Base-LX, 1000Base-SX, 1000Base-T, 100Base-TX, 10Base-T	Input current	0.36 A
Converter output interface	1000Base-LX, 1000Base-SX	Output voltage	12 V
Networking standards	IEEE 802.3, IEEE 802.3ab, IEEE 802.3ah, IEEE 802.3u, IEEE 802.3z	Output current	1 A
Ethernet interface type	Gigabit Ethernet	Power over Ethernet (PoE)	✗
Ethernet LAN data rates	10,100,1000 Mbit/s	External power adapter	✓
Auto MDI/MDI-X	✓	Weight & dimensions	
Duplex system	Full, Half	Width	87 mm
Ports & interfaces		Depth	163 mm
Connectivity technology	Wired	Height	23 mm
Ethernet LAN (RJ-45) ports	1	Weight	411 g
Fiber ports quantity	1	Operational conditions	
Fiber optic connector *	LC	Operating temperature (T-T)	0 - 60 °C
DC-in jack	✓	Storage temperature (T-T)	-10 - 70 °C
Performance		Operating relative humidity (H-H)	10 - 90%
Maximum transfer distance *	550 m	Packaging data	
Wavelength *	850 nm	Package width	136 mm
Fiber mode structure	Multi-mode	Package depth	206 mm
Mean time between failures (MTBF)	65000 h	Package height	92 mm
Design		Package weight	789 g
Internal *	✗	Packaging content	
LED indicators	LAN, Link, Power	Manual	✓
Product colour	Black	Technical details	
Housing material	Steel	Sustainability certificates	RoHS
Certification	FCC, CE	Logistics data	
		Harmonized System (HS) code	85176990



0065030854566



065030854566



0662300782262



662300782262

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.