



## APC SMT2200RM2UC uninterruptible power supply (UPS) Line-Interactive 2.2 kVA 1980 W 8 AC outlet(s)



**Brand :** APC

**Product code:** SMT2200RM2UC

**Product name :** SMT2200RM2UC



2.2 kV, 1.98 kW, 75-154V, 530J, 2U, 480x683x86mm, 43.21kg, Black

APC SMT2200RM2UC. UPS topology: Line-Interactive, Output power capacity: 2.2 kVA, Output power: 1980 W. AC outlet types: NEMA 5-15R, NEMA 5-20R, Power plug: NEMA 5-20P, AC outlets quantity: 8 AC outlet(s). Battery technology: Sealed Lead Acid (VRLA), Battery life (max): 5 year(s), Battery recharge time: 3 h. Form factor: Rackmount, Product colour: Black, Rack capacity: 2U. Width: 480 mm, Depth: 683 mm, Height: 86 mm

Features		Battery	
UPS topology *	Line-Interactive	Number of batteries supported	1
Output power capacity *	2.2 kVA	Battery life (max)	5 year(s)
Output power *	1980 W	Battery recharge time	3 h
Waveform *	Sine	Hot-swap battery	✓
Input operation voltage (min) *	75 V	Automatic battery test	✓
Input operation voltage (max) *	154 V	Cold start	✓
Input frequency *	50/60 Hz	Design	
Output operation voltage (min)	110 V	Form factor *	Rackmount
Output operation voltage (max)	127 V	Rack capacity	2U
Output frequency	50/60 Hz	Cable length	2.44 m
Automatic Voltage Regulation (AVR)	✓	Product colour *	Black
Surge energy rating	530 J	Display type	LCD
Emergency Power Off (EPO)	✓	LED indicators	Status
Output voltage Total Harmonic Distortion (THD)	5%	Certification	CSA, FCC, UL
Noise level	55 dB	Operational conditions	
Audible alarm(s)	✓	Operating temperature (T-T)	0 - 40 °C
Web-based management	✓	Storage temperature (T-T)	-15 - 45 °C
Audible alarm modes	Alarm when on battery, Low battery alarm, Overload alarm	Operating relative humidity (H-H)	0 - 95%
Temperature voltage compensation	✓	Storage relative humidity (H-H)	0 - 95%
Ports & interfaces		Operating altitude	0 - 3000 m
AC outlet types	NEMA 5-15R, NEMA 5-20R	Non-operating altitude	0 - 15000 m
Power plug	NEMA 5-20P	Technical details	
AC outlets quantity	8 AC outlet(s)	Sustainability certificates	ENERGY STAR
USB port	✓	Weight & dimensions	
Serial interface	✓	Width	480 mm
Serial interface type	RJ-45	Depth	683 mm
Ethernet LAN (RJ-45) ports	1	Height	86 mm
SmartSlot	✓	Weight	43.2 kg
Battery		Package width	600 mm
Battery technology	Sealed Lead Acid (VRLA)	Package depth	980 mm
		Package height	254 mm
		Package weight	49.7 kg
		Logistics data	
		Products per pallet	8 pc(s)



0731304331056



731304331056

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 17-MAY-2024. Prints or copies of Information are only valid on the printed Publication date