

## Tripp Lite SmartPro LCD 120V 1kVA 500W Line-Interactive UPS, Tower, LCD Display, USB, TEL/DSL/Coax Protection

**Brand :** Tripp Lite

**Product code:** SMART1000LCD

**Product name :** SmartPro LCD 120V 1kVA 500W Line-Interactive UPS, Tower, LCD Display, USB, TEL/DSL/Coax Protection

SmartPro LCD 120V 1kVA 500W Line-Interactive UPS, Tower, LCD Display, USB, TEL/DSL/Coax Protection  
Tripp Lite SmartPro LCD 120V 1kVA 500W Line-Interactive UPS, Tower, LCD Display, USB, TEL/DSL/Coax Protection. UPS topology: Line-Interactive, Output power capacity: 1 kVA, Output power: 500 W. AC outlet types: NEMA 5-15R, Power plug: NEMA 5-15P, AC outlets quantity: 8 AC outlet(s). Typical backup time at full load: 3 min, Typical backup time at half load: 10 min, Battery recharge time: 16 h. Form factor: Tower, Product colour: Black, Housing material: Acrylonitrile butadiene styrene (ABS). Width: 93 mm, Depth: 183.9 mm, Height: 300.7 mm



| Features                           |                                       | Design   |                    |
|------------------------------------|---------------------------------------|--|--------------------|
| UPS topology *                     | Line-Interactive                      | Cable length                                     | 1.8 m              |
| Output power capacity *            | 1 kVA                                 | Cooling type                                     | Active             |
| Output power *                     | 500 W                                 | Product colour *                                 | Black              |
| Waveform *                         | Sine                                  | Display type                                     | LCD                |
| Input operation voltage (min) *    | 89 V                                  | LED indicators                                   | ✓                  |
| Input frequency *                  | 60 Hz                                 | <b>Operational conditions</b>                    |                    |
| Output operation voltage (max)     | 120 V                                 | Operating temperature (T-T)                      | 0 - 40 °C          |
| Automatic Voltage Regulation (AVR) | ✓                                     | Storage temperature (T-T)                        | -15 - 50 °C        |
| Maximum current                    | 12 A                                  | Operating relative humidity (H-H)                | 0 - 95%            |
| Surge energy rating                | 1038 J                                | <b>Weight &amp; dimensions</b>                   |                    |
| Number of input phases             | 1                                     | Width  | 93 mm              |
| Efficiency                         | 97%                                   | Depth  | 183.9 mm           |
| EMI/RFI noise filtering            | ✓                                     | Height   | 300.7 mm           |
| Audible alarm(s)                   | ✓                                     | Weight   | 6.76 kg            |
| Country of origin                  | Taiwan                                | Package width                                    | 121.9 mm           |
| <b>Ports &amp; interfaces</b>      |                                       | Package depth                                    | 269.2 mm           |
| AC outlet types                    | NEMA 5-15R                            | Package height                                   | 391.2 mm           |
| Power plug                         | NEMA 5-15P                            | Package weight                                   | 7.57 kg            |
| AC outlets quantity                | 8 AC outlet(s)                        | <b>Logistics data</b>                            |                    |
| USB 2.0 ports quantity             | 1                                     | Master (outer) case width                        | 261.6 mm           |
| <b>Battery</b>                     |                                       | Master (outer) case length                       | 408.9 mm           |
| Typical backup time at full load   | 3 min                                 | Master (outer) case height                       | 287 mm             |
| Typical backup time at half load   | 10 min                                | Master (outer) case gross weight                 | 15.4 kg            |
| Battery recharge time              | 16 h                                  | Products per master (outer) case                 | 2 pc(s)            |
| Hot-swap battery                   | ✓                                     | Master (outer) case GTIN (EAN/UPC)               | 10037332124996     |
| Cold start                         | ✓                                     | <b>Other features</b>                            |                    |
| <b>Design</b>                      |                                       | I/O ports  | 8 x NEMA 5-15R     |
| Form factor *                      | Tower                                 | Non-operating relative humidity (non-condensing) | 0 - 95%            |
| Housing material                   | Acrylonitrile butadiene styrene (ABS) | Weight (imperial)                                | 6.62 kg (14.6 lbs) |



0037332124999



037332124999

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 15-MAY-2024. Prints or copies of Information are only valid on the printed Publication date