



APC SMC1500-2UC uninterruptible power supply (UPS) Line-Interactive 1.44 kVA 900 W

Brand : APC

Product code: SMC1500-2UC

Product name : SMC1500-2UC



- APC Smart-UPS C 1500VA LCD RM 2U 120V with SmartConnect
- Intelligent and efficient network power protection from entry level to scaleable runtime. Ideal UPS for servers, point-of-sale, routers, switches, hubs and other network devices
- Includes: Documentation CD, Installation guide, Rack mounting brackets, USB cable
APC Smart-UPS C, 1500VA, LCD, RM, 2U, 120V, SmartConnect
APC SMC1500-2UC. UPS topology: Line-Interactive, Output power capacity: 1.44 kVA, Output power: 900 W. Battery technology: Lead-Acid, Battery life (max): 6 year(s), Battery recharge time: 3 h. Form factor: Rackmount, Product colour: Black, Display type: LCD. Width: 432 mm, Depth: 477 mm, Height: 86 mm. Cables included: USB cable



Features		Design	
UPS topology *	Line-Interactive	Form factor *	Rackmount
Output power capacity *	1.44 kVA	Built-in fan	✓
Output power *	900 W	Product colour *	Black
Waveform *	Sine	Display type	LCD
Input operation voltage (min) *	93 V	Certification	CSA C22.2 No 107.1, CULus, ENERGY STAR V2.0 (USA), FCC part 15 class A, ICES-003, UL 1778
Input operation voltage (max) *	130 V		
Input frequency *	50/60 Hz		
Output operation voltage (min)	110 V	Operational conditions	
Output operation voltage (max)	125 V	Operating temperature (T-T)	0 - 40 °C
Output frequency	50/60 Hz	Storage temperature (T-T)	-15 - 40 °C
Automatic Voltage Regulation (AVR)	✓	Operating relative humidity (H-H)	0 - 95%
Surge energy rating	680 J	Operating altitude	0 - 3048 m
Response time	10 ms	Non-operating altitude	0 - 15240 m
Noise level	45 dB	Technical details	
Audible alarm(s)	✓	Sustainability certificates	RoHS, ENERGY STAR
Audible alarm modes	Alarm when on battery, Low battery alarm	Weight & dimensions	
Ports & interfaces		Width	432 mm
USB port	✓	Depth	477 mm
Ethernet LAN (RJ-45) ports	1	Height	86 mm
Battery		Weight	25.3 kg
Battery technology	Lead-Acid	Package width	590 mm
Battery life (max)	6 year(s)	Package depth	610 mm
Battery recharge time	3 h	Package height	235 mm
Cold start	✓	Package weight	29.1 kg
		Packaging data	
		Rack mount kit	✓
		Cables included	USB cable
		Quick installation guide	✓

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 17-MAY-2024. Prints or copies of Information are only valid on the printed Publication date