Verbatim Vi550 S3 SSD 512GB

Brand: Verbatim Product code: 49352

Product name: Vi550 S3 SSD 512GB

Vi550 Internal SATA III 2.5" SSD 512GB

Verbatim Vi550 S3 SSD 512GB:

Verbatim 2.5" SATA III 7mm solid state drives can revitalise the performance of your system. Using the latest 3D NAND technology they offer the perfect way to upgrade from either hard drive or an older SSD. The Vi550 has a superior controller for increased reliability, larger capacities and faster read/write speeds.

Expand the lifetime of your laptop or PC

Breathe new life into an older system by replacing a tired hard drive or a legacy 2D NAND SSD with a Vi550 S3 SSD. The Vi550 offers read speeds of up to 560MB/s, up to 20 times faster than a standard hard drive. With a MTBF (mean time before failure) rating of 2 million hours and TBW rating of up to 480TB (1TB capacity), the Vi550 is a high spec SSD that can be relied upon. Recommended for professional installation.

Verbatim Vi550 S3 SSD 512GB. SSD capacity: 512 GB, SSD form factor: 2.5", Read speed: 520 MB/s, Write speed: 500 MB/s, Data transfer rate: 6 Gbit/s, Component for: PC/Laptop







Features		Technical details	
SSD form factor *	2.5"	Sustainability certificates	RoHS
SSD capacity *	512 GB	Weight & dimensions	
Interface * Memory type * NVMe * Component for * Hardware encryption *	Serial ATA III 3D NAND X PC/Laptop	Width Depth Height Weight	69.9 mm 100.5 mm 7 mm 45 g
Data transfer rate	6 Gbit/s	Packaging data	
Read speed Write speed Mean time between failures (MTBF) Windows operating systems supported	520 MB/s 500 MB/s	Quick start guide Package width Package depth Package height Package weight Package type	109 mm 24 mm 159 mm 62 g Blister
Mac operating systems supported	Leopard, Mac OS X 10.7 Lion, Mac OS X 10.8 Mountain Lion, Mac OS X 10.9 Mavericks	Logistics data Master (outer) cases per pallet	780 pc(s)
Linux operating systems supported TBW rating SSD usage tag	√ 360 Consumer	Layers per pallet Products per pallet Master (outer) case width	6 pc(s) 1560 pc(s) 168 mm
Operational conditions		Master (outer) case length Harmonized System (HS) code	115 mm 84717070
Operating temperature (T-T) Storage temperature (T-T) Operating shock Vibration resistance	0 - 70 °C -40 - 85 °C 1500 G 20 G	Master (outer) case height Master (outer) case gross weight Products per master (outer) case	58 mm 163 g 2 pc(s)





023942493525

0023942493525

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.