

## CyberPower PR1000LCDRT1U uninterruptible power supply (UPS) Line-Interactive 1 kVA 800 W 7 AC outlet(s)

**Brand :** CyberPower**Product code:** PR1000LCDRT1U**Product name :** PR1000LCDRT1U

Line Interactive, PFC, NEMA 5-15P, 1000 VA, 800 W, 1030 J, NEMA 5-15R x 7, 1U

CyberPower PR1000LCDRT1U. UPS topology: Line-Interactive, Output power capacity: 1 kVA, Output power: 800 W. AC outlet types: NEMA 5-15R, Power plug: NEMA 5-15P, AC outlets quantity: 7 AC outlet(s). Battery technology: Sealed Lead Acid (VRLA), Typical backup time at full load: 3.5 min, Typical backup time at half load: 13 min. Form factor: Rackmount/Tower, Product colour: Black, Rack capacity: 1U. Width: 438.1 mm, Depth: 401.3 mm, Height: 44.5 mm



Features		Battery	
UPS topology *	Line-Interactive	Hot-swap battery	✓
Output power capacity *	1 kVA	<b>Design</b>	
Output power *	800 W	Form factor *	Rackmount/Tower
Waveform *	Sine	Rack capacity	1U
Input operation voltage (max) *	120 V	Product colour *	Black
Input frequency *	47/63 Hz	Display type	LCD
Output operation voltage (max)	120 V	LED indicators	✓
Output frequency	60 Hz	Safety	UL1778 4th, cUL CSA C22.2 No 107.3-05, FCC/DOC Class A
Surge energy rating	1030 J	<b>Operational conditions</b>	
Power factor	0.8	Operating temperature (T-T)	0 - 40 °C
Emergency Power Off (EPO)	✓	Storage temperature (T-T)	-15 - 45 °C
EMI/RFI noise filtering	✓	Storage relative humidity (H-H)	0 - 90%
<b>Ports &amp; interfaces</b>		Operating altitude	0 - 3000 m
AC outlet types	NEMA 5-15R	Non-operating altitude	0 - 15000 m
Power plug	NEMA 5-15P	<b>Technical details</b>	
AC outlets quantity	7 AC outlet(s)	Sustainability certificates	RoHS, ENERGY STAR
Serial ports quantity	1	<b>Weight &amp; dimensions</b>	
<b>Battery</b>		Width	438.1 mm
Battery technology	Sealed Lead Acid (VRLA)	Depth	401.3 mm
Number of batteries supported	4	Height	44.5 mm
Typical backup time at full load	3.5 min	Weight	16.3 kg
Typical backup time at half load	13 min	Package width	528.3 mm
Battery recharge time	6 h	Package depth	492.8 mm
		Package height	157.5 mm
		Package weight	19.3 kg
		<b>Other features</b>	
		Overload protection	✓
		Output voltage	120 V



0649532610242



649532610242

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 16-MAY-2024. Prints or copies of Information are only valid on the printed Publication date