Jabra Engage 75 SE - Mono, NA

Brand : Jabra

Product name : Engage 75 SE - Mono, NA

- Up to 13 hours battery life
- Great for long wireless calls
- Incredible wireless range
- Connect to up to 5 devices
- Built to last
- Passive Noise-Cancellation
- Base with touchscreen
- 3 wearing styles
- 52 Hours standby
- Industry-leading wireless performance. Better customer connections
- Crystal-clear calls. Enhance the customer experience
- More talk time, less interruptions. Increase productivity
- Engage 75 SE Mono, NA

Jabra Engage 75 SE - Mono, NA. Product type: Headset. Connectivity technology: Wireless, Bluetooth. Recommended usage: Office/Call center. Headphone frequency: 40 - 16000 Hz. Wireless range: 150 m. Weight: 64 g. Product colour: Black





D - ---

Performance		Microphone	
Product type *HeadsetWearing style *Head-bandRecommended usage *Office/Call coHeadset typeMonaural	Head-band Office/Call center	Microphone frequency Number of microphones MEMS (Micro-Electro-Mechanical System) microphone	100 - 10000 Hz 2 ✔
Product colour *	Black	Base station	
Operating keys	Answer/end call, Mute, Volume +, Volume -	Base station colour	Black
Volume control	Button	Battery	
Control unit type	On-ear control unit	Battery operated	✓
Control type	Buttons	Battery type	Built-in battery
DECT connectable	 Image: A second s	Battery technology	Lithium-Ion (Li-Ion)
Hearing protection technologies	Jabra PeakStop, Jabra Safetone 2.0	Rechargeable battery	✓
Number of paired devices remembered	2	Talk time Battery recharge time	13 h 1.5 h
Suitable for use in country/location	North America	Charging source	USB
Ports & interfaces		Standby time	52 h
Connectivity technology *	Wireless 5.0 40 - 16000 Hz 150 - 6800 Hz 150 m	Operational conditions	
Bluetooth version 5.		Operating temperature (T-T) Storage temperature (T-T)	-10 - 55 °C -5 - 45 °C
Frequency response (music mode) Frequency response (talk mode)		Weight & dimensions	
Wireless range		Weight	64 g
		Packaging data	
		Package width	190 mm

Product code: 9656-583-125

Headphones		Packaging data	
Ear coupling * Headphone frequency	Supraaural 40 - 16000 Hz	Package depth Package height	147 mm 93 mm
Driver unit	2.8 cm	Packaging content	
Microphone		AC adapter included *	1
Microphone type *	Boom	Cables included	Phone, USB Type-A to USB Type-C
		Base station	1
		Quantity	1
		Other features	
		Applications supported	Jabra Direct, Jabra SDK, Jabra Xpress





706487026082

0706487026082

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.