APC

APC AP7820B power distribution unit (PDU) 8 AC outlet(s) 0U/1U Black

Brand : APC

Product name : AP7820B

Product code: AP7820B

Rack PDU, Metered, 1U, 12A/208V, 10A/230V, 50/60 Hz, 8x IEC 320 C13, IEC-320 C14, 444 x 102 x 44 mm, 1730 g
APC AP7820B. PDU types: Metered, Rack capacity: 0U/1U, Mounting: Horizontal/Vertical. AC outlets quantity: 8 AC outlet(s), AC outlet types: C13 coupler, Power plug: C14 coupler. Cable length: 1.98 m, Certification: cUL, C-tick, CE, CSA, FCC 15 A, GOST, UL 60950, UL, VDE, VCCI. Monitoring: Current, Power, Voltage. Nominal input voltage: 208-230 V, Maximum current: 15 A, AC input frequency: 50 - 60 Hz

RoHS
2002/95/EC

Design

PDU types *	Metered
Rack capacity *	0U/1U
Mounting	Horizontal/Vertical
Product colour	Black

Ports & interfaces

AC outlets quantity *	8 AC outlet(s)
Power plug	C14 coupler
AC outlet types *	C13 coupler
Input connection type	IEC-320 C14

Features

LED indicators	✔
Cable length	1.98 m
Certification	cUL, C-tick, CE, CSA, FCC 15 A, GOST, UL 60950, UL, VDE, VCCI

Management features

Monitoring	Current, Power, Voltage

Power

Nominal input voltage *	208-230 V
AC input frequency	50 - 60 Hz
Maximum current *	15 A
Nominal output voltage	208-230 V
Load capacity	2300 VA

Power

Maximum input current per phase	15 A
Maximum total current draw per phase	10 A
Maximum power	2300 W

Weight & dimensions

Dimensions (WxDxH)	444 x 102 x 44 mm
Weight	1.73 kg

Packaging data

Package dimensions (WxDxH)	470 x 337 x 64 mm
Package weight	2.91 kg

Operational conditions

Operating temperature (T-T)	-5 - 45 °C
Storage temperature (T-T)	-25 - 65 °C
Operating relative humidity (H-H)	5 - 95%
Storage relative humidity (H-H)	5 - 95%
Operating altitude	0 - 3000 m
Non-operating altitude	0 - 15000 m

Technical details

Sustainability certificates	RoHS

0731304331506

731304331506