








SPECIFICATIONS

Panel Size	23.6" (60cm)
Panel Resolution	1920x1080 (FHD)
Refresh Rate	75Hz
Brightness (nits)	250
Viewing Angle	178° (H) / 178° (V)
Aspect Ratio	16:9
Curvature	1500R
Contrast Ratio	3000:1
Active Display Area (mm)	521(H)x293(V)
Pixel Pitch (H x V)	0.272(H)x0.272(V)
Surface Treatment	Anti-glare
Display Colors	16.7M
Adobe RGB / DCI-P3 / sRGB	82%/ 77% / 98%
Video ports	1 x Display Port (1.2a) 1 x HDMI (1.4b)
Response time	1ms(MPRT)
Panel Type	VA
Audio ports	1x Headphoneout
Kensington Lock	Yes
VESA Mounting	100 x 100 mm
Control	5-way OSD navigation joystick
Power Input	100~240V
DYNAMIC REFRESH RATE TECHNOLOGY	FreeSync
ACTIVATED RANGE	48 to 75Hz
DCR	100000000:1
Power Type	External Adaptor 12V 2.5A
Signal Frequency	52.8~90 KHz(H) / 48~75 Hz(V)
Adjustment (Tilt)	-5°~ 20°
Adjustment (Swivel)	N/A
Adjustment (Pivot)	N/A
Adjustment (Height)	N/A
Dimension (W x D x H)	539.8x 184.7 x 413.4 mm 539.8 x 74.2 x 321.8 mm(without stand)
Carton Dimension (W X D X H)	WW:600 x 140x 400 mm Outer:615 x 155 x 430 mm
Frameless Design	Yes

FEATURES







1ms Fast Response Time

Eliminate screen tearing and choppy frame rates with 1ms response time.



Night Vision

See every detail clearly in the dark, helping you find and attack enemies before they notice.



Wide Color Gamut



Frameless Design

With the narrow bezel, you will not even notice the monitor at all in the heat of the moment.



MONITOR G243CV

 PIP / PBP Function
 N/A

 Display Port:1920 x 1080 (75Hz)

 HDMI: 1920 x 1080 (75Hz)

 Adobe RGB, DCI-P3 and sRGB follow

 CIE1976 Standard

CONNECTIONS



- 1. 5-way joystick navigator
- 2. 1 x Display Port (1.2a)
- 3. 2 x HDMI(2.0b)
- 4. Headphone-out
- 5. DC-in
- 6. 1x Kensington Lock