

DELL Pro 14 Premium PA14250 Intel Core Ultra 7 268V Laptop 35.6 cm (14") Full HD+ 32 GB LPDDR5x-SDRAM 512 GB SSD Wi-Fi 7 (802.11be) Windows 11 Pro Grey

Brand : DELL Product family: Pro Product code: FK5CT

Product name: PA14250

- Windows 11 Pro 64-bit
- Intel Core Ultra 7 268V (12MB Cache)
- 35.6 cm (14") Full HD+ 1920 x 1200 IPS WVA
- 32GB LPDDR5x-SDRAM & 512GB SSD

Intel Core Ultra 7 268V (12MB Cache), 32GB LPDDR5x-SDRAM, 512GB SSD, 35.6 cm (14") Full HD+ 1920 x 1200 IPS WVA, Intel Arc Graphics 140V, WLAN, Webcam, Windows 11 Pro 64-bit

DELL Pro 14 Premium PA14250 Intel Core Ultra 7 268V Laptop 35.6 cm (14") Full HD+ 32 GB LPDDR5x-SDRAM 512 GB SSD Wi-Fi 7 (802.11be) Windows 11 Pro Grey:

The ultimate in design and mobility for AI PCs. Expertly crafted to be portable and quiet with the most premium collaboration features, on-device AI, sharpest display, and all-day battery life. DELL Pro 14 Premium PA14250. Product type: Laptop, Form factor: Clamshell. Processor family: Intel Core Ultra 7, Processor model: 268V. Display diagonal: 35.6 cm (14"), HD type: Full HD+, Display resolution: 1920 x 1200 pixels. Internal memory: 32 GB, Internal memory type: LPDDR5x-SDRAM. Total storage capacity: 512 GB, Storage media: SSD. On-board graphics card model: Intel Arc Graphics 140V. Operating system installed: Windows 11 Pro. Product colour: Grey. Weight: 1.14 kg





Design		Camera	
Product type * Product colour *	Laptop Grey	Video capturing speed Infrared (IR) camera	30 fps ✓
Form factor *	Clamshell	Privacy camera	1
Housing material	Magnesium	Privacy type	Privacy shutter
Market positioning	Premium	Network	
Display		Top Wi-Fi standard *	W: F: 7 (002 11ha)
Display diagonal *	35.6 cm (14")	Top Wi-Fi standard *	Wi-Fi 7 (802.11be) 802.11a, Wi-Fi 5 (802.11ac), Wi-Fi 7
Display resolution * Touchscreen *	1920 x 1200 pixels	Wi-Fi standards	(802.11a, Wi-ii 5 (602.11ac), Wi-ii 7 (802.11be), 802.11b, 802.11g, Wi-Fi 4 (802.11n), Wi-Fi 6E (802.11ax)
HD type	Full HD+	Mobile network connection *	×
Panel type	IPS WVA	Wi-Fi band	Tri-band (2.4 GHz / 5 GHz / 6 GHz)
Display technology marketing name	ComfortView Plus	Wi-Fi data rate (max)	5670 Mbit/s
LED backlight	✓	WLAN controller model	Intel Wi-Fi 7 BE201
Native aspect ratio	16:10	WLAN controller manufacturer	Intel
Anti-glare screen	✓	Ethernet LAN	×
Display brightness	400 cd/m ²	Bluetooth	✓
Pixel density	162 ppi	Ports & interfaces	
RGB colour space Colour gamut	sRGB 100%	USB 3.2 Gen 1 (3.1 Gen 1) Type-A ports quantity *	1
Maximum refresh rate	60 Hz	HDMI ports quantity *	1
Contrast ratio (typical)	1200:1	HDMI version	2.1
Processor		Thunderbolt 4 ports quantity	2
Processor manufacturer *	Intel	Combo headphone/mic port	✓
Processor family *	Intel Core Ultra 7	USB Type-C DisplayPort Alternate Mode	✓
Processor generation Processor model *	Intel Core Ultra (Series 2) 268V	PowerShare	✓
Processor cores	8	Performance	
Processor threads	8	Motherboard chipset	Intel SoC

Processor		Performance	
Processor boost frequency	5 GHz	Accelerometer	✓
Performance cores	4	Hall sensor	✓
Low Power Efficient-cores	4	Keyboard	
Performance-core Max Turbo Frequency	5 GHz	Pointing device	Touchpad
Low Power Efficient-core Max Turbo		Numeric keypad *	X
Frequency	3.7 GHz		^ /
Performance-core base frequency	2.2 GHz	Keyboard backlit	
Low Power Efficient-core Base	2200 MHz	Copilot key	✓
Frequency Processor cache	12 MB	Software	
Processor cache type	Smart Cache	Operating system architecture	64-bit
Processor base power	17 W	Operating system installed *	Windows 11 Pro
Maximum turbo power	37 W	Copilot+ PC	✓
Neural processor unit (NPU)		Brand-specific features	
•	Intel Al Doort	Brand specific technologies	Express Charge Boost capable
Neural processor unit (NPU)	Intel Al Boost	Battery	
Sparsity support	V	•	Lithium Ion (Li Ion)
Windows Studio effects support	Discretial On any VINO Windows MI	Battery technology Number of battery cells	Lithium-lon (Li-lon) 3
Al software frameworks supported by NPU	DirectML, OpenVINO, Windows ML, ONNX RT, WebNN	Battery capacity *	3 60 Wh
Total processor performance up to	118 TOPs	Battery voltage	11.7 V
NPU performance up to	48 TOPs	Battery recharge time	4 h
GPU performance up to	66 TOPs	Fast charging	/
Memory		Battery weight	215 g
Internal memory *	32 GB	Power	9
Internal memory type	LPDDR5x-SDRAM		CF W
Memory form factor	On-board	AC adapter power	65 W
Maximum internal memory *	32 GB	AC adapter frequency AC adapter input voltage	50/60 Hz 100 - 240 V
Memory data transfer rate	8533 MT/s	USB Type-C charging port *	100 - 240 V
Storage		USB Type-C required charging	
Total storage capacity *	512 GB	power (min) *	27 W
Storage media *	SSD	USB Type-C required charging	100 W
Total SSDs capacity	512 GB	power (max) *	
Number of SSDs installed	1	USB Power Delivery (USB PD)	✓
		USB charging voltage	20,5,9,15 V
SSD capacity	512 GB		
SSD capacity SSD interface	512 GB PCI Express 4.0	Security	
		Security Cable lock slot	1
SSD interface	PCI Express 4.0	,	✓ Wedge
SSD interface NVMe	PCI Express 4.0	Cable lock slot	
SSD interface NVMe SSD form factor	PCI Express 4.0 ✓ M.2	Cable lock slot Cable lock slot type	Wedge
SSD interface NVMe SSD form factor Optical drive type * Card reader integrated	PCI Express 4.0 M.2 X	Cable lock slot Cable lock slot type Fingerprint reader Trusted Platform Module (TPM) Trusted Platform Module (TPM)	Wedge ✓
SSD interface NVMe SSD form factor Optical drive type * Card reader integrated Graphics	PCI Express 4.0 M.2 X	Cable lock slot Cable lock slot type Fingerprint reader Trusted Platform Module (TPM)	Wedge ✓
SSD interface NVMe SSD form factor Optical drive type * Card reader integrated Graphics Discrete graphics card model *	PCI Express 4.0 M.2 X	Cable lock slot Cable lock slot type Fingerprint reader Trusted Platform Module (TPM) Trusted Platform Module (TPM)	Wedge ✓
SSD interface NVMe SSD form factor Optical drive type * Card reader integrated Graphics	PCI Express 4.0 M.2 X Not available	Cable lock slot Cable lock slot type Fingerprint reader Trusted Platform Module (TPM) Trusted Platform Module (TPM) version	Wedge ✓
SSD interface NVMe SSD form factor Optical drive type * Card reader integrated Graphics Discrete graphics card model * On-board graphics card * On-board GPU manufacturer	PCI Express 4.0 M.2 X X Not available Intel	Cable lock slot Cable lock slot type Fingerprint reader Trusted Platform Module (TPM) Trusted Platform Module (TPM) version Operational conditions Operating temperature (T-T) Storage temperature (T-T)	Wedge ✓ ✓ 2.0
SSD interface NVMe SSD form factor Optical drive type * Card reader integrated Graphics Discrete graphics card model * On-board graphics card * On-board GPU manufacturer Discrete graphics card *	PCI Express 4.0 M.2 X Not available Intel X	Cable lock slot Cable lock slot type Fingerprint reader Trusted Platform Module (TPM) Trusted Platform Module (TPM) version Operational conditions Operating temperature (T-T) Storage temperature (T-T) Operating relative humidity (H-H)	Wedge
SSD interface NVMe SSD form factor Optical drive type * Card reader integrated Graphics Discrete graphics card model * On-board graphics card * On-board GPU manufacturer	PCI Express 4.0 M.2 X X Not available Intel	Cable lock slot Cable lock slot type Fingerprint reader Trusted Platform Module (TPM) Trusted Platform Module (TPM) version Operational conditions Operating temperature (T-T) Storage temperature (T-T) Operating relative humidity (H-H) Storage relative humidity (H-H)	Wedge
SSD interface NVMe SSD form factor Optical drive type * Card reader integrated Graphics Discrete graphics card model * On-board graphics card * On-board GPU manufacturer Discrete graphics card * On-board graphics card family On-board graphics card model *	PCI Express 4.0 M.2 X Not available Intel Intel Arc Graphics	Cable lock slot Cable lock slot type Fingerprint reader Trusted Platform Module (TPM) Trusted Platform Module (TPM) version Operational conditions Operating temperature (T-T) Storage temperature (T-T) Operating relative humidity (H-H) Storage relative humidity (H-H) Operating altitude	Wedge 2.0 0 - 35 °C -40 - 65 °C 10 - 90% 0 - 95% -15.2 - 3048 m
SSD interface NVMe SSD form factor Optical drive type * Card reader integrated Graphics Discrete graphics card model * On-board graphics card * On-board GPU manufacturer Discrete graphics card family On-board graphics card model * Audio	PCI Express 4.0 M.2 X Not available Intel Intel Arc Graphics Intel Arc Graphics 140V	Cable lock slot Cable lock slot type Fingerprint reader Trusted Platform Module (TPM) Trusted Platform Module (TPM) version Operational conditions Operating temperature (T-T) Storage temperature (T-T) Operating relative humidity (H-H) Storage relative humidity (H-H) Operating altitude Non-operating altitude	Wedge 2.0 0 - 35 °C -40 - 65 °C 10 - 90% 0 - 95% -15.2 - 3048 m -15.2 - 10668 m
SSD interface NVMe SSD form factor Optical drive type * Card reader integrated Graphics Discrete graphics card model * On-board graphics card * On-board GPU manufacturer Discrete graphics card family On-board graphics card model * Audio Audio chip	PCI Express 4.0 M.2 X Not available Intel Intel Arc Graphics Intel Arc Graphics 140V Cirrus CS42L43 / Cirrus CS35L56	Cable lock slot Cable lock slot type Fingerprint reader Trusted Platform Module (TPM) Trusted Platform Module (TPM) version Operational conditions Operating temperature (T-T) Storage temperature (T-T) Operating relative humidity (H-H) Storage relative humidity (H-H) Operating altitude Non-operating altitude Operating shock	Wedge 2.0 0 - 35 °C -40 - 65 °C 10 - 90% 0 - 95% -15.2 - 3048 m -15.2 - 10668 m 110 G
SSD interface NVMe SSD form factor Optical drive type * Card reader integrated Graphics Discrete graphics card model * On-board graphics card * On-board GPU manufacturer Discrete graphics card * On-board graphics card family On-board graphics card model * Audio Audio chip Number of built-in speakers	PCI Express 4.0 M.2 X X Not available Intel Intel Arc Graphics Intel Arc Graphics 140V Cirrus CS42L43 / Cirrus CS35L56 4	Cable lock slot Cable lock slot type Fingerprint reader Trusted Platform Module (TPM) Trusted Platform Module (TPM) version Operational conditions Operating temperature (T-T) Storage temperature (T-T) Operating relative humidity (H-H) Storage relative humidity (H-H) Operating altitude Non-operating altitude Operating shock Non-operating shock	Wedge
SSD interface NVMe SSD form factor Optical drive type * Card reader integrated Graphics Discrete graphics card model * On-board graphics card * On-board GPU manufacturer Discrete graphics card family On-board graphics card family On-board graphics card model * Audio Audio chip Number of built-in speakers Speaker power	PCI Express 4.0 M.2 X X Not available Intel Intel Arc Graphics Intel Arc Graphics 140V Cirrus CS42L43 / Cirrus CS35L56 4 2 W	Cable lock slot Cable lock slot type Fingerprint reader Trusted Platform Module (TPM) Trusted Platform Module (TPM) version Operational conditions Operating temperature (T-T) Storage temperature (T-T) Operating relative humidity (H-H) Storage relative humidity (H-H) Operating altitude Non-operating altitude Operating shock Non-operating shock Operating vibration	Wedge
SSD interface NVMe SSD form factor Optical drive type * Card reader integrated Graphics Discrete graphics card model * On-board graphics card * On-board GPU manufacturer Discrete graphics card family On-board graphics card family On-board graphics card model * Audio Audio Audio chip Number of built-in speakers Speaker power Built-in microphone	PCI Express 4.0 M.2 X X Not available Intel Intel Arc Graphics Intel Arc Graphics 140V Cirrus CS42L43 / Cirrus CS35L56 4	Cable lock slot Cable lock slot type Fingerprint reader Trusted Platform Module (TPM) Trusted Platform Module (TPM) version Operational conditions Operating temperature (T-T) Storage temperature (T-T) Operating relative humidity (H-H) Storage relative humidity (H-H) Operating altitude Non-operating altitude Operating shock Non-operating shock Operating vibration Non-operating vibration	Wedge
SSD interface NVMe SSD form factor Optical drive type * Card reader integrated Graphics Discrete graphics card model * On-board graphics card * On-board GPU manufacturer Discrete graphics card family On-board graphics card family On-board graphics card model * Audio Audio chip Number of built-in speakers Speaker power	PCI Express 4.0 M.2 X X Not available Intel Intel Arc Graphics Intel Arc Graphics 140V Cirrus CS42L43 / Cirrus CS35L56 4 2 W	Cable lock slot Cable lock slot type Fingerprint reader Trusted Platform Module (TPM) Trusted Platform Module (TPM) version Operational conditions Operating temperature (T-T) Storage temperature (T-T) Operating relative humidity (H-H) Storage relative humidity (H-H) Operating altitude Non-operating altitude Operating shock Non-operating shock Operating vibration	Wedge
SSD interface NVMe SSD form factor Optical drive type * Card reader integrated Graphics Discrete graphics card model * On-board graphics card * On-board GPU manufacturer Discrete graphics card family On-board graphics card family On-board graphics card model * Audio Audio Audio chip Number of built-in speakers Speaker power Built-in microphone	PCI Express 4.0 M.2 X Not available Intel Intel Arc Graphics Intel Arc Graphics 140V Cirrus CS42L43 / Cirrus CS35L56 4 2 W	Cable lock slot Cable lock slot type Fingerprint reader Trusted Platform Module (TPM) Trusted Platform Module (TPM) version Operational conditions Operating temperature (T-T) Storage temperature (T-T) Operating relative humidity (H-H) Storage relative humidity (H-H) Operating altitude Non-operating altitude Operating shock Non-operating shock Operating vibration Non-operating vibration	Wedge
SSD interface NVMe SSD form factor Optical drive type * Card reader integrated Graphics Discrete graphics card model * On-board graphics card * On-board GPU manufacturer Discrete graphics card family On-board graphics card model * Audio Audio Audio chip Number of built-in speakers Speaker power Built-in microphone Camera Front camera Front camera resolution (numeric)	PCI Express 4.0 M.2 X X Not available Intel Intel Arc Graphics Intel Arc Graphics 140V Cirrus CS42L43 / Cirrus CS35L56 4 2 W M M M M M M M M M M M M M	Cable lock slot Cable lock slot type Fingerprint reader Trusted Platform Module (TPM) Trusted Platform Module (TPM) version Operational conditions Operating temperature (T-T) Storage temperature (T-T) Operating relative humidity (H-H) Storage relative humidity (H-H) Operating altitude Non-operating altitude Operating shock Operating vibration Non-operating vibration Sustainability Sustainability certificates	Wedge
SSD interface NVMe SSD form factor Optical drive type * Card reader integrated Graphics Discrete graphics card model * On-board graphics card * On-board GPU manufacturer Discrete graphics card family On-board graphics card family On-board graphics card model * Audio Audio Audio chip Number of built-in speakers Speaker power Built-in microphone Camera Front camera	PCI Express 4.0 M.2 X Not available Intel Intel Arc Graphics Intel Arc Graphics 140V Cirrus CS42L43 / Cirrus CS35L56 4 2 W	Cable lock slot Cable lock slot type Fingerprint reader Trusted Platform Module (TPM) Trusted Platform Module (TPM) version Operational conditions Operating temperature (T-T) Storage temperature (T-T) Operating relative humidity (H-H) Storage relative humidity (H-H) Operating altitude Non-operating altitude Operating shock Operating vibration Non-operating vibration Sustainability	Wedge

Weight & dimensions	
Depth	216.7 mm
Height (front)	1.64 cm
Height (rear)	1.7 cm
Weight *	1.14 kg
Packaging content	

AC adapter included *

