

LQ-780 Impact Printer



A compact 24-pin flatbed printer that's built for reliability in demanding environments.

Fast, easy printing — speeds through prints at up to 487 cps¹

Compact flatbed printer — 24-pin impact printer with flatbed printing; designed to easily fit in areas with limited space

Convenient multipart printing — prints the original plus six copies²

Engineered for reliability 3 — MVBF of 40 million lines; MTBF of 35,000 power-on hours (POH); printhead life of 400 million strokes per wire

Automatically adjusts for thick forms — Automatic Platen Gap (APG) flatbed adjustment technology easily accommodates forms of varying thicknesses

Long ribbon life — 10 million characters⁴

World-class service and support - 2-year limited warranty

Easy setup and integration — Parallel and USB interfaces

Versatility for all your back-office needs — provides a variety of built-in fonts



LQ-780 Impact Printer

General

Printing Method 24-pin impact dot matrix Print Direction Bidirectional with logic seeking Columns 106 columns (10 cpi)

Print Speed¹ High Speed Draft: 487 cps (10 cpi)

Draft: 366 cps (10 cpi) Letter Quality: 121 cps (10 cpi)

Input Buffer 64KB Noise Level 59 dBA Reliability³

MTBF: 35,000 POH (25% duty cycle)

MVBF: 40 million lines

Printhead Life: 400 million strokes/wire

Interface

Bidirectional 8-bit parallel interface (IEEE 1284 Nibble - USB)

Character Sets

13 standard version

8 barcode

15 international character sets

Resident Fonts

Epson® Draft: 10. 12. 15

Epson Roman: 10, 12, 15, proportional Epson Sans Serif: 10, 12, 15, proportional

Epson Courier: 10, 12, 15 Epson Prestige: 10, 12 Epson Script: 10 Epson OCR-B: 10 Epson Orator: 10 Epson Orator-S: 10 Epson Script C: Proportional

Barcode Fonts: EAN-13, EAN-8, Interleaved 2 of 5, UPC-A,

UPC-E, Code 39, Code 128, Postnet

Formatting

1/6" (4.23 mm) or programmable in increments of 1/360"

(0.0706 mm) **Paper Feed Speed**

47.4 milliseconds

3.61" per second, continuous feed

General (continued)

Software Drivers⁵

Windows® XP Professional x64 Edition SP2, Windows 11(64-bit), Windows Server® 2003, SP2-Windows Server 2022 (64-bit)

Printer Language

Epson ESC/P2®

IBM® 2390 Plus emulation

Control Panel Functions

Font, Pause, Tear Off, LF/FF, Load/Eject, Micro Adjust, Self Test, Data Dump and Default Settings

Printer

Rated Voltage AC 100-240 V Input Voltage Range AC 90-264 V Rated Frequency Range 50 to 60 Hz Input Frequency Range 49.5 to 60.5 Hz Dimensions (W x D x H) 18.9" x 11.9" x 8.3" Weight 14.8 lb

Ribbon Cartridge Type: Fabric; Color: Black

Ribbon Life⁴ 10 million characters (10 cpi, 48 dots/character) Limited Warranty 2-year limited warranty in th e U.S.

and Canada

Extended Service Plan⁶ Up to an additional 2 years,

available in 1- or 2-year increments

Paper Handling

Forms 1 original + 6 copies2

Cut-Sheet Single-Sheet (Front Entry, Manual Insertion)

Width: 3.5" to 12' Length: 2.8" to 16.5" Thickness: 0.0025" to 0.0074"

Cut-Sheet Multipart (Front Entry, Manual Insertion)

Width: 3.5" to 12'

Length: 2.8" to 16.5" (line glue on one side of the form, 11.7"

maximum)

Thickness: 0.0047" to 0.018"

Copy Capability 1 original + 6 copies2 Envelope

No. 6, No. 10

Thickness: 0.0063" to 0.0205"

Continuous Paper

Width: 4" to 12" Length (one page): 3" to 22" Thickness: 0.0025" to 0.059"

Paper Handling (continued)

Roll Paper

Width: 8.38" to 8.62"

Thickness: 0.0027" to 0.0035"

Paper Feed Methods

Feeding Method: Friction Feed (Front-/Rear-In, Front-Out),

Push Tractor Feed (Rear-In, Front-Out) Feeder: Rear Push Tractor, Roll Paper Holder (optional)

Paper Path

Front-/Rear-In, Front-Out Tractor: Rear-In. Rear-Out

Eco Features

ENERGY STAR® qualified RoHS compliant Recyclable product7

Epson America, Inc. is a SmartWay® Transport Partner8

Ordering Information

Product Code Description C11CJ81201 Epson LQ-780 Impact Printer S015630 Ribbon Cartridge C12C811141 Roll Paper Holder For additional information, please contact your Epson

representative.

Contact:

1 Based on Ultra Speed draft at 10 cpi. | 2 One original, plus six copies, is available only under normal temperature and humidity conditions. | 3 Ratings are estimates only, based on normal use of the printer. Epson's statements about reliability levels are not warranties of Epson products, and the only warranty for printers are the limited warranty statements for each printer. | 4 Based on Letter Quality printing, 10 cpi, 48 dots/character. | 5 Additional software drivers available in your Windows operating system or at www.epson.com | 6 See individual extended service plan for details. | 7 For convenient and reasonable recycling options, visit www.epson.com/recycle | 8 SmartWay is an innovative partnership of the U.S. Environmental Protection Agency that reduces greenhouse gases and other air pollutants and improves fuel efficiency.

See the latest innovations from Epson Business Solutions at www.epson.com/forbusiness

Better Products for a Better Future eco.epson.com

3131 Katella Ave., Los Alamitos, CA 90720





www.epson.com 185 Renfrew Drive, Markham, Ontario L3R 6G3 www.epson.ca

Specifications are subject to change without notice. EPSON and Epson ESC/P2 are registered trademarks, EPSON Exceed Your Vision is a registered logomark and Better Products for a Better Future is a trademark of Seiko Epson Corporation. Windows and Windows Server are either registered trademarks or trademarks of Microsoft Corporation in the United States and other countries. SmartWay is a registered trademark of the U.S. Environmental Protection Agency. All other product and brand names are trademarks and/or registered trademarks of their respective companies. Epson disclaims any and all rights in these marks. Copyright 2022 Epson America, Inc. Com-SS-Oct-13 CPD-62136 4/22

Epson Canada Limited

Epson America, Inc.