

## Tripp Lite PDUMNH30HVAT2 power distribution unit (PDU) 1 AC outlet(s) 1U Black

**Brand :** Tripp Lite

**Product code:** PDUMNH30HVAT2

**Product name :** PDUMNH30HVAT2



5.8kW 208/240V Single-Phase ATS/Monitored PDU - 16 C13, 2 C19 & 1 L6-30R Outlets, Dual L6- 30P Inputs, 10 ft. Cords, 2U, TAA

Tripp Lite PDUMNH30HVAT2. PDU types: Monitored, Rack capacity: 1U, Mounting: Horizontal. AC outlets quantity: 1 AC outlet(s), AC outlet types: C13 coupler, C19 coupler, NEMA L6-30R, Power plug: NEMA L6-30P. Cable length: 3 m, Certification: Tested to UL/CSA 60950-1 (USA, Canada), FCC Class A (Emissions), NOM (Mexico). Nominal input voltage: 208 V, Maximum current: 30 A, AC input frequency: 50 - 60 Hz. Width: 444.5 mm, Depth: 317.5 mm, Height: 88.9 mm



Design		Weight & dimensions	
PDU types *	Monitored	Height	88.9 mm
Rack capacity *	1U	Weight	6.21 kg
Mounting	Horizontal	<b>Packaging data</b>	
Housing material	Metal	Package weight	7.85 kg
Product colour	Black	Package width	424.2 mm
Display	LCD	Package depth	490.2 mm
On/off switch	✓	Package height	198.1 mm
Ports & interfaces		Package type	Box
AC outlets quantity *	1 AC outlet(s)	<b>Packaging content</b>	
Power plug	NEMA L6-30P	Manual	✓
AC outlet types *	C13 coupler, C19 coupler, NEMA L6-30R	<b>Operational conditions</b>	
Ethernet LAN (RJ-45) ports	1	Operating temperature (T-T)	0 - 40 °C
Features		Storage temperature (T-T)	-30 - 50 °C
LED indicators	✓	Operating relative humidity (H-H)	5 - 95%
Cable length	3 m	Storage relative humidity (H-H)	5 - 95%
Certification	Tested to UL/CSA 60950-1 (USA, Canada), FCC Class A (Emissions), NOM (Mexico)	Operating altitude	0 - 3000 m
Power		Operating temperature (T-T)	32 - 122 °F
Nominal input voltage *	208 V	<b>Technical details</b>	
AC input frequency	50 - 60 Hz	Sustainability certificates	RoHS
Maximum current *	30 A	<b>Logistics data</b>	
Nominal output voltage	200 - 240 V	Country of origin	Taiwan
Weight & dimensions		Products per master (outer) case	1 pc(s)
Width	444.5 mm		
Depth	317.5 mm		



0037332261434



037332261434

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 25-APR-2024. Prints or copies of Information are only valid on the printed Publication date