

## Viewsonic IFP86G1 interactive whiteboard 2.18 m (86") 3840 x 2160 pixels Touchscreen Black HDMI

**Brand :** Viewsonic

**Product code:** IFP86G1

**Product name :** IFP86G1


- Bring Your Own OS interactive flat panel for versatile use in any scenario
  - Seamless USB-C plug-and-play connectivity for convenient presentations
  - 65W charging of peripheral devices, ensuring uninterrupted presentations
  - Flexible integration with slot-in PCs, supporting Windows, Linux, and Android OS
- 55" TFT LCD, Touch, DLED, UHD, 16:9, 1.07B, 350 cd/m<sup>2</sup>, 1200:1, 8ms, 178/178, 12W x2 + 16W, Wi-Fi, RJ45, HDMI, SPDIF, RS232, USB, 100-240 VAC, VESA, 26.4 kg

Viewsonic IFP86G1. Display diagonal: 2.18 m (86"), Working area: 1209.6 x 680.4 mm, Display brightness: 350 cd/m<sup>2</sup>. Operating system installed: Android, Processor architecture: ARM Cortex A73 + ARM Cortex A53, Processor frequency: 1.5 GHz. Speaker power: 24 W, Subwoofer RMS power: 16 W. Ethernet LAN data rates: 10,100 Mbit/s. Interface: HDMI, USB connector type: USB Type-A, USB Type-B, USB Power Delivery up to: 65 W



Display		Ports & interfaces	
Display diagonal *	2.18 m (86")	HDMI output ports quantity	1
Display brightness	350 cd/m <sup>2</sup>	USB Power Delivery (USB PD)	✓
Display number of colours	1.07 billion colours	USB Power Delivery up to	65 W
Display resolution	3840 x 2160 pixels	Ethernet LAN (RJ-45) ports	1
Anti-glare screen	✓	OPS slot	1
HD type	4K Ultra HD	S/PDIF out port	✓
Panel type	LCD	Headphone connectivity	3.5 mm
LED backlighting type	Direct-LED	RS-232 ports	1
Native aspect ratio	16:9	<b>Ergonomics</b>	
Contrast ratio (typical)	1200:1	Product colour	Black
Contrast ratio (dynamic)	5000:1	VESA mounting	✓
Response time	8 ms	Panel mounting interface	400 x 200 mm
Touchscreen *	✓	Mean time between failures (MTBF)	30000 h
Touch technology	Multi-touch	Certification	cTUVus, FCC/ICES003, Energy Star 8.0, EMC/CE, CB/LVD, GOST-R/EAC, UkrSEPRO, EPEAT, Mexico NOM, Mexico Energy, UKCA, UK-EEL, BSMI, BIS, LBL( Low Blue Light Certification), Flicker Free, Green BOM, RoHS, ErP-Eco, REACH, SCIP, WEEE, TPCH, Packing waste, CA65, PAIA
Touchscreen type	Infrared		
Number of simultaneous touchpoints	40		
Touch resolution	32767 x 32767 pixels		
Touch system response time	10 ms	<b>Power</b>	
Viewing angle, horizontal	178°	Power consumption (typical)	89 W
Viewing angle, vertical	178°	Power consumption (off)	0.5 W
Working area *	1209.6 x 680.4 mm	AC input voltage	100 - 240 V
Hardness	7H	<b>Operational conditions</b>	
<b>Computer system</b>		Operating temperature (T-T)	0 - 40 °C
Operating system installed	Android	Operating relative humidity (H-H)	10 - 90%
Operating system version	11	<b>Weight &amp; dimensions</b>	
Built-in processor	✓	Width *	1268 mm
Processor architecture	ARM Cortex A73 + ARM Cortex A53	Depth	85 mm
Processor frequency	1.5 GHz	Height *	773 mm
Processor cores	8		
Maximum internal memory	32 GB		
RAM capacity	3 GB		
RAM type	DDR4		

<b>Audio</b>		<b>Weight &amp; dimensions</b>	
Built-in speaker(s) *	✓	Weight	62.4 kg
Number of built-in speakers	2	<b>Packaging data</b>	
Speaker power	24 W	Package width	2110 mm
Built-in subwoofer	✓	Package depth	225 mm
Subwoofer RMS power	16 W	Package height	1283 mm
<b>Projector</b>		Package weight	74.5 kg
Built-in projector *	✗	Quantity per pack	1 pc(s)
<b>Network</b>		<b>Packaging content</b>	
Ethernet LAN	✓	USB cable length	3 m
Ethernet LAN data rates	10,100 Mbit/s	Cables included	AC, HDMI, USB
<b>Ports &amp; interfaces</b>		Remote control included	✓
Interface	HDMI	Mounting kit	✓
HDCP	✓	Batteries included	✓
HDCP version	2.2	Mounting brackets included	✓
USB 3.2 Gen 1 (3.1 Gen 1) Type-A hub ports quantity	4	Quick start guide	✓
USB 2.0 ports quantity	2	Stylus included	✓
USB connector type	USB Type-A, USB Type-B	<b>Other features</b>	
HDMI ports quantity	3	Country of origin	China
USB Type-C ports quantity	1	<b>Logistics data</b>	
HDMI version	2.0	Pallet gross width	2.14 m
		Pallet gross length	114 cm
		Pallet gross height	141.2 cm
		Products per master (outer) case	1 pc(s)



0766907024685



766907024685

### Catalog Object Cloud



Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.