



TP-Link LS1005G network switch Unmanaged Gigabit Ethernet (10/100/1000) Black

Brand : TP-Link

Product code: LS1005G

Product name : LS1005G



- 5 x 10/100/1000Mbps Auto-Negotiation RJ45 port, supporting Auto-MDI/MDIX
- Green Ethernet technology saves power
- IEEE 802.3X flow control provides reliable data transfer
- Plastic casing, desktop or wall-mounting design
- Plug and play, no configuration needed
- Fanless design ensures quiet operation

LS1005G, IEEE 802.3i/802.3u/ 802.3ab/802.3x, 5x 1G RJ-45, 10 Gbps, 7.4 Mpps, 90x72x23 mm

TP-Link LS1005G. Switch type: Unmanaged. Basic switching RJ-45 Ethernet ports type: Gigabit Ethernet (10/100/1000), Basic switching RJ-45 Ethernet ports quantity: 5. MAC address table: 2000 entries, Switching capacity: 10 Gbit/s. Networking standards: IEEE 802.3i, IEEE 802.3u, IEEE 802.3x. DC input voltage: 5 V. Wall mountable



Management features		Design	
Switch type *	Unmanaged	Wall mountable	✓
Ports & interfaces		Power	
Basic switching RJ-45 Ethernet ports quantity *	5	Power supply included *	✓
Basic switching RJ-45 Ethernet ports type *	Gigabit Ethernet (10/100/1000)	DC input voltage	5 V
		Input current	0.6 A
		Power consumption (max)	3.7 W
Network		Power over Ethernet (PoE)	
Networking standards *	IEEE 802.3i, IEEE 802.3u, IEEE 802.3x	Power over Ethernet (PoE) *	✗
10G support *	✗	Operational conditions	
Flow control support	✓	Operating temperature (T-T)	0 - 40 °C
Auto MDI/MDI-X	✓	Storage temperature (T-T)	-40 - 70 °C
Auto-negotiation	✓	Operating relative humidity (H-H)	10 - 90%
		Storage relative humidity (H-H)	5 - 90%
		Heat dissipation	12.617 BTU/h
Data transmission		Weight & dimensions	
Switching capacity *	10 Gbit/s	Width	90 mm
Forwarding rate	7.4 Mpps	Depth	72 mm
MAC address table *	2000 entries	Height	23 mm
Store-and-forward	✓	Packaging content	
Jumbo frames support	✓	Quick start guide	✓
Jumbo frames	16000	Packaging data	
Packet buffer memory	1.5 MB	Package type	Box
Design		Certificates	
Rack mounting *	✗	Certification	CE, FCC, RoHS
Product colour	Black		
Housing material	Plastic		
LED indicators	✓		
International Protection (IP) code	IP20, IP40		

Logistics data

Harmonized System (HS) code 85176990



0845973085469




845973085469



1210002616164



0840460603867



840460603867



1210002616157

Catalog Object Cloud



Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.