QNAP TS-932PX NAS Tower Annapurna Labs Alpine AL-324 4 GB DDR4 0 TB QNAP Turbo System Black





Brand : QNAP

Product code: TS-932PX-4G-US

Product name : TS-932PX

- Two 10GbE SFP+ and two 2.5GbE RJ45 network ports empower bandwidth-demanding tasks and accelerate file sharing
- HBS provides comprehensive backup and data recovery; QuDedup deduplicates the data at the source to optimize storage and bandwidth usage, while reducing backup times
- Snapshots record your system status, allowing you to protect files and data from accidental deletion and malware attacks
- Cloud storage gateways realize hybrid cloud applications by working with the cache space reserved on NAS to ensure low-latency data access to the cloud
- Qtier auto-tiering technology and SSD caching enable constant storage optimization
- Increase the storage capacity of the TS-932PX with QNAP TR RAID expansion enclosures or TL JBOD

Alpine AL-324 1.7GHz, 4 GB DDR4, 512 MB, 5x 3.5, 4x 2.5", 2x 2.5G LAN, 2x 10G SFP+, 3x USB 3.2

Storage	
Storage drive capacity *	0 GB
Supported storage drive interfaces	Serial ATA III
Storage drive sizes supported	2.5,3.5"
RAID support *	✔
RAID levels	0, 1, 5, 6, 10, 50, 60, JBOD
Online RAID migration	✔
Online RAID expansion	✔
RAID rebuild	✔
Hot-swap drive bays	✔
Supported file systems	FAT32, HFS+, NTFS, ext3, ext4
Storage drives installed *	✘
Total installed storage capacity *	0 TB
Number of storage drives supported *	9
Installed storage drive type *	✘
Supported storage drive types *	HDD & SSD
Bad block scan	✔
Disk roaming	✔

Processor	
Processor manufacturer *	Annapurna Labs
Processor family *	Annapurna Labs
Processor model *	Alpine AL-324
Processor frequency *	1.7 GHz
Processor cores	4
Processor architecture	ARM Cortex-A57

Memory	
Internal memory *	4 GB
Internal memory type	DDR4
Maximum RAM supported	16 GB
Memory slots	1
Memory form factor	SO-DIMM
Flash memory	512 MB

Network	
Ethernet LAN *	✔
Ethernet LAN data rates	100,1000,2500,10000 Mbit/s

Design	
Product colour	Black
Number of fans	1 fan(s)
Fan diameter	14 cm
Drive bay locking	✔
LED indicators	HDD, LAN, SSD, Status, USB
Cable lock slot	✔
Cable lock slot type	Kensington

Performance	
Type *	NAS
Device class *	Small & Medium Business
Backup function *	✔
Backup features	Cloud, iSCSI LUN
Buzzer	✔
Multilingual support	✔
Snapshot	✔
Web-based management	✔
Security algorithms	256-bit AES, FIPS 140-2, HTTPS, SNMPv2, SNMPv3, SSH, SSL/TLS
Access Control List (ACL)	✔
Reset button	✔
On/off switch	✔
Built-in FTP server	✔
Browser supported	Mozilla Firefox, Microsoft Edge, Google Chrome, Apple Safari
System log	✔
Hot spare	✔
S.M.A.R.T. support	✔
Share folder	CIFS/SMB
USB copy function	✔

Software	
Operating system installed *	QNAP Turbo System
Windows operating systems supported	Windows 10, Windows 7, Windows 8
Linux operating systems supported	✔

Network	
Ethernet LAN data rate supported (max)	10000 Mbit/s
DHCP client	✔
DHCP server	✔
Jumbo frames support	✔
iSCSI support	✔
Wake-on-LAN ready	✔
Supported network protocols	FTP, SFTP, TFTP, OpenVPN, QBelt
Link aggregation	✔
Load balancing system	✔
Dynamic DNS (DDNS)	✔
WLAN adapter supported	✔

Ports & interfaces	
USB port *	✔
USB 3.2 Gen 1 (3.1 Gen 1) Type-A ports quantity	3
Fiber ports quantity	2
Fiber optic connector	SFP+
Ethernet LAN (RJ-45) ports *	2

Design	
Chassis type *	Tower
Cooling type *	Active

Software	
Mac operating systems supported	Mac OS X 10.10 Yosemite, Mac OS X 10.11 El Capitan, Mac OS X 10.12 Sierra, Mac OS X 10.13 High Sierra, Mac OS X 10.14 Mojave, Mac OS X 10.15 Catalina
Server operating systems supported	Windows Server 2008 R2, Windows Server 2012, Windows Server 2012 R2, Windows Server 2016, Windows Server 2019

Power	
Power supply location	External
Power supply unit (PSU) capacity	120 W
Number of power supply units	1
AC input voltage	100 - 240 V
Fan voltage	12 V

Weight & dimensions	
Width *	224.6 mm
Depth *	224.1 mm
Height *	182.7 mm

Packaging content	
External power adapter	✔
Cables included	AC, LAN (RJ-45)
Power cables quantity	1
Number of screws	56
Drive tray key included	✔

Operational conditions	
Operating temperature (T-T)	0 - 40 °C
Operating relative humidity (H-H)	5 - 95%
Storage temperature (T-T)	-20 - 70 °C
Storage relative humidity (H-H)	5 - 95%

Catalog Object Cloud



Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity. Automated scraping, data mining, or harvesting for the purpose of training machine learning models, neural networks, or artificial intelligence systems is strictly prohibited without a commercial license.

Publication date: 21-NOV-2026. Prints or copies of Information are only valid on the printed Publication date