



DELL P Series 14 Portable Monitor - P1424H

Brand : DELL

Product family: P Series

Product code: DELL-P1424H

Product name : 14 Portable Monitor - P1424H

- 35.6cm (14") Full HD 1920 x 1080 LED IPS
- 6ms, 16:9, 300cd/m², 700:1
- USB
35.6cm (14") Full HD 1920 x 1080 LED IPS, 16:9, 300cd/m², 16.7M, 6ms, 178°/178°, 700:1

DELL P Series 14 Portable Monitor - P1424H:

Experience dual-screen productivity anywhere with Dell's 14" portable monitor.

DELL P Series 14 Portable Monitor - P1424H. Display diagonal: 35.6 cm (14"), Display resolution: 1920 x 1080 pixels, HD type: Full HD, Display technology: LCD, Response time: 6 ms, Native aspect ratio: 16:9, Viewing angle, horizontal: 178°, Viewing angle, vertical: 178°. Product colour: Grey



| Display | | Power | |
|------------------------------|-----------------------|---|----------------|
| Display diagonal * | 35.6 cm (14") | Energy efficiency class (HDR) * | Not available |
| Display resolution * | 1920 x 1080 pixels | Energy consumption (SDR) per 1000 hours * | 5 kWh |
| HD type * | Full HD | Power consumption (typical) * | 5 W |
| Native aspect ratio * | 16:9 | Power consumption (standby) * | 0.3 W |
| Display technology * | LCD | Power consumption (max) | 7.5 W |
| Panel type * | IPS | Power consumption (off) | 0.3 W |
| Backlight type | LED | Power supply type | Internal |
| Touchscreen * | ✗ | Energy efficiency scale | A to G |
| Display brightness (typical) | 300 cd/m ² | European Product Registry for Energy Labelling (EPREL) code | 1435998 |
| Response time * | 6 ms | Operational conditions | |
| Anti-glare screen | ✓ | Operating temperature (T-T) | 0 - 40 °C |
| Screen shape * | Flat | Storage temperature (T-T) | -20 - 60 °C |
| Contrast ratio (typical) * | 700:1 | Operating relative humidity (H-H) | 10 - 80% |
| Maximum refresh rate * | 60 Hz | Storage relative humidity (H-H) | 5 - 90% |
| Viewing angle, horizontal | 178° | Operating altitude | 0 - 5000 m |
| Viewing angle, vertical | 178° | Non-operating altitude | 5000 - 12192 m |
| Display number of colours * | 16.7 million colours | Weight & dimensions | |
| Pixel pitch | 0.1611 x 0.1611 mm | Width (with stand) | 322.4 mm |
| Pixel density | 158 ppi | Depth (with stand) | 14.3 mm |
| Viewable size, horizontal | 30.9 cm | Height (with stand) | 202.7 mm |
| Viewable size, vertical | 17.4 cm | Weight (with stand) | 590 g |
| Digital horizontal frequency | 30 - 80 kHz | Width (without stand) | 322.4 mm |
| Digital vertical frequency | 56 - 61 Hz | Depth (without stand) | 4.95 mm |
| Display diagonal (metric) | 35.56 cm | Height (without stand) | 202.7 mm |
| Colour gamut standard | NTSC | Bezel width (side) | 6.53 mm |
| Colour gamut | 72% | Bezel width (top) | 6.54 mm |
| Multimedia | | Bezel width (bottom) | 2.22 cm |
| Built-in speaker(s) * | ✗ | | |

| Multimedia | | Packaging data | |
|--|----------|---|--------------------------|
| Built-in camera * | ✗ | Package weight | 1.12 kg |
| Design | | Packaging content | |
| Market positioning * | Business | Cables included | USB Type-C to USB Type-C |
| Product colour * | Grey | Sustainability | |
| Front bezel colour | Black | Sustainability certificates | ENERGY STAR |
| Ports & interfaces | | Doesn't contain | PVC/BFR |
| Number of USB Type-C upstream ports quantity | 2 | Carbon footprint | |
| USB Type-C DisplayPort Alternate Mode | ✓ | Total carbon footprint (kg of CO2e) | 421 |
| USB Power Delivery (USB PD) | ✓ | Total carbon emissions, standard deviation (kg of CO2e) | 99 |
| USB Power Delivery up to | 65 W | Carbon emissions, manufacturing (kg of CO2e) | 367.67 |
| HDMI * | ✗ | Carbon emissions, logistics (kg of CO2e) | 5.77 |
| Headphone out * | ✗ | Carbon emissions, energy usage (kg of CO2e) | 47.43 |
| HDCP | ✓ | Carbon emissions, end-of-life (kg of CO2e) | 0.63 |
| HDCP version | 1.4 | Total carbon emissions, w/o use phase (kg of CO2e) | 373.57 |
| Ergonomics | | PAIA version | 1.3.2, 2022 |
| VESA mounting * | ✗ | Other features | |
| Cable lock slot * | ✗ | Heavy metals free | Hg (mercury) |
| Height adjustment * | ✗ | Compliance certificates | RoHS |
| Tilt adjustment | ✓ | | |
| Tilt angle range | 10 - 90° | | |
| On Screen Display (OSD) | ✓ | | |
| Plug and Play | ✓ | | |
| LED indicators | ✓ | | |
| Power | | | |
| Energy efficiency class (SDR) * | B | | |



5397184821572



0884116452171



884116452171

Catalog Object Cloud



Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.