## ASUS PRIME Z790-A WIFI Intel Z790 LGA 1700 ATX

Brand: ASUS Product code: 90MB1CS0-M0EAY0

Product name: PRIME Z790-A WIFI

16+1 Teamed Power Stages (60A) with Enlarged Heatsinks, Gen 5 Slot for Graphics Card, AEMP II for Ultimate DDR5 Performance, USB 3.2 Gen 2x2 Type-C® & Thunderbolt (USB4®) Support , 2.5 Gb Ethernet, WiFi 6E, Intelligent Control, Al Cooling II

ASUS PRIME Z790-A WIFI. Processor manufacturer: Intel, Processor socket: LGA 1700, Compatible processor series: Intel® Celeron®, Intel® Core™ i3, Intel® Core™ i5, Intel® Core™ i7, Intel® Core™ i9,.... Supported memory types: DDR5-SDRAM, Maximum internal memory: 192 GB, Memory slots type: DIMM. Supported storage drive interfaces: M.2, SATA III, Supported storage drive types: HDD & SSD, RAID levels: 0, 1, 5, 10. Ethernet interface type: 2.5 Gigabit Ethernet, Top Wi-Fi standard: Wi-Fi 6E (802.11ax), Wi-Fi standards: 802.11a, 802.11b, 802.11g, Wi-Fi 4 (802.11n), Wi-Fi 5 (802.11ac), Wi-Fi 6 (802.11ax), Wi-Fi 6E.... Component for: PC, Motherboard form factor: ATX, Motherboard chipset family: Intel





Processor			Rear panel I/O ports	
Processor manufacturer * Processor socket *		Intel LGA 1700	USB 3.2 Gen 2 (3.1 Gen 2) Type-C ports quantity *	1
THOCCSSUL SUCKEL		Intel® Celeron®, Intel® Core™ i3, Intel® Core™ i5, Intel® Core™ i7,	USB 3.2 Gen 2x2 Type-C ports quantity	1
Compatible processor series *		Intel® Core™ i9, Intel® Pentium® Gold	Ethernet LAN (RJ-45) ports *	1
			HDMI ports quantity *	1
Supported processor sockets		LGA 1700	DisplayPorts quantity	1
Memory			Headphone outputs	1
Supported memory types * Number of memory slots *	DDR5-SDRAM 4		Line-in	✓
Memory slots type Memory channels	DIMM Dual-channel		Microphone in	✓
ECC compatibility	Non-ECC		S/PDIF out port	×
Supported memory clock speeds	4800,5000,5200, MHz	5400,5600,5800,6000,6200,6400,6600,6800,7000,7200	WiFi-AP antenna jack	1
Supported memory clock speed (max)	7200 MHz		Network	
Maximum internal memory * Unbuffered memory	192 GB ✓		Ethernet LAN	<b>✓</b>
Storage controllers			Ethernet interface type	2.5 Gigabit Ethernet
Supported storage drive types		HDD & SSD	Wi-Fi *	✓
Supported storage drive interfaces *		M.2, SATA III	Top Wi-Fi standard	Wi-Fi 6E (802.11ax)
RAID support RAID levels		<b>✓</b> 0, 1, 5, 10	Wi-Fi standards	802.11a, 802.11b, 802.11g, Wi-Fi 4 (802.11n), Wi-Fi 5 (802.11ac), Wi-Fi 6 (802.11ax), Wi-Fi 6E (802.11ax)
Graphics			Bluetooth	✓
Parallel processing technology		Not supported	Bluetooth version	5.3
Support *			Features	
On-board graphics card X		Motherboard chipset *	Intel Z790	
Internal I/O			Audio output channels *	7.1 channels
USB 2.0 connectors *		2	Product colour	Black, White
USB 3.2 Gen 1 (3.1 Gen 1) connectors *		1	Component for * Motherboard form factor *	PC ATX

Motherboard chipset family * Intel **ATX  **ATX  **ATX  **ATX  **Mindows operating systems supported  **Connector				
Power source type ATX  windows operating systems supported  Windows 10 x64, Windows 10 x64, Windows 10 x64, Windows operating systems supported  Expansion slots  Connector (24-pin)   Connector   PCI Express x1 (Gen 3.x) slots 2  PCI Express x4 (Gen 4.x) slots 1  PCI Express x16 (Gen 4.x) slots 1  PCI Express x16 (Gen 4.x) slots 1  PCI Express x16 (Gen 5.x) slots 1  PCI Express x16 (Gen 4.x) slots 1	I I/O		Features	
wer connector	2 Gen 2 (3.1 Gen 2) tors *	1	' '	
panel audio connector ower connector ower connector ower connector  ower of chassis fan connector  ower connec	er of SATA III connectors *	4	• •	Windows 10 v64 Windows 11
fan connector  ber of chassis fan connectors  ber of chassis fan connectors  4 PCI Express x1 (Gen 3.x) slots  2 PCI Express x4 (Gen 4.x) slots  1 PCI Express x16 (Gen 4.x) slots  1 PCI Express x16 (Gen 5.x) slots  1 PCI Express x16 (Gen 4.x) slots  1 PCI Express x16 (Gen 5.x) slots  1 PCI Expre	t panel audio connector	✓	supported	Williaows 10 x04, Williaows 11
Inber of chassis fan connectors 4 PCI Express x4 (Gen 4.x) slots 1 ssis intrusion connector	Power connector (24-pin)	/	Expansion slots	
PCI Express x16 (Gen 4.x) slots 1 power connector (8-pin)   PCI Express x16 (Gen 5.x) slots 1 Number of COM connector   PCI Express x16 (Gen 5.x) slots 1 Number of M.2 (M) slots 4  PCI Express x16 (Gen 5.x) slots 1 Number of M.2 (M) slots 4  PCI Express x16 (Gen 5.x) slots 1 Number of M.2 (M) slots 4  PCI Express x16 (Gen 5.x) slots 1 Number of M.2 (M) slots 4  PCI Express x16 (Gen 5.x) slots 1 Number of M.2 (M) slots 4  PCI Express x16 (Gen 4.x) slots 1 Number of M.2 (M) slots 4  PCI Express x16 (Gen 4.x) slots 1 Number of M.2 (M) slots 4  PCI Express x16 (Gen 4.x) slots 1 Number of M.2 (M) slots 4  PCI Express x16 (Gen 4.x) slots 1 Number of M.2 (M) slots 4  PCI Express x16 (Gen 4.x) slots 1 Number of M.2 (M) slots 4  PCI Express x16 (Gen 4.x) slots 1 Number of M.2 (M) slots 4  PCI Express x16 (Gen 4.x) slots 1 Number of M.2 (M) slots 4  PCI Express x16 (Gen 4.x) slots 1 Number of M.2 (M) slots 4  PCI Express x16 (Gen 4.x) slots 1 Number of M.2 (M) slots 4  PCI Express x16 (Gen 4.x) slots 1 Number of M.2 (M) slots 4  PCI Express x16 (Gen 5.x) slots 1 Number of M.2 (M) slots 4  PCI Express x16 (Gen 5.x) slots 1 Number of M.2 (M) slots 4  PCI Express x16 (Gen 5.x) slots 1 Number of M.2 (M) slots 4  PCI Express x16 (Gen 5.x) slots 1  Number of M.2 (M) slots 4  PCI Express x16 (Gen 5.x) slots 1  Number of M.2 (M) slots 4  PCI Express x16 (Gen 5.x) slots 1  Number of M.2 (M) slots 4  PCI Express x16 (Gen 5.x) slots 1  Number of M.2 (M) slots 4  PCI Express x16 (Gen 5.x) slots 1  Number of M.2 (M) slots 4  PECI Express x16 (Gen 5.x) slots 1  Number of M.2 (M) slots 4  PECI Express x16 (Gen 5.x) slots 1  PECI Express x16 (Gen 5.x) slots 1  Number of M.2 (M) slots 4  PECI Express x16 (Gen 5.x) slots 1  PECI Express x16 (Gen 5.x) slots 1  PECI Express x16 (Gen 5.x) slots 1  Number of M.2 (M) slots 2  PECI Express x16 (Gen 5.x) slots 2  PECI	J fan connector	<b>✓</b>	PCI Express x1 (Gen 3.x) slots	2
PCI Express x16 (Gen 5.x) slots 1 Number of COM connectors 1 Number of M.2 (M) slots 4  Number of M.2	mber of chassis fan connectors	4	PCI Express x4 (Gen 4.x) slots	1
Mumber of COM connectors  M connector  M con	assis intrusion connector	✓	PCI Express x16 (Gen 4.x) slots	1
M connector  M con	S power connector (8-pin)	<b>✓</b>	•	
underbolt headers  V power connector  V power connector  V power connector  V BIOS memory size  Clear CMOS button  Packaging data  Package width Package depth Package height Package weight Package ontent Packaging content Cables included  SATA	imber of COM connectors	1	Number of M.2 (M) slots	4
W power connector  W power connector  BIOS memory size  Clear CMOS button  Packaging data  Package width Package depth Package depth Package height Package weight Packaging content Packaging content Cables included SATA	M connector	1	BIOS	
Clear CMOS button  Packaging data  Package width Package depth Package height Package weight Pac	underbolt headers	1	BIOS type *	UEFI AMI
Packaging data  Package width 280 mm Package depth 265 mm  Package height 71 mm Package weight 1.27 kg  Package weight 305 mm Package weight 305 mm Package weight 305 mm Package one one of the package weight 305 mm Package one one of the package weight 305 mm Packaging content Packaging content Packaging content Cables included SATA	2V power connector	✓	BIOS memory size	256 Mbit
Package width 280 mm Package depth 265 mm Package height 71 mm Package weight 1.27 kg  Package weight 305 mm Package weight 305 mm Package weight 305 mm Package open 2 (3.1 Gen 2) Type-A Package weight 305 mm Package open 3 (3.1 Gen 2) Type-A Package weight 305 mm Package open 3 (3.1 Gen 2) Type-A Package open 3 (3.1 Gen 2) Type-A Package weight 305 mm Package open 3 (3.1 Gen 2) Type-A Package open 4 (3.1 Gen 2) Type-A Package open 5 (3.1 Gen 2) Type-A Package open 5 (3.1 Gen 2) Type-A Package open 5 (3.1 Gen 2) Type-A Package open 6 (3.1 Gen 2	GB LED pin header	✓	Clear CMOS button	✓
Package depth 265 mm  BB 3.2 Gen 2 (3.1 Gen 2) Type-A 2  Package height 71 mm  Package weight 1.27 kg  Weight & dimensions  Width 305 mm  Depth 244 mm  Packaging content  Cables included SATA	ear panel I/O ports		Packaging data	
Package depth 265 mm  BB 3.2 Gen 2 (3.1 Gen 2) Type-A 2 Package height 71 mm Package weight 1.27 kg  Weight & dimensions Width 305 mm Depth 244 mm  Packaging content Cables included SATA		Δ	Package width	280 mm
Package weight 1.27 kg  Weight & dimensions  Width 305 mm Depth 244 mm  Packaging content  Cables included SATA		•	Package depth	265 mm
Weight & dimensions Width 305 mm Depth 244 mm  Packaging content Cables included SATA		2	5 5	
Width 305 mm Depth 244 mm  Packaging content Cables included SATA	res quartery		Package weight	1.27 kg
Depth 244 mm  Packaging content  Cables included SATA			Weight & dimensions	
Packaging content  Cables included SATA			Width	305 mm
Cables included SATA			Depth	244 mm
			Packaging content	
			Cables included	SATA
Drivers included ✓			Drivers included	✓





195553939324

0195553939324



4711081939337

## **Catalog Object Cloud**



Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.