



TP-Link InSight S485PI Turret IP security camera Outdoor 3840 x 2160 pixels Wall

Brand : TP-Link

Product code: INSIGHT S485PI

Product name : InSight S485PI

- 180° Panorama View with Huge Vision
- 4K (8MP) Ultra HD and IR Range Up to 65.62 ft (20 m)
- Red-Blue Warning Lights with Stronger Deterrence
- People & Vehicle Analytics
- Human & Vehicle Classification
- Smart Detection
- Smart Video Enhancement Technology
- Audio and Alarm Interface Available
- IP67 Weatherproof and IK10 Vandal Proof
- H.265+ Compression Technology

VIGI 8MP IR Panoramic Turret Network Camera, 6 mm, 1/2.7", 1/3 to 1/10000 s, F1.65, 3840 x 2160, CBR, VBR, BLC/3D DNR/HLC/SmartIR, 120 dB, 12V DC ± 5%, Max. 18 W, 5.5 mm Coaxial Power Plug, PoE: 802.3at, class 4, Max. 21 W, IP67, 112.3 x 112.3 x 110.2 mm, 0,76 kg, White

Performance		Audio	
Type *	IP security camera	Audio output channels	1.0 channels
Placement supported *	Outdoor	Audio formats supported	G.711 A-law
Connectivity technology *	Wired	Sample rate	8 kHz
Maximum operating distance	44 m	Built-in microphone	✓
Wide Dynamic Range (WDR)	✓	Number of microphones	1
Day/night mode	✓	Bit rate range	0 - 64 Kbit/s
Infrared (IR) cut-off filter	✓	Network	
Remote viewing	✓	Ethernet LAN *	✓
Dynamic range	120 dB	Networking standards	IEEE 802.3at
Design		Supported network protocols	TCP/IP, UDP, ICMP, HTTP, HTTPS, DHCP, DNS, RTSP, NTP, UPnP, UDP, SSL/TLS, FTP/SFTP, RTP, IPv4, IPv6, ARP
Form factor *	Turret	Wi-Fi *	✗
Mounting type *	Wall	Bluetooth *	✗
Product colour *	White	SIM card slot	✓
Housing material	Metal	SIM card type	MicroSIM
Protection features	Waterproof	Live view	✓
International Protection (IP) code	IP67	Storage	
Weatherproof	✓	Compatible memory cards	MicroSD (TransFlash)
Camera		Maximum memory card size	512 GB
Minimum illumination	0 lx	Ports & interfaces	
Lens viewing angle, horizontal	180°	Ethernet LAN (RJ-45) ports	1
Lens viewing angle, vertical	86°	DC-in jack	✓
Lens viewing angle, diagonal	180°	Security	
Tilt angle range	0 - 90°	Built-in siren	✓
Camera shutter speed	1/3 to 1/10000	Password protection	✓
Image sensor		Video motion detection	✓
Optical sensor size	25.4 / 2.7 mm (1 / 2.7")	IP address filtering	✓
Progressive scan	✓	HTTPS encryption	✓
Sensor type *	CMOS	Detection distance	120 m
Panoramic camera		Alert notification type	Push notification
Sensor type (panoramic camera)	CMOS	Motion sensor	✓
Lens system		Mirror	✓
Detect distance	44 m		
Observe distance	18.33 m		
Recognize distance	8.8 m		


Lens system		Security	
Fixed focus	✓	Human and vehicle targets classification	✓
Maximum aperture number	2	Digest authentication	✓
Identify distance	4.4 m	Management features	
Fixed focal length	1.65 mm	Web-based management	✓
Night vision		Web browser	✓
Night vision *	✓	Cloud-managed *	✓
LED type	IR/White	Reset button	✓
Video		Power	
Maximum resolution *	3840 x 2160 pixels	Power source type *	DC, PoE
Total megapixels *	8 MP	Power consumption (max)	18 W
Video compression formats	H.264, H.264+, H.265, H.265+ 1280 x 720 (HD 720), 1920 x 1080 (HD 1080), 2048 x 1280, 2304 x 1296, 2560 x 1440, 2688 x 1520, 2880 x 1620, 3840 x 2160	Power consumption (Power over Ethernet (PoE))	21 W
Supported graphics resolutions		DC output voltage	12
Video recording	✓	Operational conditions	
Image quality adjustment	Brightness, Contrast, Mirror, Saturation, Sharpness	Operating temperature (T-T)	-30 - 60 °C
Bit rate control	Constant Bit Rate (CBR)/Variable Bit Rate (VBR)	Storage temperature (T-T)	-40 - 60 °C
Bit rate	Main Stream: 256 Kbps to 8 Mbps, Sub-Stream: 64 Kbps to 1024 Kbps	Operating relative humidity (H-H)	0 - 95%
Back Light Compensation (BLC)	✓	Storage relative humidity (H-H)	0 - 95%
Highlight Compensation (HLC)	✓	Weight & dimensions	
Digital Wide Dynamic Range (DWDR)	✓	Width	112.3 mm
Audio		Depth	112.3 mm
Built-in speaker(s)	✓	Height	110.2 mm
Audio system	2-way	Weight	760 g
Audio input channels	1.0 channels	Packaging content	
		Number of cameras *	1
		Mounting kit	✓
		Screws included	✓
		Drilling template included	✓
		Manual	✓



8885020627886



0810142823821



810142823821



1210002612753

Catalog Object Cloud



Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.