

## TP-Link InSight S485PI Turret IP security camera Outdoor 3840 x 2160 pixels Wall

Brand: TP-Link Product code: INSIGHT S485PI

Product name: InSight S485PI

- 180° Panorama View with Huge Vision
- 4K (8MP) Ultra HD and IR Range Up to 65.62 ft (20 m)
- Red-Blue Warning Lights with Stronger Deterrence
- People & Vehicle Analytics
- Human & Vehicle Classification
- Smart Detection
- Smart Video Enhancement Technology
- Audio and Alarm Interface Available
- IP67 Weatherproof and IK10 Vandal Proof
- H.265+ Compression Technology

VIGI 8MP IR Panoramic Turret Network Camera, 6 mm, 1/2.7", 1/3 to 1/10000 s, F1.65, 3840 x 2160, CBR, VBR, BLC/3D DNR/HLC/SmartIR, 120 dB, 12V DC  $\pm$  5%, Max. 18 W, 5.5 mm Coaxial Power Plug, PoE: 802.3at, class 4, Max. 21 W, IP67, 112.3 x 112.3 x 110.2 mm, 0,76 kg, White

Performance		Audio	
Type * Placement supported * Connectivity technology * Maximum operating distance Wide Dynamic Range (WDR) Day/night mode	IP security camera Outdoor Wired 44 m  ✓	Audio output channels Audio formats supported Sample rate Built-in microphone Number of microphones Bit rate range	1.0 channels G.711 A-law 8 kHz  1 0 - 64 Kbit/s
Infrared (IR) cut-off filter	✓	Network	
Remote viewing Dynamic range	<b>√</b> 120 dB	Ethernet LAN * Networking standards	✓ IEEE 802.3at
Posign  Form factor *  Mounting type *  Product colour *  Housing material  Protection features International Protection (IP) code  Weatherproof	Turret Wall White Metal Waterproof IP67	Supported network protocols  Wi-Fi * Bluetooth * SIM card slot SIM card type Live view	TCP/IP, UDP, ICMP, HTTP, HTTPS, DHCP, DNS, RTSP, NTP, UPnP UDP, SSL/TLS, FTP/SFTP, RTP, IPv4, IPv6, ARP  X  MicroSIM
Camera		Storage	·
Minimum illumination Lens viewing angle, horizontal Lens viewing angle, vertical Lens viewing angle, diagonal Tilt angle range Camera shutter speed	0 lx 180° 86° 180° 0 - 90° 1/3 to 1/10000	Compatible memory cards Maximum memory card size  Ports & interfaces  Ethernet LAN (RJ-45) ports  DC-in jack	MicroSD (TransFlash) 512 GB  1
Image sensor		Security	
Optical sensor size Progressive scan Sensor type *	25.4 / 2.7 mm (1 / 2.7")  CMOS	Built-in siren Password protection Video motion detection	* * *
Panoramic camera		IP address filtering	✓
Sensor type (panoramic camera)	CMOS	HTTPS encryption	✓
Lens system  Detect distance Observe distance Recognize distance	44 m 18.33 m 8.8 m	Detection distance Alert notification type Motion sensor Mirror	120 m Push notification

Lens system		Security	
Fixed focus	<b>/</b>	Human and vehicle targets classification	✓
Maximum aperture number Identify distance	2 4.4 m	Digest authentication	<b>✓</b>
Fixed focal length	1.65 mm	Management features	
Night vision		Web-based management	✓
Night vision *	✓	Web browser	✓
LED type	IR/White	Cloud-managed *	✓
Video		Reset button	✓
Maximum resolution *	3840 x 2160 pixels	Power	
Total megapixels *	8 MP	Power source type *	DC, PoE
Video compression formats	H.264, H.264+, H.265, H.265+	Power consumption (max)	18 W
	1280 x 720 (HD 720), 1920 x 1080 (HD 1080), 2048 x 1280, 2304 x 1296, 2560 x 1440, 2688 x 1520,	Power consumption (Power over	21 W
Supported graphics resolutions		Ethernet (PoE)) DC output voltage	12
	2880 x 1620, 3840 x 2160	, ,	12
Video recording	✓	Operational conditions	
Image quality adjustment	Brightness, Contrast, Mirror, Saturation, Sharpness	Operating temperature (T-T) Storage temperature (T-T)	-30 - 60 °C -40 - 60 °C
Bit rate control	Constant Bit Rate (CBR)/Variable Bit Rate (VBR)	Operating relative humidity (H-H)	0 - 95%
Bit rate	Main Stream: 256 Kbps to 8 Mbps, Sub-Stream: 64 Kbps to 1024 Kbps	Storage relative humidity (H-H)  Weight & dimensions	0 - 95%
Back Light Compensation (BLC)	<b>✓</b>	Width	112.3 mm
Highlight Compensation (HLC)	<b>✓</b>	Depth	112.3 mm
Digital Wide Dynamic Range	/	Height	110.2 mm
(DWDR)	•	Weight	760 g
Audio		Packaging content	
Built-in speaker(s)	✓	Number of cameras *	1
Audio system	2-way	Mounting kit	✓
Audio input channels	1.0 channels	Screws included	✓
		Drilling template included	✓
		Manual	✓



8885020627886

## **Catalog Object Cloud**



Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.