



TP-Link InSight S245ZI Dome IP security camera Outdoor 2688 x 1520 pixels Ceiling

Brand : TP-Link

Product code: INSIGHT S245ZI

Product name : InSight S245ZI

- 5X Optical Zoom for Easy Installation and Monitoring
- 4MP Super-High Definition and IR Range Up to 197 ft (60 m)*1
- Human & Vehicle Classification
- Smart Detection
- Smart Video Enhancement Technology
- Audio and Alarm Interface Available
- IP67 Weatherproof and IK10 Vandal Proof
- H.265+ Compression Technology

VIGI 4MP IR Motorized Varifocal Dome Network Camera, 1/2.9", 1/3 to 1/10000 s, 2.7-13.5 mm (5X Optical Zoom), F1.6, 2688 x 1520, CBR, VBR, BLC/3D DNR/HLC/SmartIR, 120 dB, 12V DC \pm 5%, Max. 10.8 W, 5.5 mm Coaxial Power Plug, PoE: 802.3af/at, class 0, Max. 12 W, IP67, 129.9 x 129.9 x 102.5 mm, 0.775 kg, White



Performance		Audio	
Type *	IP security camera	Audio input channels	1.0 channels
Placement supported *	Outdoor	Audio output channels	1.0 channels
Connectivity technology *	Wired	Audio formats supported	G.711 A-law
Maximum operating distance	200 m	Sample rate	8 kHz
Wide Dynamic Range (WDR)	✓	Built-in microphone	✓
Day/night mode	✓	Number of microphones	1
Infrared (IR) cut-off filter	✓	Bit rate range	0 - 64 Kbit/s
Remote viewing	✓	Network	
Dynamic range	120 dB	Ethernet LAN *	✓
Design		Networking standards	IEEE 802.3af, IEEE 802.3at
Form factor *	Dome	Supported network protocols	TCP/IP, UDP, ICMP, HTTP, HTTPS, DHCP, DNS, RTSP, NTP, UPnP UDP, SSL/TLS, FTP/SFTP, RTP, IPv4, IPv6, ARP
Mounting type *	Ceiling		
Product colour *	White	Wi-Fi *	✗
Housing material	Metal	Bluetooth *	✗
Protection features	Waterproof	Live view	✓
International Protection (IP) code	IP67	Storage	
IK code	IK10	Compatible memory cards	MicroSD (TransFlash)
Weatherproof	✓	Maximum memory card size	512 GB
Camera		Ports & interfaces	
Camera pan control	✓	Ethernet LAN (RJ-45) ports	1
Camera tilt control	✓	DC-in jack	✓
Minimum illumination	0 lx	Security	
Lens viewing angle, horizontal	29.6 - 102°	Built-in siren	✓
Lens viewing angle, vertical	16.8 - 53.8°	Password protection	✓
Lens viewing angle, diagonal	34.1 - 122.8°	Video motion detection	✓
Tilt angle range	0 - 75°	IP address filtering	✓
Camera shutter speed	1/3 to 1/10000	HTTPS encryption	✓
Image sensor			
Optical sensor size	25.4 / 2.9 mm (1 / 2.9")		

Image sensor		Security	
Progressive scan	✓	Detection distance	200 m
Sensor type *	CMOS	Alert notification type	Push notification
Lens system		Intelligent Video Surveillance (IVS) system features	Abnormal sound detection, Crossing line, Human detection, Intrusion, Line crossing detection, Moving object, Region entrance detection, Region exiting detection, Scene change, Vehicle detection
Optical zoom	5x		
Detect distance	200 m		
Observe distance	84 m		
Recognize distance	40 m	Motion sensor	✓
Auto focus	✓	Mirror	✓
Focus	Motorized	Human and vehicle targets classification	✓
Maximum aperture number	1.6	Digest authentication	✓
Identify distance	21 m	Management features	
Night vision		Web-based management	✓
Night vision *	✓	Web browser	✓
LED type	IR/White	Cloud-managed *	✓
Video		Reset button	✓
Maximum resolution *	2688 x 1520 pixels	Power	
Total megapixels *	4 MP	Power source type *	DC, PoE
Video compression formats	H.264, H.264+, H.265, H.265+	Power consumption (max)	10.8 W
Supported graphics resolutions	1280 x 720 (HD 720), 1920 x 1080 (HD 1080), 2048 x 1280, 2304 x 1296, 2560 x 1440, 2688 x 1520	Power consumption (Power over Ethernet (PoE))	12 W
Video recording	✓	DC output voltage	12
Image quality adjustment	Brightness, Contrast, Mirror, Saturation, Sharpness	Operational conditions	
Bit rate control	Constant Bit Rate (CBR)/Variable Bit Rate (VBR)	Operating temperature (T-T)	-30 - 60 °C
Bit rate	Main Stream: H.265+/H.265/H.264+/H.264, Sub-Stream: H.265/H.264	Storage temperature (T-T)	-40 - 60 °C
Back Light Compensation (BLC)	✓	Operating relative humidity (H-H)	0 - 95%
Highlight Compensation (HLC)	✓	Storage relative humidity (H-H)	0 - 95%
Digital Wide Dynamic Range (DWDR)	✓	Weight & dimensions	
Audio		Width	129.9 mm
Built-in speaker(s)	✓	Depth	129.9 mm
Audio system	2-way	Height	102.5 mm
		Weight	775 g
		Packaging data	
		Package type	Box
		Packaging content	
		Number of cameras *	1
		Manual	✓

Catalog Object Cloud



Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.