

NETGEAR MS108UP Unmanaged 2.5G Ethernet (100/1000/2500) Power over Ethernet (PoE)

Brand : NETGEAR

Product code: MS108UP-100NAS

Product name : MS108UP

MS108UP - 8-port Multi-Gigabit (2.5G) Ultra60 PoE++ Ethernet Unmanaged Switch

NETGEAR MS108UP Unmanaged 2.5G Ethernet (100/1000/2500) Power over Ethernet (PoE):

NETGEAR brings the first Unmanaged

Multi-Gigabit PoE++ switch MS108UP with 60Watts per port Ultra60 PoE++ technology, ideal for powerful PoE++ installations with PoE budgets up to 230W, a compact size, plug-and-play installation, and reliable performance at affordable prices. The new model MS108UP supports 2.5 Gigabit speed connectivity and Power-Over-Ethernet (PoE) that can provide up to 60W/port. The new switch model can power devices such as VoIP phones, surveillance IP cameras, wireless access points and many other applications. This new Unmanaged switch provides PoE Auto-Balance to help automatically balance the PoE power based on the device needs independent of PoE class detected. With the growing deployment of applications and an allin-one solution, providing multi-speed and high power to these applications would be ideal.

Management features		Design	
Switch type *	Unmanaged	Wall mountable	✓
Quality of Service (QoS) support	✓	Number of fans	0 fan(s)
Ports & interfaces		Electromagnetic compatibility	CE, FCC part 15 Class B, ISED, VCCI, KC, CCC, BSMI, RCM
Basic switching RJ-45 Ethernet ports quantity *	8	Performance	
Basic switching RJ-45 Ethernet ports type *	2.5G Ethernet (100/1000/2500)	Fanless	✓
2.5G Ethernet (copper) ports quantity	8	Mean time between failures (MTBF)	373643.7 h
Network		Power	
Networking standards *	IEEE 802.1p, IEEE 802.3, IEEE 802.3ab, IEEE 802.3af, IEEE 802.3at, IEEE 802.3az, IEEE 802.3bt, IEEE 802.3u, IEEE 802.3x	Power source *	DC
		Power supply included *	✓
		DC input voltage	54 V
		Input current	4.7 A
10G support *	✗	Power over Ethernet (PoE)	
Full duplex	✓	Power over Ethernet (PoE) *	✓
Half duplex	✓	Power over Ethernet plus (PoE+) ports quantity	8
Auto MDI/MDI-X	✓	Total Power over Ethernet (PoE) budget	230 W
Head-of-line (HOL) blocking	✓	Operational conditions	
Ethernet LAN data rates	100,1000,2500 Mbit/s	Operating temperature (T-T)	0 - 40 °C
Auto-sensing	✓	Storage temperature (T-T)	-20 - 70 °C
VLAN support	✓	Operating relative humidity (H-H)	0 - 90%
Number of VLANs	64	Operating altitude	0 - 3000 m
Data transmission		Heat dissipation	923.49 BTU/h
Switching capacity *	40 Gbit/s	Weight & dimensions	
MAC address table *	16000 entries	Width	210 mm
Latency (1 Gbps)	3.593 µs	Depth	140 mm
Jumbo frames support	✓	Height	40 mm
Jumbo frames	12000	Weight	900 g
Packet forwarding rate (1 Gbps)	1488000 pps	Certificates	
Packet buffer memory	1.5 MB	Certification	CB, CSA, CCC, BSMI, RCM
Design			
Rack mounting *	✗		

Design

Housing material	Metal
------------------	-------



0606449156898



606449156898

Catalog Object Cloud



Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.