



## TP-Link Omada 52-Port Gigabit L2+ Managed Switch with 48-Port PoE+

**Brand :** TP-Link

**Product family:** Omada

**Product code:** SG3452P



**Product name :** Omada 52-Port Gigabit L2+ Managed Switch with 48-Port PoE+

48x Gigabit 802.3af/at PoE+, 4x Gigabit SFP, 1x RJ45 Console, 1x Micro-USB Console, 104 Gbps, 16 K MAC, 9 KB Jumbo, 440 x 330 x 44 mm

### TP-Link Omada 52-Port Gigabit L2+ Managed Switch with 48-Port PoE+:

TP-Link | Omada L2+ managed switches provide high performance, powerful L2 and L2+ features like static routing, enterprise-level QoS, advanced security strategies and a bundle of ISP features. The IP-MAC-Port Binding (IMPB) and Access Control List (ACL) functions protect against broadcast storm, ARP and Denial-of-Service (DoS) attacks, etc. Quality of Service (QoS, L2 to L4) provides enhanced traffic management capabilities to move your data smoother and faster. The OAM and DDM functions help facilitate network management. Moreover, the easy-to-use web management interfaces, along with CLI, SNMP and Dual Image mean faster setup and configuration with less downtime. TP-Link | Omada L2+ managed Switches provide a reliable, secure solution for enterprise, campus and ISP networks.

Management features		Security	
Switch type *	Managed	Loop protection	✓
Switch layer	L2/L3	BPDU filtering/protection	✓
Quality of Service (QoS) support	✓	Authentication	MAC-based authentication, Port-based authentication
Web-based management	✓	Password protection	✓
Cloud-managed	✓	Multicast features	
ARP inspection	✓	Multicast support	✓
System event log	✓	Protocols	
MIB support	Yes	Management protocols	SNMPv1/v2c/v3, SNTp
Ports & interfaces		GARP VLAN Registration Protocol (GVRP)	✓
Basic switching RJ-45 Ethernet ports quantity *	48	Design	
Basic switching RJ-45 Ethernet ports type *	Gigabit Ethernet (10/100/1000)	Rack mounting *	✓
SFP module slots quantity	4	Form factor	1U
Console port	RJ-45/micro-USB	Product colour	Black
Power connector	AC-in jack	Reset button	✓
Network		LED indicators	✓
Networking standards *	IEEE 802.1D, IEEE 802.1p, IEEE 802.1s, IEEE 802.1w, IEEE 802.3ad, IEEE 802.3x	Number of fans	3 fan(s)
10G support *	✗	Power	
Port mirroring	✓	Power source *	AC
IP routing	✓	Power supply included *	✓
Policy-based routing	✓	AC input voltage	100 - 240 V
Flow control support	✓	AC input frequency	50/60 Hz
Link aggregation	✓	Power consumption (max)	464.2 W
Broadcast storm control	✓	Power over Ethernet (PoE)	
Rate limiting	✓	Power over Ethernet (PoE) *	✓
Spanning tree protocol	✓	Power over Ethernet plus (PoE+) ports quantity	48
Head-of-line (HOL) blocking	✓	Power over Ethernet (PoE) power per port	30 W
Ethernet LAN data rates	10,100,1000 Mbit/s	Total Power over Ethernet (PoE) budget	384 W
Active link detection	✓		
VLAN support	✓		

Network		Operational conditions	
Virtual LAN features	MAC address-based VLAN, Private VLAN, Protocol-based VLAN, Tagged VLAN, Voice VLAN	Operating temperature (T-T)	0 - 40 °C
Number of VLANs	4000	Storage temperature (T-T)	-40 - 70 °C
Data transmission		Operating relative humidity (H-H)	10 - 90%
Switching capacity *	104 Gbit/s	Storage relative humidity (H-H)	5 - 90%
Forwarding rate	77.38 Mpps	Heat dissipation	1584.08 BTU/h
MAC address table *	16000 entries	Weight & dimensions	
Store-and-forward	✓	Width	440 mm
Static route	✓	Depth	330 mm
Number of static routes	48	Height	44 mm
Jumbo frames support	✓	Packaging content	
Jumbo frames	9000	Cables included	AC
Packet buffer memory	12 MB	Quick start guide	✓
Security		Manual	✓
DHCP features	DHCP client, DHCP relay, DHCP server, DHCP snooping, DHCPv6 client, DHCPv6 snooping	Packaging data	
Access Control List (ACL)	✓	Package type	Box
IGMP snooping	✓		
SSH/SSL support	✓		



6935364006273

### Catalog Object Cloud



Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.