

## GIGABYTE UD750GM PG5 V2 ICE Power Supply Unit- PCIe Gen 5.1, 80 PLUS Gold, Fully Modular Design, 120mm Fan, ATX 3.1 compatible, EU Plug



**Brand :** GIGABYTE

**Product code:** GP-UD750GM PG5 ICE EU

**Product name :** UD750GM PG5 V2 ICE Power Supply Unit- PCIe Gen 5.1, 80 PLUS Gold, Fully Modular Design, 120mm Fan, ATX 3.1 compatible, EU Plug

- Intel ATX 3.1 and PCIe Gen 5.1 ready
- 80 PLUS Gold certified
- Fully modular design
- Powerful single +12V rail
- Compact size
- 100% Japanese capacitors
- 120mm smart hydraulic bearing (HYB) fan
- Optimized thermal solution
- OVP/OPP/SCP/UVF/OCP/OTP protection

UD750GM PG5 V2 ICE Power Supply Unit- PCIe Gen 5.1, 80 PLUS Gold, Fully Modular Design, 120mm Fan, ATX 3.1 compatible, EU Plug

[GIGABYTE UD750GM PG5 V2 ICE Power Supply Unit- PCIe Gen 5.1, 80 PLUS Gold, Fully Modular Design, 120mm Fan, ATX 3.1 compatible, EU Plug:](#)

Ensure reliable and efficient power delivery with GIGABYTE power supplies. Designed for peak performance and durability, our PSUs offer stable and consistent energy to power your high-performance systems. With advanced protections and high-quality components, GIGABYTE power supplies provide the confidence you need for seamless, uninterrupted computing experiences.

Power		Ports & interfaces	
Total power *	750 W	PCI Express power cable length	60 cm
AC input voltage *	100 - 240 V	CPU power connector (4+4 pin)	✓
AC input frequency	50/60 Hz	CPU power cable length	65 cm
Input current	12 - 6.5 A	Floppy drive power connector	1
Power factor	0.9	PCI Express connector	✓
Power Factor Correction (PFC) type	Active	Number of EPS connectors	2
Combined power (+3.3V)	105 W	Cabling type	Fully-Modular
Combined power (+12V)	750 W		
Combined power (+5V)	105 W		
Combined power (-12V)	3.6 W		
Combined power (+5Vsb)	15 W		
Max output current (+3.3V)	20 A		
Max output current (+12V)	62.5 A		
Max output current (+5V)	20 A		
Max output current (-12V)	0.3 A		
Max output current (+5Vsb)	3 A		
Hold time	16 ms		
Efficiency	90%		
Power protection features	Over current, Over power, Over voltage, Overheating, Short circuit, Under voltage		
Ports & interfaces		Performance	
Motherboard power connector *	20+4 pin ATX	80 PLUS certification *	80 PLUS Gold
Motherboard power cable length	61 cm	Purpose *	PC
Number of SATA power connectors	8	Power supply unit (PSU) form factor *	ATX
Peripheral (Molex) power connectors (4-pin) *	3	ATX version	3.1
PCI Express power connectors (6+2 pin)	4	Bearing technology	HYB
		Mean time between failures (MTBF)	100000 h
		Design	
		Product colour	White
		Cooling type	Active
		Fan diameter	12 cm
		Number of fans	1 fan(s)
		On/off switch	✓
		Weight & dimensions	
		Width	150 mm
		Depth	140 mm
		Height	86 mm
		Weight	2.34 kg

Ports & interfaces		Packaging data	
PCI Express power connectors (12+4 pin)	1	Package width	618 mm
PCI Express power connectors (12+4 pin) cable length	700 mm	Package depth	269 mm
		Package height	211 mm
		Package weight	2.5 kg
		Package type	Box
		Logistics data	
		Warranty period	5 year(s)



4719331556310

### Catalog Object Cloud



Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.