

GIGABYTE UD750GM PG5 V2 ICE Power Supply Unit- PCIe Gen 5.1, 80 PLUS Gold, Fully Modular Design, 120mm Fan, ATX 3.1 compatible, EU Plug

Brand : GIGABYTE

Product code: GP-UD750GM PG5 ICE EU

Product name : UD750GM PG5 V2 ICE Power Supply Unit- PCIe Gen 5.1, 80 PLUS Gold, Fully Modular Design, 120mm Fan, ATX 3.1 compatible, EU Plug

- Intel ATX 3.1 and PCIe Gen 5.1 ready
- 80 PLUS Gold certified
- Fully modular design
- Powerful single +12V rail
- Compact size
- 100% Japanese capacitors
- 120mm smart hydraulic bearing (HYB) fan
- Optimized thermal solution
- OVP/OPP/SCP/UVF/OCP/OTP protection

UD750GM PG5 V2 ICE Power Supply Unit- PCIe Gen 5.1, 80 PLUS Gold, Fully Modular Design, 120mm Fan, ATX 3.1 compatible, EU Plug

GIGABYTE UD750GM PG5 V2 ICE Power Supply Unit- PCIe Gen 5.1, 80 PLUS Gold, Fully Modular Design, 120mm Fan, ATX 3.1 compatible, EU Plug:

Ensure reliable and efficient power delivery with GIGABYTE power supplies. Designed for peak performance and durability, our PSUs offer stable and consistent energy to power your high-performance systems. With advanced protections and high-quality components, GIGABYTE power supplies provide the confidence you need for seamless, uninterrupted computing experiences.



| Power | | Ports & interfaces | |
|---|---|---------------------------------------|---------------|
| Total power * | 750 W | PCI Express power cable length | 60 cm |
| AC input voltage * | 100 - 240 V | CPU power connector (4+4 pin) | ✓ |
| AC input frequency | 50/60 Hz | CPU power cable length | 65 cm |
| Input current | 12 - 6.5 A | Floppy drive power connector | 1 |
| Power factor | 0.9 | PCI Express connector | ✓ |
| Power Factor Correction (PFC) type | Active | Number of EPS connectors | 2 |
| Combined power (+3.3V) | 105 W | Cabling type | Fully-Modular |
| Combined power (+12V) | 750 W | Performance | |
| Combined power (+5V) | 105 W | 80 PLUS certification * | 80 PLUS Gold |
| Combined power (-12V) | 3.6 W | Purpose * | PC |
| Combined power (+5Vsb) | 15 W | Power supply unit (PSU) form factor * | ATX |
| Max output current (+3.3V) | 20 A | ATX version | 3.1 |
| Max output current (+12V) | 62.5 A | Bearing technology | HYB |
| Max output current (+5V) | 20 A | Mean time between failures (MTBF) | 100000 h |
| Max output current (-12V) | 0.3 A | Design | |
| Max output current (+5Vsb) | 3 A | Product colour | White |
| Hold time | 16 ms | Cooling type | Active |
| Efficiency | 90% | Fan diameter | 12 cm |
| Power protection features | Over current, Over power, Over voltage, Overheating, Short circuit, Under voltage | Number of fans | 1 fan(s) |
| | | On/off switch | ✓ |
| Ports & interfaces | | Weight & dimensions | |
| Motherboard power connector * | 20+4 pin ATX | Width | 150 mm |
| Motherboard power cable length | 61 cm | Depth | 140 mm |
| Number of SATA power connectors | 8 | Height | 86 mm |
| Peripheral (Molex) power connectors (4-pin) * | 3 | Weight | 2.34 kg |
| PCI Express power connectors (6+2 pin) | 4 | | |

| Ports & interfaces | | Packaging data | |
|--|--------|-----------------|-----------|
| PCI Express power connectors (12+4 pin) | 1 | Package width | 618 mm |
| PCI Express power connectors (12+4 pin) cable length | 700 mm | Package depth | 269 mm |
| | | Package height | 211 mm |
| | | Package weight | 2.5 kg |
| | | Package type | Box |
| | | Logistics data | |
| | | Warranty period | 5 year(s) |



4719331556310

Catalog Object Cloud



Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.