

Tripp Lite 10kW 3-Phase Monitored PDU, LX Interface, 200/208/240V Outlets (42 C13/6 C19), LCD, IEC-309 30A Blue, 1.8m/6 ft. Cord, 0U 1.8m/70 in. Height, TAA


Brand : Tripp Lite

Product code: PDU3EVN6G30B

Product name : 10kW 3-Phase Monitored PDU, LX Interface, 200/208/240V Outlets (42 C13/6 C19), LCD, IEC-309 30A Blue, 1.8m/6 ft. Cord, 0U 1.8m/70 in. Height, TAA

10kW 3-Phase Monitored PDU, LX Interface, 200/208/240V Outlets (42 C13/6 C19), LCD, IEC-309 30A Blue, 1.8m/6 ft. Cord, 0U 1.8m/70 in. Height, TAA

Tripp Lite 10kW 3-Phase Monitored PDU, LX Interface, 200/208/240V Outlets (42 C13/6 C19), LCD, IEC-309 30A Blue, 1.8m/6 ft. Cord, 0U 1.8m/70 in. Height, TAA. PDU types: Monitored, Rack capacity: 0U, Type: Three-phase. AC outlets quantity: 48 AC outlet(s), AC outlet types: C13 coupler, C19 coupler, Power plug: IEC309. Cable length: 1.8 m. Supported network protocols: IPv4, IPv6, HTTP, HTTPS, SMTP, SNMPv1, SNMPv2, SNMPv3, telnet, SSH, FTP, DHCP. Nominal input voltage: 200-240 V, Maximum current: 24 A, AC input frequency: 50 - 60 Hz



Design		Weight & dimensions	
PDU types *	Monitored	Depth	72.6 mm
Type	Three-phase	Dimensions (WxDxH)	55 x 73 x 1778 mm
Rack capacity *	0U	Height	1778 mm
Mounting	Vertical	Weight	6.89 kg
Housing material	Metal	Packaging data	
Product colour	Black, Grey	Package weight	9.96 kg
Display	LCD	Package width	245.1 mm
Ports & interfaces		Package depth	1927.1 mm
AC outlets quantity *	48 AC outlet(s)	Package height	175 mm
Power plug	IEC309	Packaging content	
AC outlet types *	C13 coupler, C19 coupler	Manual	✓
Features		Operational conditions	
Cable length	1.8 m	Operating temperature (T-T)	0 - 50 °C
Management features		Storage temperature (T-T)	-15 - 60 °C
Supported network protocols	IPv4, IPv6, HTTP, HTTPS, SMTP, SNMPv1, SNMPv2, SNMPv3, telnet, SSH, FTP, DHCP	Operating relative humidity (H-H)	5 - 95%
		Operating altitude	0 - 3000 m
Power		Technical details	
Nominal input voltage *	200-240 V	Sustainability certificates	RoHS
AC input frequency	50 - 60 Hz	Logistics data	
Maximum current *	24 A	Country of origin	Taiwan
Nominal output voltage	200-240 V	Products per master (outer) case	1 pc(s)
Maximum power	10000 W		
Weight & dimensions			
Width	55.1 mm		



0037332195371



037332195371

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 24-APR-2024. Prints or copies of Information are only valid on the printed Publication date