Product data sheet

Specifications



APC Rack PDU 9000 Switched, ZeroU, 17.3kW, 208V, (20) C13/ C15, (12) C19/C21

APDU9966

UV	er	VI	e	W
----	----	----	---	---

Lead time Usually in Stock

Main

wan	
Main Input Voltage	208 V 3 phase
Main Output Voltage	208 V
Input Connection Type	IEC 60309 60 A 3P+PE
Cable length	6 ft (1.83 m)
Number of cables	1
Communication Port Protocol	SNMP Redfish
Provided Equipment	Installation guide Rack Mounting brackets Safety guide

Physical

Color	Black
Height	72.17 in (183.3 cm)
Width	4.37 in (11.1 cm)
Depth	2.99 in (7.6 cm)
Net Weight	30.86 lb(US) (14 kg)
Mounting Location	Side
Mounting preference	No preference
Mounting Mode	Rack-mounted

Input

Line Rated Current	48 A
Max line current	48 A
Input current limits	60 A
Load Capacity	17300 VA
Input Frequency	50/60 Hz

Output

Number of power socket outlets 20 C13/C15

12 C19/C21

Conformance

Product Certifications cUL Listed FCC part 15 class A

0...50000 ft (0.00...15240.00 m)

IEC 62368-1 **Standards**

Environmental

23...140 °F (-5...60 °C) Ambient air temperature for operation **Relative Humidity** 5...95 % 0...10000 ft Operating altitude -13...149 °F (-25...65 °C) **Ambient Air Temperature for** Storage **Storage Relative Humidity** 5...95 %

Batteries & Runtime

Storage altitude

Communication Network Type 10/100/1000BASE-T

Ordering and shipping details

731304356332 **GTIN**

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	84.61 in (214.9 cm)
Package 1 Width	4.41 in (11.2 cm)
Package 1 Length	8.70 in (22.1 cm)
Package 1 Weight	44.00 lb(US) (19.96 kg)

Offer Sustainability

EU RoHS Directive	Under investigation
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.

Contractual warranty

Warranty 3 years repair or replace

Recommended replacement(s)