

## Brother ADS-1300 scanner ADF scanner 600 x 600 DPI A4 White

**Brand :** Brother

**Product code:** ADS-1300

**Product name :** ADS-1300

- Scan up to 30ppm
- 60ipm, 2-sided colour scan
- 20 Sheet Automatic Document Feeder (ADF)
- Power directly via USB Type-C
- Control up to 3 scan activity shortcuts direct from the device
- Dedicated plastic ID card slot

Power directly from your laptop using USB Type-C, so you can scan, save and share where it's most convenient to you.

Brother ADS-1300 scanner ADF scanner 600 x 600 DPI A4 White:

Make everyday document scanning simple with the ADS-1300 compact, portable document scanner. Scan and save your paper documents wherever you are working. Whether its utility bill, business documents or medical forms, once plugged into your laptop, you can scan and securely store data digitally and have instant access whenever you need it. Scan to PC, Cloud, USB Host PDF editing software included Optional paper output tray available \*See datasheet for detailed technical information



Scanning		Ports & interfaces	
Maximum scan size *	215.9 x 355.6 mm	USB port *	✓
Optical scanning resolution *	600 x 600 DPI	USB connector type	USB Type-C
Enhanced scan resolution	1200 x 1200 DPI		
Duplex scanning *	✓		
Greyscale levels	256		
ADF scan speed (b/w, A4)	7 ppm		
Design		Power	
Scanner type *	ADF scanner	Power supply type *	USB
Product colour *	White	Power consumption (typical)	11 W
Control type	Buttons	Power consumption (off)	0.1 W
Built-in display *	✗		
Performance		Weight & dimensions	
Scan to	PC	Width	288 mm
Scan drivers	ICA, SANE, TWAIN, WIA	Depth	101 mm
		Height	85 mm
		Weight	1.37 kg
Paper handling		Packaging data	
Scanning media types supported	Business Card, Plastic Card, Thick paper, Plain paper, Recycled paper, Thin paper	Package width	158 mm
Maximum ISO A-series paper size *	A4	Package depth	200 mm
Card thickness (max)	1.24 mm	Package height	369 mm
Paper tray media weight	51.8 - 128 g/m <sup>2</sup>	Package weight	2.36 kg
		Packaging content	
		Cables included	USB
		Operational conditions	
		Operating temperature (T-T)	5 - 35 °C
		Operating relative humidity (H-H)	20 - 80%



0012502674221



012502674221

### Catalog Object Cloud



Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.