StarTech.com OAM Managed Gigabit Ethernet Fiber Media Converter - Multi Mode LC 550m - 802.3ah Compliant

Brand : StarTech.com

Product code: ET91000LCOAM

Product name : OAM Managed Gigabit Ethernet Fiber Media Converter - Multi Mode LC 550m - 802.3ah Compliant

StarTech.com Multimode (MM) LC Fiber Media Converter with SFP - OAM Management - 802.3ah Compliant - Gigabit Ethernet - 550m - 850nm (ET91000LCOAM)
StarTech.com OAM Managed Gigabit Ethernet Fiber Media Converter - Multi Mode LC 550m - 802.3ah Compliant. Maximum data transfer rate: 1250 Mbit/s, Converter input interface: 1000Base-LX, 1000Base-SX, 1000Base-T, 100Base-TX, 10Base-T, Converter output interface: 1000Base-LX, 1000Base-SX. Maximum transfer distance: 550 m, Wavelength: 850 nm, Fiber mode structure: Multi-mode. LED indicators: LAN, Link, Power, Product colour: Black, Housing material: Steel. Fiber optic connector: LC, Connectivity technology: Wired. Input voltage: 100 - 240 V, Input current: 0.36 A, Output voltage: 12 V

Network

Maximum data transfer rate *	1250 Mbit/s
Converter input interface	1000Base-LX, 1000Base-SX, 1000Base-T, 100Base-TX, 10Base-T
Converter output interface	1000Base-LX, 1000Base-SX
Networking standards	IEEE 802.3, IEEE 802.3ab, IEEE 802.3ah, IEEE 802.3u, IEEE 802.3z
Ethernet interface type	Gigabit Ethernet
Ethernet LAN data rates	10,100,1000 Mbit/s
Auto MDI/MDI-X	✔
Duplex system	Full, Half

Performance

Maximum transfer distance *	550 m
Wavelength *	850 nm
Fiber mode structure	Multi-mode
Mean time between failures (MTBF)	65000 h

Features

Internal *	✗
LED indicators	LAN, Link, Power
Product colour	Black
Housing material	Steel

Ports & interfaces

Connectivity technology	Wired
Ethernet LAN (RJ-45) ports	1
Fiber ports quantity	1
Fiber optic connector *	LC
DC-in jack	✔

Power

Input current	0.36 A
Output voltage	12 V
Output current	1 A
Power over Ethernet (PoE)	✗
External power adapter	✔

Weight & dimensions

Width	87 mm
Depth	163 mm
Height	23 mm
Weight	411 g

Operational conditions

Operating temperature (T-T)	0 - 60 °C
Storage temperature (T-T)	-10 - 70 °C
Operating relative humidity (H-H)	10 - 90%

Packaging content

Manual	✔

Packaging data

Package width	136 mm
Package depth	206 mm
Package height	92 mm
Package weight	789 g

Certificates

Compliance certificates	RoHS
Certification	FCC, CE

Logistics data

Harmonized System (HS) code	85176990

Power

Input voltage	100 - 240 V

0065030854566

065030854566

0662300782262

662300782262

Catalog Object Cloud