



# APC Rack PDU 2G, Metered, ZeroU, 17.3kW, 240V, (30) C13 & (12) C19



Brand : APC

Product code: AP8887

Product name : Rack PDU 2G, Metered, ZeroU, 17.3kW, 240V, (30) C13 & (12) C19

Rack PDU 2G, Metered, ZeroU, 17.3kW, 240V, (30) C13 & (12) C19

APC Rack PDU 2G, Metered, ZeroU, 17.3kW, 240V, (30) C13 & (12) C19:

APC Metered Rack Power Distribution Units (PDUs) provide active metering to enable energy optimization and circuit protection. User-defined alarm thresholds mitigate risk with real-time local and remote alerts to warn of potential circuit overloads. Metered Rack PDUs provide power utilization data to allow Data Center Managers to make informed decisions on load balancing and right sizing IT environments to lower total cost of ownership. Metered Rack PDUs include real power monitoring, a temperature/humidity sensor port, locking IEC receptacles, and ultra low profile circuit breakers. Users can access and configure Metered Rack PDUs through secure Web, SNMP, or Telnet Interfaces which are complimented by APC Centralized Management platforms using InfraStruxure Central, Operations, Capacity, and Energy Efficiency.

Design		Certificates	
PDU types *	Metered	Compliance certificates	RoHS
Rack capacity *	0U	Certification	cUL, EN 55022 A, EN 55024, EN 61000-3-2, EN 61000-3-3, FCC-15 A, UL, VCCI A
Mounting	Horizontal/Vertical	<b>Operational conditions</b>	
Product colour	Black	Operating temperature (T-T)	0 - 55 °C
Display	LCD	Storage temperature (T-T)	-25 - 65 °C
<b>Ports &amp; interfaces</b>		Operating relative humidity (H-H)	5 - 95%
AC outlets quantity *	42 AC outlet(s)	Storage relative humidity (H-H)	5 - 95%
AC outlet types *	C13 coupler, C19 coupler	Operating altitude	0 - 3000 m
Input connection type	IEC 309 30A 3P+N+E	Non-operating altitude	0 - 15000 m
<b>Features</b>		<b>Weight &amp; dimensions</b>	
Cable length	1.83 m	Width	56 mm
<b>Power</b>		Depth	51 mm
Nominal input voltage *	400 V	Height	1829 mm
AC input frequency	50 - 60 Hz	Weight	9.6 kg
Maximum current *	30 A	<b>Packaging data</b>	
Nominal output voltage	240 V	Package weight	13.6 kg
Output voltage	240 V	Package width	221 mm
Load capacity	17300 VA	Package depth	112 mm
Maximum input current per phase	30 A	Package height	2149 mm
Maximum total current draw per phase	24 A	<b>Logistics data</b>	
Power protection features	Overload	Total carbon footprint (kg of CO2e)	67314.89



0731304292432



731304292432

### Catalog Object Cloud



Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.