



APC Rack PDU 2G, Metered, ZeroU, 17.3kW, 240V, (30) C13 & (12) C19

Brand : APC

Product code: AP8887

Product name : Rack PDU 2G, Metered, ZeroU, 17.3kW, 240V, (30) C13 & (12) C19


Rack PDU 2G, Metered, ZeroU, 17.3kW, 240V, (30) C13 & (12) C19

APC Rack PDU 2G, Metered, ZeroU, 17.3kW, 240V, (30) C13 & (12) C19:

APC Metered Rack Power Distribution Units (PDUs) provide active metering to enable energy optimization and circuit protection User-defined alarm thresholds mitigate risk with real-time local and remote alerts to warn of potential circuit overloads Metered Rack PDUs provide power utilization data to allow Data Center Managers to make informed decisions on load balancing and right sizing IT environments to lower total cost of ownership Metered Rack PDUs include real power monitoring, a temperature/humidity sensor port, locking IEC receptacles, and ultra low profile circuit breakers Users can access and configure Metered Rack PDUs through secure Web, SNMP, or Telnet Interfaces which are complimented by APC Centralized Management platforms using InfraStruxure Central, Operations, Capacity, and Energy Efficiency

Design		Certificates	
PDU types *	Metered	Compliance certificates	RoHS
Rack capacity *	0U	Certification	cUL, EN 55022 A, EN 55024, EN 61000-3-2, EN 61000-3-3, FCC-15 A, UL, VCCI A
Mounting	Horizontal/Vertical		
Product colour	Black	Operational conditions	
Display	LCD	Operating temperature (T-T)	0 - 55 °C
Ports & interfaces		Storage temperature (T-T)	-25 - 65 °C
AC outlets quantity *	42 AC outlet(s)	Operating relative humidity (H-H)	5 - 95%
AC outlet types *	C13 coupler, C19 coupler	Storage relative humidity (H-H)	5 - 95%
Input connection type	IEC 309 30A 3P+N+E	Operating altitude	0 - 3000 m
Features		Non-operating altitude	0 - 15000 m
Cable length	1.83 m	Weight & dimensions	
Power		Width	56 mm
Nominal input voltage *	400 V	Depth	51 mm
AC input frequency	50 - 60 Hz	Height	1829 mm
Maximum current *	30 A	Weight	9.6 kg
Nominal output voltage	240 V	Packaging data	
Output voltage	240 V	Package weight	13.6 kg
Load capacity	17300 VA	Package width	221 mm
Maximum input current per phase	30 A	Package depth	112 mm
Maximum total current draw per phase	24 A	Package height	2149 mm
Power protection features	Overload	Logistics data	
		Total carbon footprint (kg of CO2e)	67314.89





0731304292432



731304292432

Catalog Object Cloud



Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.