

Tripp Lite SmartPro 120V 750VA 450W Line-Interactive UPS, AVR (Boost only), Tower, USB


Brand : Tripp Lite

Product code: SMART750USB

Product name : SmartPro 120V 750VA 450W Line-Interactive UPS, AVR (Boost only), Tower, USB

SmartPro 120V 750VA 450W Line-Interactive UPS, AVR (Boost only), Tower, USB

Tripp Lite SmartPro 120V 750VA 450W Line-Interactive UPS, AVR (Boost only), Tower, USB. UPS topology: Line-Interactive, Output power capacity: 0.75 kVA, Output power: 450 W. AC outlet types: NEMA 5-15R, Power plug: NEMA 5-15P, AC outlets quantity: 6 AC outlet(s). Typical backup time at full load: 2.2 min, Typical backup time at half load: 8.3 min, Battery recharge time: 4.5 h. Form factor: Tower, Product colour: Black, Housing material: Polyvinyl chloride (PVC). Width: 133.4 mm, Depth: 190.5 mm, Height: 271.5 mm



Features		Design	
UPS topology *	Line-Interactive	Form factor *	Tower
Output power capacity *	0.75 kVA	Housing material	Polyvinyl chloride (PVC)
Output power *	450 W	Cable length	1.8 m
Waveform *	Sine	Product colour *	Black
Input frequency *	60 Hz	LED indicators	✓
Output operation voltage (min)	115 V	Certification	UL1778, CSA, NOM, FCC
Output operation voltage (max)	120 V	Operational conditions	
Output voltage regulation	+/- 5%	Operating temperature (T-T)	0 - 40 °C
Automatic Voltage Regulation (AVR)	✓	Storage temperature (T-T)	-15 - 50 °C
Maximum current	15 A	Operating relative humidity (H-H)	0 - 95%
Surge energy rating	510 J	Technical details	
Number of input phases	1	Sustainability certificates	RoHS
Efficiency	97%	Weight & dimensions	
EMI/RFI noise filtering	✓	Width	133.4 mm
Surge protection	✓	Depth	190.5 mm
Surge protection features	Fax, Modem, Network, Telephone	Height	271.5 mm
Power protection features	Under voltage	Weight	6.76 kg
Audible alarm(s)	✓	Package width	195.6 mm
Country of origin	China	Package depth	353.1 mm
Ports & interfaces		Package height	355.1 mm
AC outlet types	NEMA 5-15R	Package weight	7.78 kg
Power plug	NEMA 5-15P	Logistics data	
AC outlets quantity	6 AC outlet(s)	Master (outer) case width	276.9 mm
USB 2.0 ports quantity	1	Master (outer) case length	403.9 mm
Modem (RJ-11) ports	1	Master (outer) case height	382 mm
Ethernet LAN (RJ-45) ports	1	Master (outer) case gross weight	15.4 kg
Battery		Products per master (outer) case	2 pc(s)
Typical backup time at full load	2.2 min		

Battery		Logistics data	
Typical backup time at half load	8.3 min	Master (outer) case GTIN (EAN/UPC) 10037332119947	
Battery recharge time	4.5 h	Other features	
Hot-swap battery	✓	Nominal input voltage	120 V
Cold start	✓	Non-operating relative humidity (non-condensing)	0 - 95%
		Weight (imperial)	7.89 kg (17.4 lbs)



0037332119940



037332119940

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 12-MAY-2024. Prints or copies of Information are only valid on the printed Publication date