



APC AP8862 power distribution unit (PDU) 36 AC outlet(s) Black

Brand : APC  
Product code: AP8862  
Product name : AP8862

Rack 2G, Metered, NEMA 5-20R x 36, NEMA L21-20P, 5760 VA

APC AP8862 power distribution unit (PDU) 36 AC outlet(s) Black:

APC Metered Rack Power Distribution Units (PDUs) provide active metering to enable energy optimization and circuit protection. User-defined alarm thresholds mitigate risk with real-time local and remote alerts to warn of potential circuit overloads. Metered Rack PDUs provide power utilization data to allow Data Center Managers to make informed decisions on load balancing and right sizing IT environments to lower total cost of ownership. Metered Rack PDUs include real power monitoring, a temperature/humidity sensor port, locking IEC receptacles, and ultra low profile circuit breakers. Users can access and configure Metered Rack PDUs through secure Web, SNMP, or Telnet Interfaces which are complimented by APC Centralized Management platforms using InfraStruxure Central, Operations, Capacity, and Energy Efficiency.



Design		Certificates	
PDU types *	Metered	Certification	cUL Listed, FCC Part 15 Class A, ICES-003, UL 60950-1, UL Listed
Mounting	Horizontal/Vertical	Operational conditions	
Product colour	Black		
Ports & interfaces		Operating temperature (T-T)	-5 - 45 °C
AC outlets quantity *	36 AC outlet(s)	Storage temperature (T-T)	-25 - 65 °C
Power plug	NEMA L21-20P	Operating relative humidity (H-H)	5 - 95%
AC outlet types *	NEMA 5-20R	Storage relative humidity (H-H)	5 - 95%
Features		Operating altitude	0 - 3000 m
LED indicators	✓	Non-operating altitude	0 - 15000 m
Cable length	1.83 m	Operating temperature (T-T)	23 - 113 °F
Power		Weight & dimensions	
Nominal input voltage *	208 V	Width	55 mm
AC input frequency	50 - 60 Hz	Depth	44 mm
Nominal output voltage	120 V	Height	1791 mm
Load capacity	5760 VA	Weight	6.04 kg
Maximum input current per phase	20 A	Packaging data	
Maximum total current draw per phase	16 A	Package weight	8.12 kg
Certificates		Package width	160 mm
Compliance certificates	RoHS	Package depth	108 mm
		Package height	2006 mm



0731304307488



731304307488

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 08-MAY-2025. Prints or copies of Information are only valid on the printed Publication date