



TP-Link Omada IES206G network switch Managed Gigabit Ethernet (10/100/1000) Black

Brand : TP-Link

Product family: Omada

Product code: IES206G

Product name : IES206G

- 6 × Gigabit Ports (4 × RJ45, 1 × Combo RJ45/SFP, 1 × SFP)
 - Professional Industrial-Grade Design: -40~75°C Operating Temperature, 6kV Lighting Protection, and 1+1 Redundant Power Input
 - Abundant Features: VLAN, QoS, and STP/RSTP
 - Centralized Cloud Management via the Web or Omada Appt
 - Durable IP40 Aluminum Casing and DIN-rail / Wall-mount Design
- IES206G - Omada 6-Port Gigabit Industrial Easy Managed Switch
TP-Link Omada IES206G. Switch type: Managed. Basic switching RJ-45 Ethernet ports type: Gigabit Ethernet (10/100/1000), Basic switching RJ-45 Ethernet ports quantity: 4. MAC address table: 8000 entries, Switching capacity: 12 Gbit/s. Networking standards: IEEE 802.1D, IEEE 802.1Q, IEEE 802.1p, IEEE 802.1w, IEEE 802.3ab, IEEE 802.3u, IEEE 802.3x. DC input voltage: 9 - 60 V. Wall mountable

Management features		Security	
Switch type *	Managed	IGMP snooping	✓
Quality of Service (QoS) support	✓	Multicast features	
Web-based management	✓	Multicast support	✓
Cloud-managed	✓	Design	
Ports & interfaces		Product colour	Black
Basic switching RJ-45 Ethernet ports quantity *	4	Wall mountable	✓
Basic switching RJ-45 Ethernet ports type *	Gigabit Ethernet (10/100/1000)	DIN rail mounting	✓
Combo SFP ports quantity	1	Performance	
SFP module slots quantity	1	Fanless	✓
Network		Power	
Networking standards *	IEEE 802.1D, IEEE 802.1Q, IEEE 802.1p, IEEE 802.1w, IEEE 802.3ab, IEEE 802.3u, IEEE 802.3x	Power source *	DC
10G support *	✗	Power supply included *	✓
Port mirroring	✓	Redundant power supply (RPS) support	✓
Flow control support	✓	DC input voltage	9 - 60 V
Link aggregation	✓	Power over Ethernet (PoE)	
Auto MDI/MDI-X	✓	Power over Ethernet (PoE) *	✗
Spanning tree protocol	✓	Operational conditions	
Auto-negotiation	✓	Operating temperature (T-T)	-40 - 75 °C
Data transmission		Storage temperature (T-T)	-40 - 85 °C
Switching capacity *	12 Gbit/s	Operating relative humidity (H-H)	5 - 95%
Forwarding rate	8.93 Mpps	Storage relative humidity (H-H)	5 - 95%
MAC address table *	8000 entries	Weight & dimensions	
Store-and-forward	✓	Width	129 mm
Jumbo frames support	✓	Depth	95 mm
Jumbo frames	15000	Height	45 mm
Security		Certificates	
DHCP features	DHCP client	Certification	FCC, CE, RoHS



1210002602075



0840460600934



840460600934

Catalog Object Cloud



Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.