



QNAP TVS-972XU NAS Rack (1U) Intel® Core™ i3 i3-8100 4 GB DDR4 0 TB Black

Brand : QNAP

Product code: TVS-972XU-I3-4G-US



Product name : TVS-972XU

Intel Core i3-8100 3.6 GHz, 4 GB DDR4, 4 GB Flash, 2 x 10GbE SFP+, 2 x USB 3.0, 2 x Type-C USB 3.1 Gen2, 2 x Type-A USB 3.1 Gen2, 1 x HDMI

QNAP TVS-972XU. Type: NAS. Chassis type: Rack (1U). Processor family: Intel® Core™ i3, Processor model: i3-8100, Processor frequency: 3.6 GHz. Internal memory: 4 GB, Internal memory type: DDR4. Total installed storage capacity: 0 TB



Storage		Design	
Supported storage drive interfaces	Serial ATA III	LED indicators	HDD, LAN, Status
Storage drive sizes supported	2.5,3.5"	Cable lock slot	✓
RAID support *	✓	Cable lock slot type	Kensington
Hot-swap drive bays	✓	Performance	
Storage drives installed *	✗	Type *	NAS
Total installed storage capacity *	0 TB	Backup function *	✓
Installed storage drive type *	✗	Noise level	44.1 dB
Supported storage drive types *	HDD & SSD	Reset button	✓
Processor		On/off switch	✓
Processor manufacturer *	Intel	Power	
Processor generation	8th gen Intel® Core™ i3	Power supply unit (PSU) capacity	250 W
Processor family *	Intel® Core™ i3	Number of power supply units	2
Processor model *	i3-8100	Power consumption (typical)	72.17 W
Processor frequency *	3.6 GHz	AC input voltage	100 - 240 V
Processor cores	4	Fan voltage	12 V
Processor threads	4	Weight & dimensions	
Processor cache	6 MB	Width *	482.6 mm
Bus type	DMI3	Depth *	484.1 mm
CPU configuration (max)	1	Height *	43.3 mm
ECC supported by processor	✗	Weight	7.48 kg
PCI Express configurations	1x16, 1x8+2x4, 2x8	Package weight	10.3 kg
PCI Express slots version	3.0	Processor special features	
Processor cache type	Smart Cache	Embedded options available	✓
Processor codename	Coffee Lake	Enhanced Intel SpeedStep Technology	✓
Processor lithography	14 nm	Execute Disable Bit	✓
Processor operating modes	64-bit	Idle States	✓
Processor package size	37.5 x 37.5 mm	Intel 64	✓
Processor socket	LGA 1151 (Socket H4)	Intel Clear Video Technology	✓
Scalability	1S	Intel Enhanced Halt State	✓
System bus rate	8 GT/s	Intel Identity Protection Technology version	1.00
Tjunction	100 °C	Intel Secure Key Technology version	1.00
Thermal Design Power (TDP)	65 W		
On-board graphics card model	Intel® UHD Graphics 630		
Maximum internal memory supported by processor	64 GB		

Processor		Processor special features	
Memory bandwidth supported by processor (max)	37.5 GB/s	Intel Stable Image Platform Program (SIPP)	✗
Conflict-Free processor	✓	Intel Stable Image Platform Program (SIPP) version	0.00
Memory		Intel Trusted Execution Technology	✗
Internal memory *	4 GB	Intel TSX-NI	✗
Internal memory type	DDR4	Intel TSX-NI version	0.00
Maximum RAM supported	64 GB	Intel Virtualization Technology (VT-x)	✓
Memory slots	4	Intel Virtualization Technology for Directed I/O (VT-d)	✓
Flash memory	4000 MB	Intel VT-x with Extended Page Tables (EPT)	✓
Network		Intel® AES New Instructions (Intel® AES-NI)	✓
Ethernet LAN *	✓	Intel® Clear Video HD Technology (Intel® CVT HD)	✓
Ethernet LAN data rates	10,100,1000 Mbit/s	Intel® Clear Video Technology for Mobile Internet Devices (Intel CVT for MID)	✓
Wi-Fi	✗	Intel® Hyper Threading Technology (Intel® HT Technology)	✗
Ports & interfaces		Intel® Identity Protection Technology (Intel® IPT)	✓
USB port *	✓	Intel® InTru™ 3D Technology	✓
USB 3.2 Gen 2 (3.1 Gen 2) Type-A ports quantity	2	Intel® OS Guard	✓
USB 3.2 Gen 2 (3.1 Gen 2) Type-C ports quantity	2	Intel® Quick Sync Video Technology	✓
Fiber ports quantity	2	Intel® Secure Key	✓
Fiber optic connector	SFP+	Intel® Turbo Boost Technology	✗
HDMI ports quantity	1	Maximum number of PCI Express lanes	16
HDMI version	2.0	Number of execution units	23
Ethernet LAN (RJ-45) ports *	2	Thermal Monitoring Technologies	✓
Graphics		Thermal solution specification	PCG 2015C
On-board graphics card base frequency	350 MHz	Memory channels supported by processor	Dual
On-board graphics card dynamic frequency (max)	1100 MHz	Memory types supported by processor	DDR4-SDRAM
On-board graphics card DirectX version	12.0	Operational conditions	
On-board graphics card OpenGL version	4.5	Operating temperature (T-T)	0 - 40 °C
On-board graphics card ID	0x3E91	Operating relative humidity (H-H)	5 - 95%
Maximum on-board graphics card memory	64 GB	Other features	
Number of displays supported (on-board graphics)	3	Processor ARK ID	126688
Design			
Chassis type *	Rack (1U)		
Cooling type *	Active		
Product colour	Black		
Number of fans	3 fan(s)		
Fan diameter	4 cm		

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 28-APR-2025. Prints or copies of Information are only valid on the printed Publication date