APC

APC SMT2200C uninterruptible power supply (UPS) Line-Interactive 2.2 kVA 1980 W 10 AC outlet(s)

Brand : APC

Product name : SMT2200C

Product code: SMT2200C

2.2 kVA, 1.98 kW, 75-154V, 50/60Hz. 530J, 196x544x432mm, 50.9kg, Black
APC SMT2200C. UPS topology: Line-Interactive, Output power capacity: 2.2 kVA, Output power: 1980 W. AC outlet types: NEMA 5–15R, NEMA 5–20R, Power plug: NEMA 5-20P, AC outlets quantity: 10 AC outlet(s). Battery technology: Sealed Lead Acid (VRLA), Battery life (max): 5 year(s), Battery recharge time: 3 h. Form factor: Tower, Product colour: Black, Cable length: 1.83 m. Certification: CSA, FCC, UL

Features

UPS topology *	Line-Interactive
Output power capacity *	2.2 kVA
Output power *	1980 W
Waveform *	Sine
Input operation voltage (min) *	75 V
Input operation voltage (max) *	154 V
Input frequency *	50/60 Hz
Output operation voltage (min)	110 V
Output operation voltage (max)	127 V
Output frequency	50/60 Hz
Automatic Voltage Regulation (AVR)	✔
Surge energy rating	530 J
Emergency Power Off (EPO)	✔
Output voltage Total Harmonic Distortion (THD)	5%
Noise level	45 dB
Surge protection	✘
Audible alarm(s)	✔
Web-based management	✔
Audible alarm modes	Alarm when on battery, Low battery alarm, Overload alarm
Auto-restart	✔
Temperature voltage compensation	✔

Ports & interfaces

AC outlet types	NEMA 5–15R, NEMA 5–20R
Power plug	NEMA 5-20P
AC outlets quantity	10 AC outlet(s)
USB port	✔
USB 2.0 ports quantity	1
Serial interface	✔
Serial interface type	RS-232
Ethernet LAN (RJ-45) ports	1
SmartSlot	✔

Battery

Battery technology	Sealed Lead Acid (VRLA)
Number of batteries supported	1
Battery life (max)	5 year(s)
Battery recharge time	3 h
Hot-swap battery	✔
Automatic battery test	✔

Design

Form factor *	Tower
Cable length	1.83 m
Product colour *	Black
Display type	LCD
LED indicators	✔

Operational conditions

Operating temperature (T-T)	0 - 40 °C
Storage temperature (T-T)	-15 - 45 °C
Operating relative humidity (H-H)	0 - 95%
Storage relative humidity (H-H)	0 - 95%
Operating altitude	0 - 3000 m
Non-operating altitude	0 - 15000 m

Certificates

Certification	CSA, FCC, UL

Sustainability

Sustainability certificates	ENERGY STAR

Weight & dimensions

Width	196 mm
Depth	544 mm
Height	432 mm
Weight	50.9 kg

Packaging data

Package width	381 mm
Package depth	762 mm
Package height	559 mm
Package weight	60.9 kg

Logistics data

Products per pallet	9 pc(s)

0731304331049

731304331049

Catalog Object Cloud