



## APC SMT3000C uninterruptible power supply (UPS) Line-Interactive 2.88 kVA 2700 W 10 AC outlet(s)

Brand : APC

Product code: SMT3000C

Product name : SMT3000C

2.7 kW, 2.88 kVA, 75-154V, 50/60Hz, 530J, 196x544x432mm, 52.73kg, Black

APC SMT3000C. UPS topology: Line-Interactive, Output power capacity: 2.88 kVA, Output power: 2700 W. AC outlet types: NEMA 5-15R, NEMA 5-20R, Power plug: NEMA L5-30P, AC outlets quantity: 10 AC outlet(s). Battery technology: Sealed Lead Acid (VRLA), Battery life (max): 5 year(s), Battery recharge time: 3 h. Form factor: Tower, Product colour: Black, Cable length: 1.83 m. Compliance certificates: RoHS, Certification: CSA, FCC, UL, REACH, PEP, EOL



| Features                                       |  | Design                            |                               |
|--|--|-----------------------------------|-------------------------------|
| UPS topology *                                 | Line-Interactive                         | Form factor *                     | Tower                         |
| Output power capacity *                        | 2.88 kVA                                 | Cable length                      | 1.83 m                        |
| Output power *                                 | 2700 W                                   | Product colour *                  | Black                         |
| Waveform *                                     | Sine                                     | Display type                      | LCD                           |
| Input operation voltage (min) *                | 75 V                                     | Operational conditions            |                               |
| Input operation voltage (max) *                | 154 V                                    | Operating temperature (T-T)       | 0 - 40 °C                     |
| Input frequency *                              | 50/60 Hz                                 | Storage temperature (T-T)         | -15 - 45 °C                   |
| Output operation voltage (max)                 | 120 V                                    | Operating relative humidity (H-H) | 0 - 95%                       |
| Output frequency                               | 50/60 Hz                                 | Storage relative humidity (H-H)   | 0 - 95%                       |
| Surge energy rating                            | 530 J                                    | Operating altitude                | 0 - 3000 m                    |
| Emergency Power Off (EPO)                      | ✓  | Non-operating altitude            | 0 - 15000 m                   |
| Output voltage Total Harmonic Distortion (THD) | 5%                                       | Certificates                      |                               |
| Noise level                                    | 45 dB                                    | Compliance certificates           | RoHS                          |
| Audible alarm(s)                               | ✓  | Certification                     | CSA, FCC, UL, REACH, PEP, EOL |
| Audible alarm modes                            | Alarm when on battery, Low battery alarm | Packaging content                 |                               |
| Ports & interfaces                             |  | Cables included                   | RS-232, USB cable             |
| AC outlet types                                | NEMA 5-15R, NEMA 5-20R                   | Sustainability                    |                               |
| Power plug                                     | NEMA L5-30P                              | Sustainability certificates       | ENERGY STAR                   |
| AC outlets quantity                            | 10 AC outlet(s)                          | Weight & dimensions               |                               |
| USB port                                       | ✓  | Width                             | 196 mm                        |
| USB 2.0 ports quantity                         | 1  | Depth                             | 544 mm                        |
| SmartSlot                                      | ✓  | Height                            | 432 mm                        |
| Battery  |  | Weight                            | 52.7 kg                       |
| Battery technology                             | Sealed Lead Acid (VRLA)                  | Packaging data                    |                               |
| Number of batteries supported                  | 1  | Resource CD                       | ✓                             |
| Battery life (max)                             | 5 year(s)                                | Software CD                       | ✓                             |
| Battery recharge time                          | 3 h                                      | Package width                     | 381 mm                        |
| Replacement battery cartridge                  | RBC55                                    | Package depth                     | 762 mm                        |
|  |  | Package height                    | 559 mm                        |
|  |  | Package weight                    | 60.9 kg                       |
|  |  | Logistics data                    |                               |
|  |  | Products per pallet               | 9 pc(s)                       |



0731304331063



731304331063

### Catalog Object Cloud



Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.