



APC SMT3000C uninterruptible power supply (UPS) Line-Interactive 2.88 kVA 2700 W 10 AC outlet(s)

Brand : APC

Product code: SMT3000C

Product name : SMT3000C

2.7 kW, 2.88 kVA, 75-154V, 50/60Hz, 530J, 196x544x432mm, 52.73kg, Black
APC SMT3000C. UPS topology: Line-Interactive, Output power capacity: 2.88 kVA, Output power: 2700 W. AC outlet types: NEMA 5-15R, NEMA 5-20R, Power plug: NEMA L5-30P, AC outlets quantity: 10 AC outlet(s). Battery technology: Sealed Lead Acid (VRLA), Battery life (max): 5 year(s), Battery recharge time: 3 h. Form factor: Tower, Product colour: Black, Cable length: 1.83 m. Width: 196 mm, Depth: 544 mm, Height: 432 mm



Features		Battery	
UPS topology *	Line-Interactive	Replacement battery cartridge	RBC55
Output power capacity *	2.88 kVA	Design	
Output power *	2700 W	Form factor *	Tower
Waveform *	Sine	Cable length	1.83 m
Input operation voltage (min) *	75 V	Product colour *	Black
Input operation voltage (max) *	154 V	Display type	LCD
Input frequency *	50/60 Hz	Certification	CSA, FCC, UL, REACH, PEP, EOL
Output operation voltage (max)	120 V	Operational conditions	
Output frequency	50/60 Hz	Operating temperature (T-T)	0 - 40 °C
Surge energy rating	530 J	Storage temperature (T-T)	-15 - 45 °C
Emergency Power Off (EPO)	✓	Operating relative humidity (H-H)	0 - 95%
Output voltage Total Harmonic Distortion (THD)	5%	Storage relative humidity (H-H)	0 - 95%
Noise level	45 dB	Operating altitude	0 - 3000 m
Audible alarm(s)	✓	Non-operating altitude	0 - 15000 m
Audible alarm modes	Alarm when on battery, Low battery alarm	Technical details	
Ports & interfaces		Sustainability certificates	RoHS, ENERGY STAR
AC outlet types	NEMA 5-15R, NEMA 5-20R	Weight & dimensions	
Power plug	NEMA L5-30P	Width	196 mm
AC outlets quantity	10 AC outlet(s)	Depth	544 mm
USB port	✓	Height	432 mm
USB 2.0 ports quantity	1	Weight	52.7 kg
SmartSlot	✓	Package width	381 mm
Battery		Package depth	762 mm
Battery technology	Sealed Lead Acid (VRLA)	Package height	559 mm
Number of batteries supported	1	Package weight	60.9 kg
Battery life (max)	5 year(s)	Packaging data	
Battery recharge time	3 h	Cables included	RS-232, USB cable
		Resource CD	✓
		Software CD	✓
Logistics data			
		Products per pallet	9 pc(s)



0731304331063



731304331063

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 23-APR-2024. Prints or copies of Information are only valid on the printed Publication date