APC

APC SMT3000RM2UC uninterruptible power supply (UPS) Line-Interactive 2.88 kVA 2700 W 8 AC outlet(s)

Brand : APC

Product code: SMT3000RM2UC

Product name : SMT3000RM2UC

2.88kVA, 2.7kW, 75-154V, 50/60Hz, 459J, 480x683x86mm, 44.28kg, Black
APC SMT3000RM2UC. UPS topology: Line-Interactive, Output power capacity: 2.88 kVA, Output power: 2700 W. AC outlet types: NEMA 5-15R, NEMA 5–20R, Power plug: NEMA L5-30P, AC outlets quantity: 8 AC outlet(s). Battery technology: Sealed Lead Acid (VRLA), Battery life (max): 5 year(s), Battery recharge time: 3 h. Form factor: Rackmount, Product colour: Black, Rack capacity: 2U. Certification: FCC, CSA, UL

Features

UPS topology *	Line-Interactive
Output power capacity *	2.88 kVA
Output power *	2700 W
Waveform *	Sine
Input operation voltage (min) *	75 V
Input operation voltage (max) *	154 V
Input frequency *	50/60 Hz
Output operation voltage (min)	110 V
Output operation voltage (max)	127 V
Output frequency	50/60 Hz
Automatic Voltage Regulation (AVR)	✔
Surge energy rating	459 J
Output voltage Total Harmonic Distortion (THD)	5%
Noise level	55 dB
Surge protection	✔
Audible alarm(s)	✔
Web-based management	✔
Auto-restart	✔
Temperature voltage compensation	✔

Ports & interfaces

AC outlet types	NEMA 5-15R, NEMA 5–20R
Power plug	NEMA L5-30P
AC outlets quantity	8 AC outlet(s)
USB port	✔
USB 2.0 ports quantity	1
SmartSlot	✔

Battery

Battery technology	Sealed Lead Acid (VRLA)
Number of batteries supported	1
Battery life (max)	5 year(s)
Battery recharge time	3 h
Hot-swap battery	✔

Battery

Automatic battery test	✔

Design

Form factor *	Rackmount
Rack capacity	2U
Cable length	2.44 m
Product colour *	Black
Display type	LCD
LED indicators	Status

Operational conditions

Operating temperature (T-T)	0 - 40 °C
Storage temperature (T-T)	-15 - 45 °C
Operating relative humidity (H-H)	0 - 95%
Storage relative humidity (H-H)	0 - 95%
Operating altitude	0 - 3000 m
Non-operating altitude	0 - 15000 m

Certificates

Certification	FCC, CSA, UL

Packaging content

Cables included	RS-232, USB cable
Quick installation guide	✔

Sustainability

Sustainability certificates	ENERGY STAR

Weight & dimensions

Width	480 mm
Depth	683 mm
Height	86 mm
Weight	44.3 kg

Packaging data

Screws included	✔
Resource CD	✔
Software CD	✔
Package width	600 mm
Package depth	980 mm
Package height	254 mm
Package weight	51.7 kg

Logistics data

Products per pallet	8 pc(s)

Logistics data

Harmonized System (HS) code	85078000

0731304331070

731304331070

Catalog Object Cloud