

TP-Link INSIGHT S345 Bullet IP security camera Outdoor 2688 x 1520 pixels Wall

Brand: TP-Link Product code: INSIGHT S345(2.8MM)

Product name: INSIGHT S345

- 4MP Super-High Definition and 24h Full-Color
- People & Vehicle Analytics§
- Human & Vehicle Classification
- Smart Detection
- Smart Video Enhancement Technology
- Active Defense and Two-Way Audio
- IP67 Waterproof
- H.265+ Compression Technology

VIGI 4MP Outdoor Full-Color Bullet Network Camera, 1/2.7", 1/3 to 1/10000 s, F1.6, 2688 x 1520, CBR, VBR, BLC/3D DNR/HLC/SmartIR, 120 dB, 12V DC \pm 5%, Max. 9.7 W, 5.5 mm Coaxial Power Plug, PoE: 802.3af/at, class 0, Max. 10.7 W, IP67, 184 x 74 x 74 mm, 0.525 kg, White

TP-Link INSIGHT S345. Type: IP security camera, Placement supported: Outdoor, Connectivity technology: Wired. Mounting type: Wall, Product colour: White, Form factor: Bullet. Lens viewing angle, horizontal: 100°, Lens viewing angle, vertical: 54°, Lens viewing angle, diagonal: 118°. Sensor type: CMOS, Optical sensor size: 25.4 / 2.7 mm (1 / 2.7"). Detect distance: 64 m, Observe distance: 27 m, Recognize distance: 13 m





Performance		Audio	
Type * Placement supported * Connectivity technology * Maximum operating distance Wide Dynamic Range (WDR) Day/night mode	IP security camera Outdoor Wired 64 m	Audio output channels Audio formats supported Sample rate Built-in microphone Number of microphones Bit rate range	1.0 channels G.711 A-law 8 kHz 1 0 - 64 Kbit/s
Infrared (IR) cut-off filter	✓	Network	
Remote viewing Dynamic range	✓ 120 dB	Ethernet LAN * Networking standards	✓ IEEE 802.3af, IEEE 802.3at
Design Form factor * Mounting type *	Bullet Wall	Supported network protocols	TCP/IP, UDP, ICMP, HTTP, HTTPS, DHCP, DNS, RTSP, NTP, UPnP UDP, SSL/TLS, FTP/SFTP, RTP, IPv4, IPv6, ARP
Product colour *	White	Wi-Fi *	×
Housing material	Metal	Bluetooth *	×
Protection features	Waterproof	Live view	✓
International Protection (IP) code Weatherproof	IP67 ✓	Storage	
Camera		Compatible memory cards Maximum memory card size	MicroSD (TransFlash) 512 GB
Minimum illumination	0 lx	Ports & interfaces	
Lens viewing angle, horizontal Lens viewing angle, vertical	100° 54°	Ethernet LAN (RJ-45) ports	1
Lens viewing angle, diagonal	118°	DC-in jack	✓
Tilt angle range	0 - 90°	Security	
Camera shutter speed	1/3 to 1/10000	Built-in siren	✓
Image sensor		Password protection	✓
Optical sensor size	25.4 / 2.7 mm (1 / 2.7")	Video motion detection	✓
Progressive scan	✓	IP address filtering	✓
Sensor type *	CMOS	HTTPS encryption	✓
Lens system		Alert notification type	Push notification
Detect distance	64 m	Motion sensor	✓
Observe distance Recognize distance	27 m 13 m	Mirror	✓

Lens system		Security	
Maximum aperture number	1.6	Human and vehicle targets	✓
Identify distance	6 m	classification	
Fixed focal length	2.8 mm	Digest authentication	✓
Night vision		Management features	
Night vision *	✓	Web-based management	✓
LED type	IR/White	Web browser	✓
Video		Cloud-managed *	✓
Maximum resolution *	2688 x 1520 pixels	Reset button	✓
Total megapixels *	4 MP	Power	
Video compression formats	H.264, H.264+, H.265, H.265+	Power source type *	DC, PoE
Supported graphics resolutions	1280 x 720 (HD 720), 1920 x 1080 (HD 1080), 2048 x 1280, 2304 x 1296, 2560 x 1440, 2688 x 1520 ✓ Brightness, Contrast, Mirror, Saturation, Sharpness	Power consumption (Power over Ethernet (PoE))	10.7 W
Video recording		DC output voltage	12
•		Operational conditions	
Image quality adjustment		Operating temperature (T-T)	-30 - 60 °C
Bit rate control	Constant Bit Rate (CBR)/Variable Bit Rate (VBR)	Storage temperature (T-T)	-40 - 60 °C
	Main Stream: 256 Kbps to 6 Mbps,	Operating relative humidity (H-H)	0 - 95%
Bit rate	Sub-Stream: 64 Kbps to 512 Kbps	Storage relative humidity (H-H)	0 - 95%
Back Light Compensation (BLC)	✓	Weight & dimensions	
Highlight Compensation (HLC)	✓	Width	74 mm
Digital Wide Dynamic Range	1	Height	74 mm
(DWDR)	•	Length	184 mm
Audio		Weight	525 g
Built-in speaker(s)	✓	Packaging content	
Audio system	2-way	Number of cameras *	1
Audio input channels	1.0 channels	Mounting kit	✓
		Screws included	✓
		Drilling template included	✓
		Manual	✓





810142823906

0810142823906





1210002606394

8885020628043

Catalog Object Cloud



Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.