

j5create JVCU100 USB™ HD Webcam with 360° Rotation, 1080p Video Capture Resolution, Black

Brand : j5create

Product code: JVCU100-N

Product name : JVCU100 USB™ HD Webcam with 360° Rotation, 1080p Video Capture Resolution, Black



JVCU100 USB HD Webcam with 360° Rotation, 1080p Video Capture Resolution, Black

[j5create JVCU100 USB™ HD Webcam with 360° Rotation, 1080p Video Capture Resolution, Black:](#)

The USB™ HD Webcam with 360° Rotation delivers Full HD 1080p resolution for clear and detailed images. It's perfect for everyday use, featuring a high-fidelity microphone to reduce external noise, and enhanced light sensitivity that adjusts automatically to suit different lighting conditions. In addition, it has an 80° field of view and can be swiveled a full 360° for maximum flexibility.

This USB™ HD Webcam is plug-and-play, and works with popular applications like Zoom®, Skype®, Microsoft Teams™ and Google Meet™. The webcam is compatible with Windows®, MacOS®, ChromeOS™, making it the perfect camera for at home or in the office.



| Performance | | Weight & dimensions | |
|-----------------------------|---|------------------------------------|--|
| Megapixel (approx.) * | 2.07 MP | Height | 53 mm |
| Maximum video resolution * | 1920 x 1080 pixels | Weight | 120 g |
| Maximum frame rate | 30 fps | Packaging data | |
| Camera HD type * | Full HD | Quantity | 1 |
| Resolution at capture speed | 640x480@30fps, 1280x720@30fps, 1920x1080@30fps | Package type | Box |
| Supported video modes | 720p, 1080p | Package width | 155 mm |
| Video formats supported | H.264, M-JPEG, YUV | Package depth | 95 mm |
| Maximum image resolution | 1920 x 1080 pixels | Package height | 60 mm |
| Auto focus | ✓ | Package weight | 210 g |
| Face tracking * | ✗ | Packaging content | |
| Signal-to-Noise Ratio (SNR) | 50 dB | Quick installation guide | ✓ |
| Power consumption (typical) | 5 W | Box contents | 1 x USB™ HD Webcam with 360° rotation (Model: JVCU100), 1 x Quick Installation Guide |
| Operating voltage | 5 V | System requirements | |
| Operating current | 0.5 A | Minimum system requirements | Available USB™ Type-A port, Windows® 10, macOS® with UVC support, Chrome OS™ with UVC support, Operating systems compliant with standard UVC 1.0/1.1 & UAC support |
| Plug and Play | ✓ | Microphone | |
| Design | | Built-in microphone * | ✓ |
| Interface * | USB | Logistics data | |
| Product colour * | Black | Quantity per box | 1 pc(s) |
| Housing material | Acrylonitrile butadiene styrene (ABS), Polycarbonate (PC) | Products per shipping (inner) case | 3 pc(s) |
| Mounting type * | Clip/Stand | Shipping (inner) case length | 20.7 cm |
| Sensor type | CMOS | Shipping (inner) case width | 10.3 cm |
| Optical sensor size | 25.4 / 2.9 mm (1 / 2.9") | | |
| Built-in flash * | ✗ | | |
| Image stabilizer | ✗ | | |
| Cable length | 1.5 m | | |

| Software | | Logistics data | |
|-------------------------------------|---|--|----------------|
| Windows operating systems supported | Windows 10, Windows 8.1, Yes | Shipping (inner) case height | 16.5 cm |
| | Mac OS X 10.10 Yosemite, Mac OS X 10.11 El Capitan, Mac OS X 10.12 Sierra, Mac OS X 10.13 High Sierra, Mac OS X 10.14 Mojave, Mac OS X 10.15 Catalina, Mac OS X 10.15.3 Catalina, Mac OS X 10.5 Leopard, Mac OS X 10.6 Snow Leopard, Mac OS X 10.7 Lion, Mac OS X 10.8 Mountain Lion, Mac OS X 10.9 Mavericks, Mac OS X 11.0 Big Sur, Mac OS X 12.0 Monterey, Yes | Export Control Classification Number (ECCN) | EAR99 |
| Mac operating systems supported | | Shipping (inner) case gross weight | 740 g |
| | | Commodity Classification Automated Tracking System (CCATS) | 8525.50.0000 |
| Linux operating systems supported | ✓ | Master (outer) case width | 230 mm |
| Other operating systems supported | ChromeOS | Master (outer) case length | 435 mm |
| | | Master (outer) case height | 190 mm |
| | | Master (outer) case gross weight | 3.04 kg |
| | | Master (outer) case GTIN (EAN/UPC) | 24712795085574 |
| | | Products per master (outer) case | 12 pc(s) |
| | | Country of origin | Taiwan |
| Operational conditions | | Technical details | |
| Storage relative humidity (H-H) | 0 - 90% | Warranty period | 2 year(s) |
| Operating relative humidity (H-H) | 0 - 90% | | |
| Storage temperature (T-T) | -20 - 60 °C | | |
| Operating temperature (T-T) | 0 - 40 °C | | |
| Weight & dimensions | | | |
| Width | 102 mm | | |
| Depth | 53.5 mm | | |



4712795085570



(01)24712795085574

Catalog Object Cloud



Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.