

Viewsonic 65" 4K OS-Free Commercial Display

Brand : Viewsonic

Product code: CDE65G3-1C

Product name : 65" 4K OS-Free Commercial Display



- OS-Free Architecture minimizes vulnerabilities in secure and sensitive environments
 - USB-C and HDMI 2.1 connectivity supports easy BYOD use without additional adapters
 - Fast cold boot and 24/7 operation ensures instant power-on and nonstop performance
 - Built-in USB media playback supports offline content delivery and digital signage
 - ProAV system integration enables centralized control
 - EPEAT® Gold certification supports sustainable, large-scale commercial deployments
 - 500-nit brightness and 4K UHD resolution deliver vivid visuals in any orientation
- 65", 4K UHD (3840 x 2160), TFT LCD, DLED, 500 nits, 5000:1, 6.5 ms, 2x 10 W, HDMI 2.1, RS-232, VGA, SPDIF, RJ45, USB-A, USB-C, 3.5 mm, OS-Free
- Viewsonic 65" 4K OS-Free Commercial Display. Product design: Digital signage flat panel. Display diagonal: 165.1 cm (65"), Display technology: LCD, Display resolution: 3840 x 2160 pixels, Display brightness: 500 cd/m², HD type: 4K Ultra HD. Operating hours (hours/days): 24/7. Product colour: Black

Display		Design	
Panel type	TFT	Screen shape	Flat
LED backlight	✓	VESA mounting *	✓
LED backlighting type	Direct-LED	Panel mounting interface	200 x 200 mm
Display diagonal *	165.1 cm (65")	Bezel width (bottom)	1.59 cm
Display technology *	LCD	Bezel width (side)	1.59 cm
Display resolution *	3840 x 2160 pixels	Bezel width (top)	1.59 cm
Display brightness *	500 cd/m ²	Anti-glare screen	✓
HD type *	4K Ultra HD	Performance	
Touchscreen *	✗	Purpose *	Commercial
Native aspect ratio	16:9	Operating hours (hours/days)	24/7
Response time	6.5 ms	HDCP	✓
Contrast ratio (typical)	5000:1	HDCP version	1.4/2.2
Viewing angle, horizontal	178°	Power	
Viewing angle, vertical	178°	Power consumption (typical) *	101.7 W
Active display area (W x H)	1428.48 x 803.52 mm	AC input voltage	100 - 240 V
Panel life	50000 h	Weight & dimensions	
Native refresh rate	60 Hz	Display width	1466.7 mm
Haze rate	25%	Display depth	79.7 mm
Surface hardness	3H	Display height	841 mm
Ports & interfaces		Display weight	22.8 kg
HDMI ports quantity *	3	Weight	25.1 kg
HDMI version	2.1	Packaging data	
HDMI input ports quantity	3	Package width	1640 mm
DVI port *	✗	Package depth	185 mm
VGA (D-Sub) input ports	1	Package height	960 mm
DisplayPort version	1.2	Package weight	34 kg
USB port *	✓	Packaging content	
USB ports quantity	3	Remote control included	✓
USB version	2.0	Batteries included	✓
USB connector type	USB Type-A, USB Type-C	Cables included	AC, HDMI, RS-232
USB Type-C DisplayPort Alternate Mode	✓		
Ethernet LAN (RJ-45) ports	1		

Ports & interfaces		Packaging content	
PC Audio in	✓	Mounting kit	✓
RS-232 interface	✓	Operational conditions	
Digital audio optical out	1	Operating temperature (T-T)	0 - 40 °C
PC Audio out	✓	Operating relative humidity (H-H)	20 - 80%
Audio		Logistics data	
Built-in speaker(s) *	✓	Products per master (outer) case	1 pc(s)
Number of built-in speakers	2	Pallet gross length	114 cm
RMS rated power	20 W	Pallet gross width	168.5 cm
Design		Pallet gross height	2.04 m
Product design *	Digital signage flat panel	Harmonized System (HS) code	8528521000
Placement supported *	Indoor	Network	
Orientation	Horizontal/Vertical	Ethernet LAN *	✓
Product colour *	Black	Technical details	
		Sustainability certificates	ENERGY STAR, EPEAT Gold, ErP CB, CE, EAC, Federal Communications Commission (FCC), RCM, REACH, RoHS, WEEE, cTUVus
		Compliance certificates	



0766907035704



766907035704

Catalog Object Cloud



Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.