


Viewsonic 65" 4K OS-Free Commercial Display

Brand : Viewsonic

Product code: CDE65G3-1C

Product name : 65" 4K OS-Free Commercial Display



- OS-Free Architecture minimizes vulnerabilities in secure and sensitive environments
 - USB-C and HDMI 2.1 connectivity supports easy BYOD use without additional adapters
 - Fast cold boot and 24/7 operation ensures instant power-on and nonstop performance
 - Built-in USB media playback supports offline content delivery and digital signage
 - ProAV system integration enables centralized control
 - EPEAT® Gold certification supports sustainable, large-scale commercial deployments
 - 500-nit brightness and 4K UHD resolution deliver vivid visuals in any orientation
- 65", 4K UHD (3840 x 2160), TFT LCD, DLED, 500 nits, 5000:1, 6.5 ms, 2x 10 W, HDMI 2.1, RS-232, VGA, SPDIF, RJ45, USB-A, USB-C, 3.5 mm, OS-Free
- Viewsonic 65" 4K OS-Free Commercial Display. Product design: Digital signage flat panel. Display diagonal: 165.1 cm (65"), Display technology: LCD, Display resolution: 3840 x 2160 pixels, Display brightness: 500 cd/m², HD type: 4K Ultra HD. Operating hours (hours/days): 24/7. Product colour: Black

| Display | | Design | |
|---------------------------------------|------------------------|--------------------------------|------------------|
| Panel type | TFT | Screen shape | Flat |
| LED backlight | ✓ | VESA mounting * | ✓ |
| LED backlighting type | Direct-LED | Panel mounting interface | 200 x 200 mm |
| Display diagonal * | 165.1 cm (65") | Bezel width (bottom) | 1.59 cm |
| Display technology * | LCD | Bezel width (side) | 1.59 cm |
| Display resolution * | 3840 x 2160 pixels | Bezel width (top) | 1.59 cm |
| Display brightness * | 500 cd/m ² | Anti-glare screen | ✓ |
| HD type * | 4K Ultra HD | Performance | |
| Touchscreen * | ✗ | Purpose * | Commercial |
| Native aspect ratio | 16:9 | Operating hours (hours/days) | 24/7 |
| Response time | 6.5 ms | HDCP | ✓ |
| Contrast ratio (typical) | 5000:1 | HDCP version | 1.4/2.2 |
| Viewing angle, horizontal | 178° | Power | |
| Viewing angle, vertical | 178° | Power consumption (typical) * | 101.7 W |
| Active display area (W x H) | 1428.48 x 803.52 mm | AC input voltage | 100 - 240 V |
| Panel life | 50000 h | Weight & dimensions | |
| Native refresh rate | 60 Hz | Display width | 1466.7 mm |
| Haze rate | 25% | Display depth | 79.7 mm |
| Surface hardness | 3H | Display height | 841 mm |
| Ports & interfaces | | Display weight | 22.8 kg |
| HDMI ports quantity * | 3 | Weight | 25.1 kg |
| HDMI version | 2.1 | Packaging data | |
| HDMI input ports quantity | 3 | Package width | 1640 mm |
| DVI port * | ✗ | Package depth | 185 mm |
| VGA (D-Sub) input ports | 1 | Package height | 960 mm |
| DisplayPort version | 1.2 | Package weight | 34 kg |
| USB port * | ✓ | Packaging content | |
| USB ports quantity | 3 | Remote control included | ✓ |
| USB version | 2.0 | Batteries included | ✓ |
| USB connector type | USB Type-A, USB Type-C | Cables included | AC, HDMI, RS-232 |
| USB Type-C DisplayPort Alternate Mode | ✓ | | |
| Ethernet LAN (RJ-45) ports | 1 | | |

| Ports & interfaces | | Packaging content | |
|-----------------------------|----------------------------|-----------------------------------|--|
| PC Audio in | ✓ | Mounting kit | ✓ |
| RS-232 interface | ✓ | Operational conditions | |
| Digital audio optical out | 1 | Operating temperature (T-T) | 0 - 40 °C |
| PC Audio out | ✓ | Operating relative humidity (H-H) | 20 - 80% |
| Audio | | Logistics data | |
| Built-in speaker(s) * | ✓ | Products per master (outer) case | 1 pc(s) |
| Number of built-in speakers | 2 | Pallet gross length | 114 cm |
| RMS rated power | 20 W | Pallet gross width | 168.5 cm |
| Design | | Pallet gross height | 2.04 m |
| Product design * | Digital signage flat panel | Harmonized System (HS) code | 8528521000 |
| Placement supported * | Indoor | Network | |
| Orientation | Horizontal/Vertical | Ethernet LAN * | ✓ |
| Product colour * | Black | Technical details | |
| | | Sustainability certificates | ENERGY STAR, EPEAT Gold, ErP CB, CE, EAC, Federal Communications Commission (FCC), RCM, REACH, RoHS, WEEE, cTUVus |
| | | Compliance certificates | |



0766907035704



766907035704

Catalog Object Cloud



Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity. Automated scraping, data mining, or harvesting for the purpose of training machine learning models, neural networks, or artificial intelligence systems is strictly prohibited without a commercial license.