

Brother ADS-4300N scanner ADF scanner 600 x 600 DPI A4 Black, White

Brand: Brother Product code: ADS-4300N

Product name: ADS-4300N

- 3 configurable hot keys
- Advanced image processing and batch scanning
- Features Ultrasonic Multifeed Sensor, Separation Switch
- Brother Mobile Connect app
- Supports AirPrint Scan
- Includes Brother ScanEssentials software
- Driver compatibility with TWAIN (Win and macOS), WIA, Linux SANE ADF, 40 ppm, 600 x 600/1200 x 1200 dpi, LAN, 59dB, USB 3.0

Brother ADS-4300N scanner ADF scanner 600 x 600 DPI A4 Black, White:

With high-speed wired connectivity. Great choice for scanning documents to the network and collaborating with colleagues. Ideal for shared use in the office.





Scanning		Power	
Optical scanning resolution * Enhanced scan resolution Colour scanning Duplex scanning * Input colour depth Output colour depth Output greyscale depth Greyscale levels ADF scan speed (b/w, A4) ADF scan speed (colour, A4) Duplex ADF scan speed (colour, A4) Duplex ADF scan speed (colour, A4)	600 x 600 DPI 1200 x 1200 DPI 4 48 bit 24 bit 8 bit 256 40 ppm 40 ppm 80 ipm 80 ipm	Power consumption (typical) Power consumption (standby) Power consumption (off) AC input frequency Power consumption (sleep) Output voltage Output current Weight & dimensions Width Depth	24 W 6.8 W 0.1 W 50 - 60 Hz 1.7 W 24 V 1.9 A
		Height Weight	391 mm 3.09 kg
Design		Packaging data	
Scanner type * Product colour * Control type Built-in display *	ADF scanner Black, White Buttons	Quantity per pack Package width Package depth Package height	1 pc(s) 391 mm 320 mm 243 mm
Performance		Package weight	3.74 kg
Sensor type * Light source Scan file formats	le (max) * 6000 pages y cycle 120000 pages per month FTP, Image, PC, SMB, USB ICA, SANE, TWAIN, WIA	Packaging content Cables included Sustainability	AC, USB
Daily duty cycle (max) * Maximum duty cycle Scan to		Sustainability compliance System requirements	/
Scan drivers Scanning noise level		Windows operating systems supported Mac operating systems supported	*

Input capacity		System requirements	
Auto document feeder (ADF) input capacity	80 sheets	Linux operating systems supported	✓ Windows Server 2012, Windows
Paper handling	Business Card, Plain paper, Plastic	Server operating systems supported	Server 2012 R2, Windows Server 2016, Windows Server 2019
Scanning media types supported	Card, Recycled paper, Thick paper,	Operational conditions	
Maximum ISO A-series paper size * Card thickness (max) Paper tray media weight Auto Document Feeder (ADF) media	Thin paper A4 1.1 mm 40 - 200 g/m ²	Operating temperature (T-T) Storage temperature (T-T) Operating relative humidity (H-H) Storage relative humidity (H-H)	5 - 35 °C -20 - 60 °C 20 - 80% 10 - 90%
weight	40 - 200 g/m²	Other features	
Maximum scan width Maximum scan length	21.6 cm 5 m	Compliance certificates Spare part retention	RoHS 5 year(s) GS Mark ISIS WHOL KofaxTM 5,10
Ports & interfaces	,	Certification	VRS Elite 5.2.0 Kofax Express 3.3.0
USB port * USB version	✓ 2.0/3.2 Gen 1 (3.1 Gen 1)	Technical details	
Network	2.0/3.2 GCH 1 (3.1 GCH 1)	Pallet type	800 x 1200 mm
Ethernet LAN	✓	Logistics data	
Security algorithms Supported network protocols (IPv6)	EAP-FAST, EAP-MD5, EAP-TLS, EAP- TTLS, HTTPS, PEAP, SMTP-AUTH, SNMPv3, SSL/TLS RA, DNS Resolver, mDNS, LLMNR responder, Web Services(Scan),	Products per pallet Country of origin Master (outer) cases per pallet Layers per pallet Pallet gross weight	40 pc(s) China 40 pc(s) 5 pc(s) 166.4 kg
Supported network protocols (IPv4)	SNTP Client, HTTP/HTTPS server, ICMPv6 DHCP, APIPA (Auto IP), WINS/NetBIOS, DNS Resolver, mDNS, SNMPv1/v2c/v3, ICMP, Web Services(Scan), HTTP/HTTPS server, LLMNR responder, SNTP Client, LDAP	Pallet gross height Master (outer) cases per pallet layer Harmonized System (HS) code	17.8 cm 8 pc(s) 84716070
IPv6 support	1		
Supported network protocols	DHCP, APIPA (Auto IP), WINS/NetBIOS, DNS Resolver, mDNS, SNMPv1/v2c/v3, ICMP, Web Services(Scan), HTTP/HTTPS server, LLMNR responder, SNTP Client, LDAP, RA, DNS Resolver, mDNS, LLMNR responder, Web Services(Scan), SNTP Client, HTTP/HTTPS server, ICMPv6		
Power			
Power supply type *	AC		





012502666349

0012502666349



4977766814638

Catalog Object Cloud



Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.