![brother at your side logo]

Brother ADS-4300N scanner ADF scanner 600 x 600 DPI A4 Black, White

Brand : Brother

Product name : ADS-4300N

Product code: ADS-4300N

- Scan up to 40 pages per minute
- 2-sided scan up to 40 pages per minute
- 80 sheet Automatic Document Feeder (ADF)
- Wired connectivity
- SuperSpeed USB3.
- Scan directly to USB host

With high-speed wired connectivity. Great choice for scanning documents to the network and collaborating with colleagues. Ideal for shared use in the office.

Brother ADS-4300N scanner ADF scanner 600 x 600 DPI A4 Black, White:

Designed for businesses needing a high-speed, efficient network scanner. Connect your ADS-4300N to your network and effortlessly capture your documents to share and collaborate with colleagues.3 configurable hot keysAdvanced image processing and batch scanningFeatures Ultrasonic Multifeed Sensor, Separation SwitchBrother Mobile Connect appSupports AirPrint ScanIncludes Brother ScanEssentials softwareDriver compatibility with TWAIN (Win and macOS), WIA, Linux SANE


Scanning

Optical scanning resolution *	600 x 600 DPI
Enhanced scan resolution	1200 x 1200 DPI
Colour scanning	✔
Duplex scanning *	✔
Input colour depth	48 bit
Output colour depth	24 bit
Output greyscale depth	8 bit
Greyscale levels	256
ADF scan speed (b/w, A4)	40 ppm
ADF scan speed (colour, A4)	40 ppm
Duplex ADF scan speed (b/w, A4)	80 ipm
Duplex ADF scan speed (colour, A4)	80 ipm

Design

Scanner type *	ADF scanner
Product colour *	Black, White
Control type	Buttons
Built-in display *	✘

Performance

Sensor type *	Dual CIS
Light source	LED
Scan file formats	JPEG, PDF, TIFF
Daily duty cycle (max) *	6000 pages
Maximum duty cycle	120000 pages per month
Scan to	FTP, Image, PC, SMB, USB
Scan drivers	ICA, SANE, TWAIN, WIA
Scanning noise level	59 dB

Power

Power consumption (typical)	24 W
Power consumption (standby)	6.8 W
Power consumption (off)	0.1 W
AC input frequency	50 - 60 Hz
Power consumption (sleep)	1.7 W
Output voltage	24 V
Output current	1.9 A

Weight & dimensions

Width	243 mm
Depth	320 mm
Height	391 mm
Weight	3.09 kg

Packaging data

Quantity per pack	1 pc(s)
Package width	391 mm
Package depth	320 mm
Package height	243 mm
Package weight	3.74 kg

Packaging content

Cables included	AC, USB

Sustainability

Sustainability compliance	✔

System requirements

Windows operating systems supported	✔
Mac operating systems supported	✔

Input capacity

Auto document feeder (ADF) input capacity	80 sheets

Paper handling

Scanning media types supported	Business Card, Plain paper, Plastic Card, Recycled paper, Thick paper, Thin paper
Maximum ISO A-series paper size *	A4
Card thickness (max)	1.1 mm
Paper tray media weight	40 - 200 g/m²
Auto Document Feeder (ADF) media weight	40 - 200 g/m²
Maximum scan width	21.6 cm
Maximum scan length	5 m

Ports & interfaces

USB port *	✔
USB version	2.0/3.2 Gen 1 (3.1 Gen 1)

Network

Ethernet LAN	✔
Security algorithms	EAP-FAST, EAP-MD5, EAP-TLS, EAP-TTLS, HTTPS, PEAP, SMTP-AUTH, SNMPv3, SSL/TLS
Supported network protocols (IPv6)	RA, DNS Resolver, mDNS, LLMNR responder, Web Services(Scan), SNTP Client, HTTP/HTTPS server, ICMPv6
Supported network protocols (IPv4)	DHCP, APIPA (Auto IP), WINS/NetBIOS, DNS Resolver, mDNS, SNMPv1/v2c/v3, ICMP, Web Services(Scan), HTTP/HTTPS server, LLMNR responder, SNTP Client, LDAP
IPv6 support	✔
Supported network protocols	DHCP, APIPA (Auto IP), WINS/NetBIOS, DNS Resolver, mDNS, SNMPv1/v2c/v3, ICMP, Web Services(Scan), HTTP/HTTPS server, LLMNR responder, SNTP Client, LDAP, RA, DNS Resolver, mDNS, LLMNR responder, Web Services(Scan), SNTP Client, HTTP/HTTPS server, ICMPv6

Power

Power supply type *	AC

System requirements

Linux operating systems supported	✔
Server operating systems supported	Windows Server 2012, Windows Server 2012 R2, Windows Server 2016, Windows Server 2019

Operational conditions

Operating temperature (T-T)	5 - 35 °C
Storage temperature (T-T)	-20 - 60 °C
Operating relative humidity (H-H)	20 - 80%
Storage relative humidity (H-H)	10 - 90%

Other features

Compliance certificates	RoHS
Spare part retention	5 year(s)
Certification	GS Mark ISIS WHQL KofaxTM 5,10 VRS Elite 5.2.0 Kofax Express 3.3.0

Technical details

Pallet type	800 x 1200 mm

Logistics data

Products per pallet	40 pc(s)
Country of origin	China
Master (outer) cases per pallet	40 pc(s)
Layers per pallet	5 pc(s)
Pallet gross weight	166.4 kg
Pallet gross height	17.8 cm
Master (outer) cases per pallet layer	8 pc(s)
Harmonized System (HS) code	84716070

0012502666349

012502666349

4977766814638

4977766814621

4977766814652

Catalog Object Cloud