



APC SMT750C uninterruptible power supply (UPS) Line-Interactive
0.75 kVA 500 W 6 AC outlet(s)

Brand : APC

Product code: SMT750C

Product name : SMT750C

Smart-UPS 750VA, LCD, 120V, with SmartConnect
APC SMT750C. UPS topology: Line-Interactive, Output power capacity: 0.75 kVA, Output power: 500 W.
AC outlet types: NEMA 5-15R, Power plug: NEMA 5-15P, AC outlets quantity: 6 AC outlet(s). Battery
technology: Sealed Lead Acid (VRLA), Battery life (max): 5 year(s), Battery recharge time: 3 h. Form
factor: Tower, Product colour: Black, Display type: LCD. Compliance certificates: RoHS, Certification:
CSA, CSA C22.2 No. 107.1, FCC Part 15 Class B, ICES-003, UL 1778, REACH



Features		Design	
UPS topology *	Line-Interactive	Form factor *	Tower
Output power capacity *	0.75 kVA	Product colour *	Black
Output power *	500 W	Display type	LCD
Waveform *	Sine	Operational conditions	
Input operation voltage (min) *	82 V	Operating temperature (T-T)	0 - 40 °C
Input operation voltage (max) *	144 V	Storage temperature (T-T)	-15 - 45 °C
Input frequency *	50/60 Hz	Operating relative humidity (H-H)	0 - 90%
Output operation voltage (min)	110 V	Storage relative humidity (H-H)	0 - 95%
Output operation voltage (max)	127 V	Operating altitude	0 - 3000 m
Output frequency	50/60 Hz	Non-operating altitude	0 - 15000 m
Surge energy rating	540 J	Certificates	
Hold time (min)	6 ms	Compliance certificates	RoHS
Hold time (max)	10 ms	Certification	CSA, CSA C22.2 No. 107.1, FCC Part 15 Class B, ICES-003, UL 1778, REACH
Noise level	41 dB	Packaging content	
Audible alarm(s)	✓	Cables included	USB cable
Web-based management	✓	Sustainability	
Audible alarm modes	Alarm when on battery, Low battery alarm	Sustainability certificates	ENERGY STAR
Ports & interfaces		Weight & dimensions	
AC outlet types	NEMA 5-15R	Width	138 mm
Power plug	NEMA 5-15P	Depth	369 mm
AC outlets quantity	6 AC outlet(s)	Height	161 mm
USB port	✓	Weight	12.5 kg
Serial interface	✓	Packaging data	
SmartSlot	✓	Resource CD	✓
Battery		Software CD	✓
Battery technology	Sealed Lead Acid (VRLA)		
Battery life (max)	5 year(s)		
Battery recharge time	3 h		

Battery		Packaging data	
Hot-swap battery	✓	Package width	278 mm
Automatic battery test	✓	Package depth	499 mm
Cold start	✓	Package height	301 mm
Replacement battery cartridge	RBC48	Package weight	14 kg
Logistics data			
		Products per pallet	24 pc(s)
Other features			
		Output voltage	120 V



0731304325451



731304325451

Catalog Object Cloud



Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.