HP Jetdirect 2800w NFC/Wireless Direct Accessory

M

Activate wireless printing from mobile devices.



Just go and print

- Print on the move with wireless direct printing use your smartphone, tablet or laptop to select a JetDirect enabled printer.
- Move between offices and still have access to mobile printing.

Get convenient mobile printing at a touch

- Enable touch-to-print convenience. The HP JetDirect 2800w works with NFC-capable devices through a peer-to-peer connection³.
- Simply touch an HP JetDirect-enabled printer or MFP with a mobile device to start printing³.

Go mobile and stay secure

- Keep your network out of reach: The HP Jetdirect 2800w supports wireless direct printing and touch-to-print using NFC-capable devices^{2,3}.
- The peer-to-peer connection allows mobile users to print without accessing the company network.

Mobility meets manageability

- Easily manage the HP Jetdirect 2800w across your entire fleet through HP Web Jetadmin⁴.
- Turn wireless printing capabilities on and off and add a pass phrase using one interface.

²Mobile device needs to be connected directly to the wi-fi network of a wireless direct-capable printer prior to printing. Depending on mobile device, an app or driver may also be required. Wireless performance is dependent upon physical environment and distance from the access point in the printer.

Mobile device must support near field communications—enabled printing (NFC), currently compatible with HP ElitePad and Samsung galaxy Note 3. For more information, see hp.com/go/mobileprinting. 4HP Web Jetadmin is free and available for download at hp.com/go/webjetadmin.

HP Jetdirect 2800w NFC/Wireless Direct Accessory

Technical specifications

J8029A	Installation Poster; HP J8029A 2800w; Warranty cards; 2 mini-USB cables
Compatibility	
Operating systems	Windows Server 2008, Windows 2008 64-bit, Windows 7, Windows Vista, Windows Vista 64-bit, Windows XP, Windows XP 64-bit, Windows Server 2003, Windows 2003 64-bit, Mac OS X v10.2, v10.3, v10.4 or higher, Novell 5.1 or higher, RED HAT Linux 7.x or higher, SUSE Linux 8.x or higher, HP-UX 10.20, 11.x, 11.i, Solaris® 2.5 or higher (SPARC® systems only), IBM® AIX 3.2.5 or higher 1, MPE-iX, Citrix® Presentation Server, Windows Terminal Services
Printer supported	HP LaserJet M806, M830, M880, M855, M525, M575, M551, M601, M602, M603, M775, M712 and M725 Series
Browsers supported	Internet Explorer 6.0 or higher; Mozilla 2.x or higher; Firefox 2.x or higher; Safari; Chrome
Connectivity	
Interfaces (standard)	Hi-Speed USB 2.0; 802.11b/g Wireless; NFC
Environmental ranges	
Operating temperature	0 to 40° C
Storage temperature	-40 to 70º C
Operating humidity	15 to 95% RH
Storage humidity	15 to 95% RH
Print Server Specifications	
Network types	Wireless LAN (802.11 b/g)
Print server type	External, HIP (Hardware Integration Pocket)
Embedded Web Server	Yes
Install, configure, and manage with HP Web Jetadmin	No
Upgradeable firmware	Yes
Security management description	Management security: SNMPv3, SSL/TLS (HTTPS); Wireless network security: WPA2-Personal (WPA2-AES); Administrator password
Dimensions (w x d x h)	
Product dimensions	98 x 74 x 21 mm
Packaged	224 x 152 x 58 mm
Weight	
Product weight	0.08 kg
Packaged	0.27 kg
Power consumption	
Maximum	2.5 watts (maximum)
Power requirements	Host USB powered accessory, Input Voltage: 5 V, 500 mA
Power supply type	None (USB bus driven)
Certification	
Safety	EU (Low Voltage Directive 2006/95/EC), EN 60950-1:2006 + A11:2009 + A1:2010 + A12:2011
Electromagnetic	EU (EMC Directive 2004/108/EC) EN 301 489-1 V1.9.2, EN 489-3 V1.4.1, EN 489-17 V2.1.1
Warranty	
	One-year, limited warranty; product exchange. Warranty and support options vary by product, country and local legal requirements.