QNAP

QNAP ES1686DC NAS Rack (3U) Intel® Xeon® D D-2142IT 64 GB DDR4 0 TB QNAP Enterprise System Black

Brand: QNAP Product code: ES1686DC-2142IT-128G-CA

Product name : ES1686DC







Stavana		Daufaumanaa	
Storage		Performance	
Storage drive capacity *	0 GB	Snapshot	1
Supported storage drive interfaces	Serial ATA III, Serial Attached SCSI (SAS)	Web-based management	✓
Storage drive sizes supported	2.5,3.5"	Security algorithms	256-bit AES, FIPS 140-2, HTTPS, SSH, SSL/TLS
Number of M.2 (M & B) slots	2	Access Control List (ACL)	✓
RAID support *	1	Reset button	/
RAID levels	0, 1, 5, 6, 10, 50, 60	On/off switch	1
Hot-swap drive bays	✓	Built-in FTP server	1
Supported file systems	ZFS	Dullell I I Server	
Storage drives installed * Total installed storage capacity *	X 0 TB	Browser supported	Apple Safari, Google Chrome, Microsoft Internet Explorer, Mozilla Firefox
Number of storage drives supported	10	Hot spare	1
*	16	S.M.A.R.T. support	1
Supported storage drive types *	HDD & SSD		
Processor		Software	
Processor manufacturer *	Intel	Operating system installed *	QNAP Enterprise System
Processor family *	Intel® Xeon® D	Windows operating systems supported	Windows 10, Windows 7, Windows 8
Processor model *	D-2142IT	Linux operating systems supported	✓
Processor frequency *	1.9 GHz	. 5,	•
Processor boost frequency	3 GHz	Mac operating systems supported	Windows Comercia 2000 B2 Windows
Processor cores	8	Server operating systems supported	Windows Server 2008 R2, Windows Server 2012, Windows Server 2012
Processor threads	16		R2, Windows Server 2016
Processor cache	11 MB	Power	
Bus type	UPI	Power supply location	Built-in
CPU configuration (max)	1	Power supply unit (PSU) capacity	770 W
PCI Express slots version	3.0	Number of power supply units	1
Processor code	SR3ZZ	Redundant power supply (RPS)	,
Processor codename	Skylake	support	✓
Processor lithography	14 nm	Power consumption (typical)	500.87 W
Processor operating modes	64-bit BGA 2518	AC input voltage	90 - 264 V
Processor socket	1S	Fan voltage	12 V
Scalability Stepping	M1	Weight & dimensions	
Thermal Design Power (TDP)	65 W	Width *	483.1 mm
Maximum internal memory		Depth *	630.6 mm
supported by processor	512 GB	Height *	132 mm

D		De also sinos contro d	
Processor		Packaging content	
Conflict-Free processor	V	Cables included	AC, LAN (RJ-45)
Memory		Quick installation guide	/
Internal memory *	64 GB	Rack mount kit	/
Internal memory type	DDR4	Number of screws	128
Maximum RAM supported	512 GB	Processor special features	
Memory slots	8	Embedded options available	✓
Memory form factor Flash memory	RDIMM/LRDIMM 4000 MB	Enhanced Intel SpeedStep Technology	✓
Network		Execute Disable Bit	✓
Ethernet LAN *	✓	Idle States	✓
Ethernet LAN data rates	1000,10000 Mbit/s	Intel 64	✓
Ethernet LAN data rate supported		Intel Enhanced Halt State	✓
(max)	10000 Mbit/s	Intel QuickAssist Technology	×
Wi-Fi	×	Intel Secure Key Technology version	1.00
Jumbo frames support	✓	Intel Trusted Execution Technology	✓
iSCSI support	✓	Intel TSX-NI	✓
Wake-on-LAN ready	✓	Intel TSX-NI version	1.00
Supported network protocols	TCP/IP, IPv4, IPv6, CIFS/SMB2/SMB3, NFS v3/NFS v4, FTP, FTPS, TFTP,	Intel Virtualization Technology (VT-x)	•
	HTTP, HTTPS, SSH, iSCSI, SNMP, SMTP, SMSC	Intel Virtualization Technology for Directed I/O (VT-d)	/
Link aggregation Ports & interfaces	✓	Intel VT-x with Extended Page Tables (EPT)	/
	1	Intel® AES New Instructions (Intel®	1
USB port * USB 3.2 Gen 1 (3.1 Gen 1) Type-A	·	AES-NI)	
ports quantity	2	Intel® Hyper Threading Technology (Intel® HT Technology)	✓
Fiber ports quantity	4	Intel® OS Guard	✓
Fiber optic connector	SFP+	Intel® Secure Key	✓
Ethernet LAN (RJ-45) ports *	3	Intel® Turbo Boost Technology	2.0
PCI Express x8 (Gen 3.x) slots Design	2	Maximum number of PCI Express lanes	32
Chassis type *	Rack (3U)	Thermal Monitoring Technologies	1
Cooling type *	Active	Memory types supported by processor	DDR4-SDRAM
Product colour Number of fans	Black 3 fan(s)	Operational conditions	
Fan diameter	6 cm	Operating temperature (T-T)	0 - 40 °C
LED indicators	✓	Operating relative humidity (H-H)	5 - 95%
Performance		Other features	
Type * Device class *	NAS Large Enterprise Business	Certification	FCC A (USA) CE (EN55022 A, EN55024) EN60950 BSMI VCCI CB LVD
Backup function * Backup features Multilingual support	✓ Cloud, iSCSI LUN	Processor ARK ID	136432
Noise level	55.8 dB		

Catalog Object Cloud



Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.