## Samsung LH55QMBTBGCXZA Signage Display Interactive flat panel 139.7 cm (55") Wi-Fi 400 cd/m² 4K Ultra HD Black Touchscreen 24/7

Brand : Samsung Product code: LH55QMBTBGCXZA

**Product name:** LH55QMBTBGCXZA

- All-in-one touch solution wiht Tizen
- UHD resolution
- Non-glare display

55", 3840 x 2160, VA, 92% DCI-P3, 48  $\sim$  75 kHz, 30  $\sim$  81 kHz, 200 x 200 mm, 26.9 kg Samsung LH55QMBTBGCXZA. Product design: Interactive flat panel. Display diagonal: 139.7 cm (55"), Display resolution: 3840 x 2160 pixels, Display brightness: 400 cd/m², HD type: 4K Ultra HD, Touchscreen. Wi-Fi. Operating hours (hours/days): 24/7. Product colour: Black





Display		Design	
Panel type  Display diagonal *  Display resolution *  Display brightness *  HD type *  Touchscreen *  Touchscreen technology  Contrast ratio (typical)  Viewing angle, horizontal  Pixel pitch  VA  139.7 cm (55")  3840 x 2160 pixels  400 cd/m²  4K Ultra HD  Capacitive  Capacitive  4000:1  178°  Viewing angle, vertical  178°  Pixel pitch  0.315 x 0.315 mm	139.7 cm (55") 3840 x 2160 pixels 400 cd/m <sup>2</sup>	Placement supported * Product colour * VESA mounting * Panel mounting interface Anti-glare screen	Indoor Black ✓ 200 x 200 mm
	Capacitive 4000:1 178° 178°	Performance Purpose * Operating hours (hours/days) HDCP HDCP version	Universal 24/7 ✓ 2.2
Horizontal scan range	30 - 81 kHz	Power	
Vertical scan range Haze rate	48 - 75 Hz 25%	Power consumption (typical) * Power consumption (sleep)	143 W 0.5 W
Ports & interfaces		AC input voltage	100 - 240 V
HDMI ports quantity * HDMI version HDMI input ports quantity	3 2.0 3	AC input frequency Weight & dimensions Display width	50 - 60 Hz 1253.8 mm
DVI port * X DisplayPorts quantity * 1 USB port *	1	Display depth Display height Display weight	56.7 mm 734.6 mm 26.9 kg
Ethernet LAN *	•	Packaging data	
Wi-Fi * RS-232 interface	<b>,</b>	Package width Package depth	1421 mm 165 mm
Audio Built-in speaker(s) *	×	Package height Package volume	884 mm 32500 cm³
·	^	Operational conditions	
<b>Design</b> Product design *	Interactive flat panel	Operating temperature (T-T) Operating relative humidity (H-H)	0 - 40 °C 10 - 80%

## **Catalog Object Cloud**



Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.